

Potential Flow Forces and Moments from Selected Ship Flow Codes in a Set of Numerical Experiments

Appendix K — Minimum and Maximum Plots for Prescribed Heave Motion of Model 5613

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 01 MAY 2008		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Potential Flow Forces and Moments from Selected Ship Flow Codes in a Set of Numerical Experiments Appendix K Minimum and Maximum Plots for Prescribed Heave Motion of Model 5613				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center Carderock Division 9500 Macarthur Boulevard West Bethesda, MD 20817-5700				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM002134. Potential Flow Forces and Moments from Selected Ship Flow Codes in a Set of Numerical Experiments					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 341	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Contents

	<i>Page</i>
Figures	K-2
Tables	K-6
Introduction	K-41

Figures

	<i>Page</i>
K-1. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-42
K-2. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-47
K-3. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-52
K-4. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-57
K-5. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-62
K-6. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-67
K-7. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-72
K-8. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-77
K-9. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-82
K-10. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-87
K-11. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-92

TASK 1/HEAVE MOTION/MODEL 5613

- K-12. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-97
- K-13. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-102
- K-14. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-107
- K-15. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-112
- K-16. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-117
- K-17. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-122
- K-18. Minimum and maximum of filtered $(F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-127
- K-19. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-132
- K-20. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-137
- K-21. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-142
- K-22. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-147
- K-23. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-152
- K-24. Minimum and maximum of filtered $(M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-157
- K-25. Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m. K-162

TASK 1/HEAVE MOTION/MODEL 5613

K-26.	Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-167
K-27.	Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-172
K-28.	Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-177
K-29.	Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-182
K-30.	Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-187
K-31.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-192
K-32.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-197
K-33.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-202
K-34.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-207
K-35.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-212
K-36.	Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-217
K-37.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-222
K-38.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-227
K-39.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-232

TASK 1/HEAVE MOTION/MODEL 5613

K-40.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-237
K-41.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-242
K-42.	Minimum and maximum of filtered $(M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-247
K-43.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-252
K-44.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-257
K-45.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-262
K-46.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-267
K-47.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-272
K-48.	Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-277
K-49.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-282
K-50.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-287
K-51.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-292
K-52.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-297
K-53.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-302

TASK 1/HEAVE MOTION/MODEL 5613

K-54.	Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-307
K-55.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-312
K-56.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-317
K-57.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-322
K-58.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-327
K-59.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-332
K-60.	Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.	K-337

Tables

	<i>Page</i>
K-1. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-43
K-2. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-43
K-3. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-44
K-4. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-44
K-5. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-45
K-6. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-45

TASK 1/HEAVE MOTION/MODEL 5613

K-7.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-46
K-8.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)	K-46
K-9.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-48
K-10.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-48
K-11.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-49
K-12.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-49
K-13.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-50
K-14.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-50
K-15.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-51
K-16.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)	K-51
K-17.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-53
K-18.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-53
K-19.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-54
K-20.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-54

TASK 1/HEAVE MOTION/MODEL 5613

K-21.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-55
K-22.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-55
K-23.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-56
K-24.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)	K-56
K-25.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-58
K-26.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-58
K-27.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-59
K-28.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-59
K-29.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-60
K-30.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-60
K-31.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-61
K-32.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)	K-61
K-33.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-63
K-34.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-63

TASK 1/HEAVE MOTION/MODEL 5613

K-35.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-64
K-36.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-64
K-37.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-65
K-38.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-65
K-39.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-66
K-40.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)	K-66
K-41.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-68
K-42.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-68
K-43.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-69
K-44.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-69
K-45.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-70
K-46.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-70
K-47.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-71
K-48.	Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)	K-71

TASK 1/HEAVE MOTION/MODEL 5613

- K-49. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-73
- K-50. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-73
- K-51. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-74
- K-52. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-74
- K-53. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-75
- K-54. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-75
- K-55. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-76
- K-56. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-76
- K-57. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-78
- K-58. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-78
- K-59. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-79
- K-60. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-79
- K-61. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-80
- K-62. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-80

TASK 1/HEAVE MOTION/MODEL 5613

- K-63. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-81
- K-64. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-81
- K-65. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-83
- K-66. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-83
- K-67. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-84
- K-68. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-84
- K-69. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-85
- K-70. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-85
- K-71. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-86
- K-72. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-86
- K-73. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-88
- K-74. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-88
- K-75. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-89
- K-76. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-89

TASK 1/HEAVE MOTION/MODEL 5613

- K-77. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-90
- K-78. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-90
- K-79. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-91
- K-80. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-91
- K-81. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-93
- K-82. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-93
- K-83. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-94
- K-84. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-94
- K-85. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-95
- K-86. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-95
- K-87. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-96
- K-88. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-96
- K-89. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-98
- K-90. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-98

TASK 1/HEAVE MOTION/MODEL 5613

- K-91. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-99
- K-92. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-99
- K-93. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-100
- K-94. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-100
- K-95. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-101
- K-96. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-101
- K-97. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-103
- K-98. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-103
- K-99. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-104
- K-100. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-104
- K-101. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-105
- K-102. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-105
- K-103. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-106
- K-104. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-106

TASK 1/HEAVE MOTION/MODEL 5613

- K-105. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-108
- K-106. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-108
- K-107. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-109
- K-108. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-109
- K-109. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-110
- K-110. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-110
- K-111. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-111
- K-112. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-111
- K-113. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-113
- K-114. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-113
- K-115. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-114
- K-116. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-114
- K-117. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-115
- K-118. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-115

TASK 1/HEAVE MOTION/MODEL 5613

- K-119. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-116
- K-120. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-116
- K-121. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-118
- K-122. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-118
- K-123. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-119
- K-124. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-119
- K-125. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-120
- K-126. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-120
- K-127. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-121
- K-128. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-121
- K-129. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-123
- K-130. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-123
- K-131. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-124
- K-132. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-124

TASK 1/HEAVE MOTION/MODEL 5613

- K-133. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 0.3831 \text{ rad/s}, F_n = 0.3$) K-125
- K-134. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 0.3831 \text{ rad/s}, F_n = 0.3$) K-125
- K-135. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L =$
 $154 \text{ m}, \omega = 0.3831 \text{ rad/s}, F_n = 0.3$) K-126
- K-136. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 0.3831 \text{ rad/s}, F_n = 0.3$) K-126
- K-137. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-128
- K-138. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-128
- K-139. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-129
- K-140. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-129
- K-141. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-130
- K-142. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-130
- K-143. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L =$
 $154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-131
- K-144. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 1.1000 \text{ rad/s}, F_n = 0.3$) K-131
- K-145. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 0.2079 \text{ rad/s}, F_n = 0.0$) K-133
- K-146. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
 $L = 154 \text{ m}, \omega = 0.2079 \text{ rad/s}, F_n = 0.0$) K-133

TASK 1/HEAVE MOTION/MODEL 5613

- [illegible]

TASK 1/HEAVE MOTION/MODEL 5613

- [illegible]

TASK 1/HEAVE MOTION/MODEL 5613

- K-175. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-151
- K-176. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-151
- K-177. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-153
- K-178. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-153
- K-179. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-154
- K-180. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-154
- K-181. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-155
- K-182. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-155
- K-183. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-156
- K-184. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-156
- K-185. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-158
- K-186. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-158
- K-187. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-159
- K-188. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-159

TASK 1/HEAVE MOTION/MODEL 5613

- K-189. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-160
- K-190. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-160
- K-191. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-161
- K-192. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-161
- K-193. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-163
- K-194. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-163
- K-195. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-164
- K-196. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-164
- K-197. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-165
- K-198. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-165
- K-199. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-166
- K-200. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-166
- K-201. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-168
- K-202. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-168

TASK 1/HEAVE MOTION/MODEL 5613

- K-203. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-169
- K-204. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-169
- K-205. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-170
- K-206. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-170
- K-207. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-171
- K-208. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-171
- K-209. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-173
- K-210. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-173
- K-211. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-174
- K-212. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-174
- K-213. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-175
- K-214. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-175
- K-215. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-176
- K-216. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-176

TASK 1/HEAVE MOTION/MODEL 5613

- K-217. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-178
- K-218. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-178
- K-219. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-179
- K-220. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-179
- K-221. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-180
- K-222. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-180
- K-223. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-181
- K-224. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-181
- K-225. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-183
- K-226. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-183
- K-227. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-184
- K-228. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-184
- K-229. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-185
- K-230. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-185

TASK 1/HEAVE MOTION/MODEL 5613

- K-231. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-186
- K-232. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-186
- K-233. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-188
- K-234. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-188
- K-235. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-189
- K-236. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-189
- K-237. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-190
- K-238. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-190
- K-239. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-191
- K-240. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-191
- K-241. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-193
- K-242. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-193
- K-243. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-194
- K-244. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-194

TASK 1/HEAVE MOTION/MODEL 5613

- K-245. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-195
- K-246. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-195
- K-247. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-196
- K-248. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-196
- K-249. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-198
- K-250. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-198
- K-251. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-199
- K-252. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-199
- K-253. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-200
- K-254. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-200
- K-255. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-201
- K-256. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-201
- K-257. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-203
- K-258. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-203

TASK 1/HEAVE MOTION/MODEL 5613

- K-259. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-204
- K-260. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-204
- K-261. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-205
- K-262. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-205
- K-263. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-206
- K-264. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-206
- K-265. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-208
- K-266. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-208
- K-267. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-209
- K-268. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-209
- K-269. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-210
- K-270. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-210
- K-271. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-211
- K-272. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-211

TASK 1/HEAVE MOTION/MODEL 5613

- K-273. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-213
- K-274. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-213
- K-275. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-214
- K-276. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-214
- K-277. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-215
- K-278. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-215
- K-279. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-216
- K-280. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-216
- K-281. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-218
- K-282. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-218
- K-283. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-219
- K-284. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-219
- K-285. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-220
- K-286. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-220

TASK 1/HEAVE MOTION/MODEL 5613

- K-287. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-221
- K-288. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-221
- K-289. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-223
- K-290. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-223
- K-291. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-224
- K-292. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-224
- K-293. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-225
- K-294. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-225
- K-295. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-226
- K-296. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-226
- K-297. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-228
- K-298. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-228
- K-299. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-229
- K-300. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-229

TASK 1/HEAVE MOTION/MODEL 5613

- K-301. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-230
- K-302. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-230
- K-303. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-231
- K-304. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-231
- K-305. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-233
- K-306. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-233
- K-307. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-234
- K-308. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-234
- K-309. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-235
- K-310. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-235
- K-311. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-236
- K-312. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-236
- K-313. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-238
- K-314. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-238

TASK 1/HEAVE MOTION/MODEL 5613

- K-315. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-239
- K-316. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-239
- K-317. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-240
- K-318. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-240
- K-319. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-241
- K-320. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-241
- K-321. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-243
- K-322. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-243
- K-323. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-244
- K-324. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-244
- K-325. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-245
- K-326. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-245
- K-327. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-246
- K-328. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-246

TASK 1/HEAVE MOTION/MODEL 5613

- K-329. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-248
- K-330. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-248
- K-331. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-249
- K-332. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-249
- K-333. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-250
- K-334. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-250
- K-335. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-251
- K-336. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-251
- K-337. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-253
- K-338. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-253
- K-339. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-254
- K-340. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-254
- K-341. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-255
- K-342. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-255

TASK 1/HEAVE MOTION/MODEL 5613

- K-343. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-256
- K-344. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-256
- K-345. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-258
- K-346. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-258
- K-347. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-259
- K-348. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-259
- K-349. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-260
- K-350. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-260
- K-351. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-261
- K-352. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-261
- K-353. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-263
- K-354. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-263
- K-355. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-264
- K-356. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-264

TASK 1/HEAVE MOTION/MODEL 5613

- K-357. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-265
- K-358. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-265
- K-359. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-266
- K-360. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-266
- K-361. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-268
- K-362. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-268
- K-363. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-269
- K-364. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-269
- K-365. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-270
- K-366. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-270
- K-367. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-271
- K-368. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-271
- K-369. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-273
- K-370. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-273

TASK 1/HEAVE MOTION/MODEL 5613

- K-371. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-274
- K-372. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-274
- K-373. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-275
- K-374. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-275
- K-375. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-276
- K-376. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-276
- K-377. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-278
- K-378. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-278
- K-379. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-279
- K-380. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-279
- K-381. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-280
- K-382. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-280
- K-383. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-281
- K-384. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-281

TASK 1/HEAVE MOTION/MODEL 5613

- K-385. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-283
- K-386. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-283
- K-387. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-284
- K-388. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-284
- K-389. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-285
- K-390. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-285
- K-391. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-286
- K-392. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-286
- K-393. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-288
- K-394. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-288
- K-395. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-289
- K-396. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-289
- K-397. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-290
- K-398. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-290

TASK 1/HEAVE MOTION/MODEL 5613

- K-399. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-291
- K-400. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-291
- K-401. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-293
- K-402. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-293
- K-403. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-294
- K-404. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-294
- K-405. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-295
- K-406. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-295
- K-407. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-296
- K-408. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-296
- K-409. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-298
- K-410. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-298
- K-411. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-299
- K-412. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-299

TASK 1/HEAVE MOTION/MODEL 5613

- K-413. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-300
- K-414. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-300
- K-415. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-301
- K-416. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-301
- K-417. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-303
- K-418. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-303
- K-419. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-304
- K-420. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-304
- K-421. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-305
- K-422. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-305
- K-423. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-306
- K-424. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-306
- K-425. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-308
- K-426. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-308

TASK 1/HEAVE MOTION/MODEL 5613

- K-427. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-309
- K-428. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-309
- K-429. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-310
- K-430. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-310
- K-431. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-311
- K-432. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-311
- K-433. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-313
- K-434. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-313
- K-435. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-314
- K-436. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-314
- K-437. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-315
- K-438. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-315
- K-439. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-316
- K-440. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$) K-316

TASK 1/HEAVE MOTION/MODEL 5613

- K-441. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-318
- K-442. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-318
- K-443. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-319
- K-444. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-319
- K-445. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-320
- K-446. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-320
- K-447. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-321
- K-448. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$) K-321
- K-449. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-323
- K-450. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-323
- K-451. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-324
- K-452. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-324
- K-453. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-325
- K-454. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a / T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-325

TASK 1/HEAVE MOTION/MODEL 5613

- K-455. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-326
- K-456. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$) K-326
- K-457. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-328
- K-458. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-328
- K-459. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-329
- K-460. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-329
- K-461. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-330
- K-462. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-330
- K-463. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-331
- K-464. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$) K-331
- K-465. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-333
- K-466. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-333
- K-467. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-334
- K-468. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-334

TASK 1/HEAVE MOTION/MODEL 5613

- K-469. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-335
- K-470. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-335
- K-471. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-336
- K-472. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$) K-336
- K-473. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-338
- K-474. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-338
- K-475. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-339
- K-476. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-339
- K-477. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-340
- K-478. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-340
- K-479. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L =
154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-341
- K-480. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$
for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to
L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$) K-341

Introduction

This appendix contains plots and tables related to the minimum and maximum value of each variable versus the nondimensional heave amplitude z_a/T for the prescribed heave motion of Model 5514 in task 1. The plots are found in Figures K–1 through K–60. For each variable, speed, and frequency there is one plot that depicts the results from all the codes. If f stands for a time-dependent variable, then the quantities plotted are the minimum and maximum of

$$f^* \equiv \frac{f - \langle f \rangle}{z_a/T}$$

where $\langle f \rangle$ is the mean. Only filtered values f are used since filtered values lessen the impact of spikes that probably originate in numerical filtering schemes in the codes. Linear variation as a function of the amplitude appears as a horizontal line. Quadratic variation appears as a straight line with a nonzero slope.

Tables K–1 through K–480 in this appendix correspond to the plots. Following each plot is one table for each of the eight codes for which data were received. The tables give information about the mean, the minimum and maximum of the unfiltered variable, the minimum and maximum of the filtered variable, and the starred function depicted in the figure.

For the corresponding time history plots, the reader is referred to Appendix B.

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-1. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-1. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.82E-07	-0.275	0.275	-0.275	0.275	-5.49	5.50
.10	-3.78E-07	-0.550	0.550	-0.549	0.550	-5.49	5.50
.20	-7.22E-07	-1.10	1.10	-1.10	1.10	-5.49	5.50
.40	-1.62E-06	-2.20	2.20	-2.20	2.20	-5.49	5.50
.80	-3.05E-06	-4.40	4.40	-4.40	4.40	-5.49	5.50

Table K-2. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.82E-07	-0.275	0.275	-0.275	0.275	-5.49	5.50
.10	-3.78E-07	-0.550	0.550	-0.549	0.550	-5.49	5.50
.20	-7.22E-07	-1.10	1.10	-1.10	1.10	-5.49	5.50
.40	-1.62E-06	-2.20	2.20	-2.20	2.20	-5.49	5.50
.80	-3.05E-06	-4.40	4.40	-4.40	4.40	-5.49	5.50

Table K-3. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.18E-08	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-9.58E-08	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.75E-07	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-3.96E-07	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-9.35E-07	-4.40	4.40	-4.40	4.40	-5.49	5.49

Table K-4. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

Table K-5. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

Table K-6. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

TASK 1/HEAVE MOTION/MODEL 5613

Table K-7. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-8. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	2.93E-08	-0.275	0.275	-0.272	0.272	-5.45	5.45
.10	6.32E-08	-0.550	0.550	-0.545	0.545	-5.45	5.45
.20	1.29E-07	-1.10	1.10	-1.09	1.09	-5.45	5.45
.40	2.39E-07	-2.20	2.20	-2.18	2.18	-5.45	5.45
.80	2.05E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-2. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–9. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	1.38E-08	-0.275	0.275	-0.274	0.276	-5.48	5.52
.10	7.26E-09	-0.550	0.550	-0.548	0.552	-5.48	5.52
.20	2.27E-08	-1.10	1.10	-1.10	1.10	-5.48	5.52
.40	3.01E-08	-2.20	2.20	-2.19	2.21	-5.48	5.52
.80	5.34E-08	-4.40	4.40	-4.38	4.41	-5.48	5.52

Table K–10. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	1.38E-08	-0.275	0.275	-0.274	0.276	-5.48	5.52
.10	7.26E-09	-0.550	0.550	-0.548	0.552	-5.48	5.52
.20	2.27E-08	-1.10	1.10	-1.10	1.10	-5.48	5.52
.40	3.01E-08	-2.20	2.20	-2.19	2.21	-5.48	5.52
.80	5.34E-08	-4.40	4.40	-4.38	4.41	-5.48	5.52

Table K–11. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.63E-08	-0.275	0.275	-0.274	0.274	-5.48	5.48
.10	-4.38E-08	-0.550	0.550	-0.548	0.548	-5.48	5.48
.20	-1.05E-07	-1.10	1.10	-1.10	1.10	-5.48	5.48
.40	-1.66E-07	-2.20	2.20	-2.19	2.19	-5.48	5.48
.80	-2.70E-07	-4.40	4.40	-4.38	4.38	-5.48	5.48

Table K–12. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–13. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–14. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–15. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–16. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	5.12E-09	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	1.96E-08	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	4.58E-08	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-3.34E-08	-2.20	2.20	-2.18	2.18	-5.44	5.44
.80	4.96E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-3. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–17. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-2.91E-07	-0.275	0.275	-0.266	0.268	-5.33	5.37
.10	-5.71E-07	-0.550	0.550	-0.533	0.537	-5.33	5.37
.20	-1.21E-06	-1.10	1.10	-1.07	1.07	-5.33	5.37
.40	-2.33E-06	-2.20	2.20	-2.13	2.15	-5.33	5.37
.80	-4.73E-06	-4.40	4.40	-4.26	4.29	-5.33	5.37

Table K–18. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-2.91E-07	-0.275	0.275	-0.266	0.268	-5.33	5.37
.10	-5.71E-07	-0.550	0.550	-0.533	0.537	-5.33	5.37
.20	-1.21E-06	-1.10	1.10	-1.07	1.07	-5.33	5.37
.40	-2.33E-06	-2.20	2.20	-2.13	2.15	-5.33	5.37
.80	-4.73E-06	-4.40	4.40	-4.26	4.29	-5.33	5.37

Table K–19. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.43E-08	-0.275	0.275	-0.266	0.266	-5.33	5.33
.10	-1.21E-07	-0.549	0.550	-0.533	0.533	-5.33	5.33
.20	-2.64E-07	-1.10	1.10	-1.07	1.07	-5.33	5.33
.40	-4.83E-07	-2.20	2.20	-2.13	2.13	-5.33	5.33
.80	-9.56E-07	-4.39	4.40	-4.26	4.26	-5.33	5.33

Table K–20. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–21. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–22. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–23. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–24. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.04E-08	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.84E-08	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-4.64E-08	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-3.47E-08	-2.20	2.20	-2.18	2.18	-5.44	5.44
.80	-4.82E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-4. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–25. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.82E-07	-0.275	0.275	-0.275	0.275	-5.49	5.50
.10	-3.78E-07	-0.550	0.550	-0.549	0.550	-5.49	5.50
.20	-7.22E-07	-1.10	1.10	-1.10	1.10	-5.49	5.50
.40	-1.62E-06	-2.20	2.20	-2.20	2.20	-5.49	5.50
.80	-3.05E-06	-4.40	4.40	-4.40	4.40	-5.49	5.50

Table K–26. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.82E-07	-0.275	0.275	-0.275	0.275	-5.49	5.50
.10	-3.78E-07	-0.550	0.550	-0.549	0.550	-5.49	5.50
.20	-7.22E-07	-1.10	1.10	-1.10	1.10	-5.49	5.50
.40	-1.62E-06	-2.20	2.20	-2.20	2.20	-5.49	5.50
.80	-3.05E-06	-4.40	4.40	-4.40	4.40	-5.49	5.50

Table K–27. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.18E-08	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-9.58E-08	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.75E-07	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-3.96E-07	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-9.35E-07	-4.40	4.40	-4.40	4.40	-5.49	5.49

Table K–28. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

Table K–29. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

Table K–30. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.97E-07	-0.275	0.275	-0.275	0.275	-5.50	5.50
.10	-4.35E-07	-0.550	0.550	-0.550	0.550	-5.50	5.50
.20	-7.49E-07	-1.10	1.10	-1.10	1.10	-5.50	5.50
.40	-1.22E-06	-2.20	2.20	-2.20	2.20	-5.50	5.50
.80	-2.70E-06	-4.40	4.40	-4.40	4.40	-5.50	5.50

Table K–31. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–32. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	2.93E-08	-0.275	0.275	-0.272	0.272	-5.45	5.45
.10	6.32E-08	-0.550	0.550	-0.545	0.545	-5.45	5.45
.20	1.29E-07	-1.10	1.10	-1.09	1.09	-5.45	5.45
.40	2.39E-07	-2.20	2.20	-2.18	2.18	-5.45	5.45
.80	2.05E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-5. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–33. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	1.38E-08	-0.275	0.275	-0.274	0.276	-5.48	5.52
.10	7.26E-09	-0.550	0.550	-0.548	0.552	-5.48	5.52
.20	2.27E-08	-1.10	1.10	-1.10	1.10	-5.48	5.52
.40	3.01E-08	-2.20	2.20	-2.19	2.21	-5.48	5.52
.80	5.34E-08	-4.40	4.40	-4.38	4.41	-5.48	5.52

Table K–34. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	1.38E-08	-0.275	0.275	-0.274	0.276	-5.48	5.52
.10	7.26E-09	-0.550	0.550	-0.548	0.552	-5.48	5.52
.20	2.27E-08	-1.10	1.10	-1.10	1.10	-5.48	5.52
.40	3.01E-08	-2.20	2.20	-2.19	2.21	-5.48	5.52
.80	5.34E-08	-4.40	4.40	-4.38	4.41	-5.48	5.52

Table K–35. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.63E-08	-0.275	0.275	-0.274	0.274	-5.48	5.48
.10	-4.38E-08	-0.550	0.550	-0.548	0.548	-5.48	5.48
.20	-1.05E-07	-1.10	1.10	-1.10	1.10	-5.48	5.48
.40	-1.66E-07	-2.20	2.20	-2.19	2.19	-5.48	5.48
.80	-2.70E-07	-4.40	4.40	-4.38	4.38	-5.48	5.48

Table K–36. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–37. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–38. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-3.95E-07	-0.275	0.275	-0.275	0.275	-5.49	5.49
.10	-6.99E-07	-0.550	0.550	-0.549	0.549	-5.49	5.49
.20	-1.33E-06	-1.10	1.10	-1.10	1.10	-5.49	5.49
.40	-2.90E-06	-2.20	2.20	-2.20	2.20	-5.49	5.49
.80	-6.32E-06	-4.40	4.40	-4.39	4.39	-5.49	5.49

Table K–39. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	4.13E-03	-1.10	1.10	-1.09	1.09	-5.48	5.44
.40	8.27E-03	-2.20	2.20	-2.19	2.19	-5.48	5.44
.80	1.65E-02	-4.40	4.40	-4.37	4.37	-5.48	5.44

Table K–40. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	5.12E-09	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	1.96E-08	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	4.58E-08	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-3.34E-08	-2.20	2.20	-2.18	2.18	-5.44	5.44
.80	4.96E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-6. Minimum and maximum of filtered $(z_e - \langle z_e \rangle) / (z_a / T)$ vs. (z_a / T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–41. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-2.91E-07	-0.275	0.275	-0.266	0.268	-5.33	5.37
.10	-5.71E-07	-0.550	0.550	-0.533	0.537	-5.33	5.37
.20	-1.21E-06	-1.10	1.10	-1.07	1.07	-5.33	5.37
.40	-2.33E-06	-2.20	2.20	-2.13	2.15	-5.33	5.37
.80	-4.73E-06	-4.40	4.40	-4.26	4.29	-5.33	5.37

Table K–42. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-2.91E-07	-0.275	0.275	-0.266	0.268	-5.33	5.37
.10	-5.71E-07	-0.550	0.550	-0.533	0.537	-5.33	5.37
.20	-1.21E-06	-1.10	1.10	-1.07	1.07	-5.33	5.37
.40	-2.33E-06	-2.20	2.20	-2.13	2.15	-5.33	5.37
.80	-4.73E-06	-4.40	4.40	-4.26	4.29	-5.33	5.37

Table K–43. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.43E-08	-0.275	0.275	-0.266	0.266	-5.33	5.33
.10	-1.21E-07	-0.549	0.550	-0.533	0.533	-5.33	5.33
.20	-2.64E-07	-1.10	1.10	-1.07	1.07	-5.33	5.33
.40	-4.83E-07	-2.20	2.20	-2.13	2.13	-5.33	5.33
.80	-9.56E-07	-4.39	4.40	-4.26	4.26	-5.33	5.33

Table K–44. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–45. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–46. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-5.88E-07	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.20E-06	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-2.35E-06	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-4.81E-06	-2.20	2.20	-2.17	2.17	-5.44	5.44
.80	-9.72E-06	-4.40	4.40	-4.35	4.35	-5.44	5.44

Table K–47. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	9.55E-03	-1.10	1.10	-1.04	1.04	-5.25	5.16
.40	1.91E-02	-2.20	2.20	-2.08	2.08	-5.25	5.16
.80	1.91E-02	-4.40	4.40	-4.38	4.34	-5.50	5.40

Table K–48. Minimum and Maximum of Variables z_e and $(z_e)^* = (z_e - \langle z_e \rangle) / (z_a / T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle z_e \rangle$ Mean (m)	Unfiltered z_e		Filtered z_e		Filtered $(z_e)^*$	
		Min. (m)	Max. (m)	Min. (m)	Max. (m)	Min. (m)	Max. (m)
.05	-1.04E-08	-0.275	0.275	-0.272	0.272	-5.44	5.44
.10	-1.84E-08	-0.550	0.550	-0.544	0.544	-5.44	5.44
.20	-4.64E-08	-1.10	1.10	-1.09	1.09	-5.44	5.44
.40	-3.47E-08	-2.20	2.20	-2.18	2.18	-5.44	5.44
.80	-4.82E-07	-4.40	4.40	-4.36	4.36	-5.46	5.46

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-7. Minimum and maximum of filtered $(F_x^{ptot} - \langle F_x^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–49. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.04E-03	-5.43	5.45	-5.42	5.43	-108.	109.
.10	-2.07E-03	-10.9	10.9	-10.8	10.9	-108.	109.
.20	-4.14E-03	-21.7	21.8	-21.7	21.7	-108.	109.
.40	-8.28E-03	-43.5	43.6	-43.4	43.4	-108.	109.
.80	-1.66E-02	-86.9	87.3	-86.7	86.8	-108.	109.

Table K–50. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.09	2.09	12.4	2.64	12.4	-89.1	105.
.10	10.5	1.90	20.6	2.71	20.1	-77.6	96.0
.20	12.8	-1.63E+03	38.6	-207.	38.7	-1.10E+03	129.
.40	33.6	-31.1	84.4	2.54	84.2	-77.6	127.
.80	90.2	-30.7	1.05E+03	-8.74	281.	-124.	238.

Table K-51. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.37	-8.29	-10.6	11.0
.10	-8.87	-9.37	-8.28	-9.36	-8.29	-4.95	5.75
.20	-9.37	-12.0	-7.55	-11.9	-7.55	-12.9	9.07
.40	-8.36	-12.0	-6.62	-11.7	-6.63	-8.26	4.33
.80	-7.06	-12.0	-2.14	-10.7	-2.15	-4.58	6.14

Table K-52. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	4.87E-02	-3.66	3.66	-3.66	3.66	-74.2	72.3
.10	0.195	-7.33	7.33	-7.33	7.33	-75.2	71.3
.20	0.779	-14.7	14.7	-14.6	14.7	-77.1	69.4
.40	3.12	-29.3	29.3	-29.3	29.3	-81.0	65.5
.80	12.5	-58.6	58.8	-58.6	58.8	-88.8	57.9

Table K-53. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.0	-45.6	-32.5	-45.6	-32.5	-130.	131.
.10	-38.8	-52.0	-26.0	-52.0	-26.0	-131.	128.
.20	-38.2	-64.9	-12.8	-64.9	-12.9	-134.	127.
.40	-36.0	-91.3	12.8	-91.2	12.8	-138.	122.
.80	-28.6	-144.	55.1	-143.	55.1	-144.	105.

Table K-54. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.0	-45.4	-32.4	-45.4	-32.4	-129.	130.
.10	-38.6	-51.3	-26.5	-51.3	-26.5	-128.	121.
.20	-37.4	-62.4	-15.6	-62.4	-16.3	-125.	106.
.40	-33.6	-82.2	5.45	-82.0	3.54	-121.	92.8
.80	-23.4	-147.	100.	-126.	82.3	-128.	132.

Table K–55. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–56. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-8. Minimum and maximum of filtered $(F_x^{ptot} - \langle F_x^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-57. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.68E-02	-33.6	33.6	-33.5	33.4	-669.	671.
.10	-0.174	-67.3	67.1	-67.1	66.9	-669.	671.
.20	-0.347	-135.	134.	-134.	134.	-669.	671.
.40	-0.695	-269.	269.	-268.	268.	-669.	671.
.80	-1.39	-538.	537.	-537.	535.	-669.	671.

Table K-58. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.01	-23.0	39.4	-22.3	39.3	-586.	645.
.10	10.3	-52.0	77.6	-51.5	77.3	-618.	670.
.20	21.4	-102.	148.	-98.1	147.	-597.	629.
.40	33.1	-196.	259.	-188.	253.	-552.	549.
.80	87.1	-343.	522.	-334.	488.	-526.	502.

Table K–59. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.28	-9.37	-8.29	-10.5	11.0
.10	-8.87	-9.37	-8.28	-9.35	-8.30	-4.76	5.68
.20	-9.38	-12.0	-7.55	-11.9	-7.56	-12.7	9.10
.40	-8.34	-12.0	-6.63	-11.0	-6.64	-6.61	4.26
.80	-7.06	-12.0	-2.14	-9.84	-2.17	-3.47	6.11

Table K–60. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.148	-10.9	10.9	-10.9	10.9	-220.	214.
.10	0.591	-21.8	21.7	-21.7	21.7	-223.	211.
.20	2.37	-43.5	43.5	-43.4	43.4	-229.	205.
.40	9.47	-87.0	87.0	-86.8	86.9	-241.	194.
.80	37.9	-174.	175.	-174.	175.	-264.	171.

Table K-61. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-38.9	-52.8	-25.3	-52.7	-25.3	-276.	272.
.10	-38.4	-66.4	-11.6	-66.3	-11.6	-279.	268.
.20	-36.6	-93.8	16.0	-93.7	15.9	-285.	263.
.40	-29.6	-149.	70.4	-149.	70.3	-298.	250.
.80	-3.16	-259.	171.	-258.	171.	-319.	217.

Table K-62. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-38.6	-52.0	-24.8	-52.0	-24.8	-269.	275.
.10	-37.2	-63.2	-11.8	-63.2	-11.8	-260.	254.
.20	-32.4	-81.1	13.9	-81.1	11.3	-244.	218.
.40	-15.2	-117.	70.9	-102.	54.1	-217.	173.
.80	34.5	-248.	402.	-113.	308.	-184.	342.

Table K–63. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–64. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K–9. Minimum and maximum of filtered $(F_x^{ptot} - \langle F_x^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–65. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered $(F_x^{\text{ptot}})^*$ Min. (kN)	Max. (kN)
.05	-1.14	-111.	107.	-107.	104.	-2.13E+03	2.10E+03
.10	-2.28	-222.	215.	-215.	208.	-2.13E+03	2.10E+03
.20	-4.56	-443.	429.	-430.	416.	-2.13E+03	2.10E+03
.40	-9.13	-886.	859.	-859.	832.	-2.13E+03	2.10E+03
.80	-18.3	-1.77E+03	1.72E+03	-1.72E+03	1.66E+03	-2.13E+03	2.10E+03

Table K–66. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered $(F_x^{\text{ptot}})^*$ Min. (kN)	Max. (kN)
.05	5.96	-94.8	114.	-91.9	111.	-1.96E+03	2.09E+03
.10	8.18	-206.	224.	-199.	218.	-2.07E+03	2.10E+03
.20	17.1	-390.	446.	-376.	432.	-1.97E+03	2.07E+03
.40	25.0	-761.	833.	-737.	806.	-1.91E+03	1.95E+03
.80	89.1	-1.41E+03	2.45E+03	-1.37E+03	1.66E+03	-1.83E+03	1.97E+03

Table K–67. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.36	-8.29	-10.4	11.0
.10	-8.87	-9.37	-8.29	-9.21	-8.41	-3.43	4.57
.20	-9.37	-12.0	-7.55	-11.9	-7.60	-12.8	8.89
.40	-8.34	-11.8	-6.63	-9.59	-6.76	-3.12	3.95
.80	-7.06	-11.4	-2.14	-9.74	-2.55	-3.35	5.64

Table K–68. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	2.00	-124.	124.	-122.	123.	-2.48E+03	2.42E+03
.10	8.00	-247.	250.	-244.	247.	-2.52E+03	2.39E+03
.20	32.0	-491.	503.	-484.	499.	-2.58E+03	2.33E+03
.40	128.	-974.	1.03E+03	-959.	1.02E+03	-2.72E+03	2.23E+03
.80	512.	-1.92E+03	2.23E+03	-1.88E+03	2.21E+03	-2.99E+03	2.13E+03

Table K–69. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	-37.1	-165.	88.2	-164.	86.8	-2.54E+03	2.48E+03
.10	-31.0	-291.	216.	-288.	214.	-2.57E+03	2.45E+03
.20	-6.97	-541.	475.	-534.	471.	-2.64E+03	2.39E+03
.40	88.9	-1.03E+03	1.01E+03	-1.02E+03	1.00E+03	-2.77E+03	2.28E+03
.80	471.	-2.00E+03	2.21E+03	-1.96E+03	2.19E+03	-3.04E+03	2.15E+03

Table K–70. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	-38.8	-168.	82.4	-166.	81.6	-2.55E+03	2.41E+03
.10	-44.0	-300.	184.	-297.	181.	-2.53E+03	2.25E+03
.20	-58.9	-569.	353.	-562.	313.	-2.51E+03	1.86E+03
.40	-78.8	-1.14E+03	1.01E+03	-1.12E+03	716.	-2.60E+03	1.99E+03
.80	-64.7	-2.44E+03	3.02E+03	-2.38E+03	2.32E+03	-2.90E+03	2.98E+03

Table K–71. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–72. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-10. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-73. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	-0.208	-76.4	78.6	-76.4	78.5	-1.52E+03	1.57E+03
.10	-0.416	-153.	157.	-153.	157.	-1.52E+03	1.57E+03
.20	-0.833	-306.	314.	-305.	314.	-1.52E+03	1.57E+03
.40	-1.67	-611.	629.	-611.	628.	-1.52E+03	1.57E+03
.80	-3.33	-1.22E+03	1.26E+03	-1.22E+03	1.26E+03	-1.52E+03	1.57E+03

Table K-74. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	6.89	-71.2	81.1	-70.8	81.1	-1.55E+03	1.48E+03
.10	10.1	-144.	165.	-142.	165.	-1.52E+03	1.55E+03
.20	12.0	-1.85E+03	324.	-428.	342.	-2.20E+03	1.65E+03
.40	31.9	-584.	646.	-575.	644.	-1.52E+03	1.53E+03
.80	86.8	-1.15E+03	2.10E+03	-1.14E+03	1.24E+03	-1.53E+03	1.44E+03

Table K-75. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.37	-8.29	-10.6	11.0
.10	-8.87	-9.37	-8.28	-9.36	-8.29	-4.95	5.75
.20	-9.37	-12.0	-7.55	-11.9	-7.55	-12.9	9.07
.40	-8.36	-12.0	-6.62	-11.7	-6.63	-8.26	4.33
.80	-7.06	-12.0	-2.14	-10.7	-2.15	-4.58	6.14

Table K-76. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.5	-70.1	-12.7	-70.1	-12.8	-572.	574.
.10	-41.2	-98.4	16.3	-98.4	16.3	-572.	575.
.20	-40.3	-154.	75.2	-154.	75.1	-570.	577.
.40	-36.4	-263.	196.	-263.	196.	-567.	581.
.80	-21.0	-470.	450.	-470.	450.	-561.	589.

Table K-77. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-80.6	-111.	-50.6	-111.	-50.6	-599.	599.
.10	-80.3	-140.	-20.2	-140.	-20.3	-598.	601.
.20	-79.3	-199.	41.1	-199.	41.0	-597.	602.
.40	-75.6	-313.	167.	-313.	166.	-594.	605.
.80	-62.1	-533.	429.	-533.	429.	-588.	614.

Table K-78. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-69.4	-307.	130.	-246.	129.	-3.53E+03	3.98E+03
.10	-7.52	-364.	333.	-322.	332.	-3.15E+03	3.40E+03
.20	134.	-466.	752.	-403.	751.	-2.69E+03	3.08E+03
.40	362.	-795.	1.54E+03	-509.	1.52E+03	-2.18E+03	2.88E+03
.80	763.	-1.74E+03	3.28E+03	-811.	2.90E+03	-1.97E+03	2.68E+03

Table K–79. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–80. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-11. Minimum and maximum of filtered $(F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–81. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	4.80E-02	-68.9	70.4	-68.6	70.5	-1.37E+03	1.41E+03
.10	9.60E-02	-138.	141.	-137.	141.	-1.37E+03	1.41E+03
.20	0.192	-275.	282.	-274.	282.	-1.37E+03	1.41E+03
.40	0.384	-551.	563.	-548.	564.	-1.37E+03	1.41E+03
.80	0.768	-1.10E+03	1.13E+03	-1.10E+03	1.13E+03	-1.37E+03	1.41E+03

Table K–82. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.14	-52.7	77.4	-52.5	77.4	-1.19E+03	1.41E+03
.10	10.6	-122.	150.	-121.	150.	-1.32E+03	1.40E+03
.20	21.9	-223.	299.	-221.	299.	-1.22E+03	1.38E+03
.40	34.2	-423.	538.	-422.	538.	-1.14E+03	1.26E+03
.80	89.2	-734.	1.08E+03	-731.	1.08E+03	-1.03E+03	1.23E+03

Table K-83. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.28	-9.37	-8.29	-10.5	11.0
.10	-8.87	-9.37	-8.28	-9.35	-8.30	-4.76	5.68
.20	-9.38	-12.0	-7.55	-11.9	-7.56	-12.7	9.10
.40	-8.34	-12.0	-6.63	-11.0	-6.64	-6.61	4.26
.80	-7.06	-12.0	-2.14	-9.84	-2.17	-3.47	6.11

Table K-84. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.2	-97.6	14.8	-97.5	14.7	-1.13E+03	1.12E+03
.10	-40.3	-153.	71.4	-153.	71.2	-1.13E+03	1.12E+03
.20	-36.6	-264.	186.	-264.	185.	-1.14E+03	1.11E+03
.40	-21.9	-483.	418.	-482.	418.	-1.15E+03	1.10E+03
.80	36.9	-912.	905.	-911.	904.	-1.18E+03	1.08E+03

Table K-85. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-80.3	-139.	-21.6	-139.	-21.7	-1.18E+03	1.17E+03
.10	-79.4	-198.	37.6	-198.	37.5	-1.18E+03	1.17E+03
.20	-75.6	-314.	157.	-313.	157.	-1.19E+03	1.16E+03
.40	-61.1	-544.	400.	-544.	399.	-1.21E+03	1.15E+03
.80	-4.16	-996.	900.	-995.	899.	-1.24E+03	1.13E+03

Table K-86. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-72.7	-323.	89.8	-282.	89.5	-4.20E+03	3.24E+03
.10	-11.5	-403.	252.	-334.	252.	-3.23E+03	2.63E+03
.20	120.	-493.	580.	-372.	574.	-2.46E+03	2.27E+03
.40	303.	-1.08E+03	1.16E+03	-478.	1.14E+03	-1.95E+03	2.09E+03
.80	546.	-2.61E+03	2.61E+03	-628.	2.17E+03	-1.47E+03	2.03E+03

Table K-87. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	-480.	-996.	-107.	-989.	-113.	-2.55E+03	1.83E+03
.40	-629.	-1.75E+03	7.46	-1.74E+03	-12.3	-2.77E+03	1.54E+03
.80	-1.10E+03	-3.69E+03	23.4	-3.65E+03	13.5	-3.18E+03	1.40E+03

Table K-88. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-12. Minimum and maximum of filtered $(F_x^{ptot} - \langle F_x^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–89. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.92	-66.8	67.9	-64.8	60.3	-1.26E+03	1.25E+03
.10	-3.83	-134.	136.	-130.	121.	-1.26E+03	1.25E+03
.20	-7.67	-267.	272.	-259.	241.	-1.26E+03	1.25E+03
.40	-15.3	-534.	543.	-518.	483.	-1.26E+03	1.25E+03
.80	-30.7	-1.07E+03	1.09E+03	-1.04E+03	966.	-1.26E+03	1.25E+03

Table K–90. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	5.19	-50.8	74.5	-49.3	66.7	-1.09E+03	1.23E+03
.10	6.63	-118.	145.	-114.	131.	-1.21E+03	1.24E+03
.20	14.0	-214.	288.	-206.	256.	-1.10E+03	1.21E+03
.40	18.8	-409.	517.	-396.	458.	-1.04E+03	1.10E+03
.80	76.7	-718.	1.86E+03	-690.	997.	-959.	1.15E+03

Table K–91. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.36	-8.29	-10.4	11.0
.10	-8.87	-9.37	-8.29	-9.21	-8.41	-3.43	4.57
.20	-9.37	-12.0	-7.55	-11.9	-7.60	-12.8	8.89
.40	-8.34	-11.8	-6.63	-9.59	-6.76	-3.12	3.95
.80	-7.06	-11.4	-2.14	-9.74	-2.55	-3.35	5.64

Table K–92. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$	Unfiltered F_x^{ptot}		Filtered F_x^{ptot}		Filtered $(F_x^{\text{ptot}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-40.0	-124.	40.0	-123.	39.2	-1.65E+03	1.58E+03
.10	-35.2	-206.	121.	-204.	120.	-1.69E+03	1.55E+03
.20	-16.3	-374.	282.	-369.	280.	-1.76E+03	1.48E+03
.40	59.3	-717.	612.	-704.	608.	-1.91E+03	1.37E+03
.80	362.	-1.44E+03	1.46E+03	-1.40E+03	1.45E+03	-2.21E+03	1.36E+03

Table K–93. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	-79.0	-167.	5.28	-166.	4.40	-1.74E+03	1.67E+03
.10	-74.2	-254.	90.6	-252.	89.0	-1.77E+03	1.63E+03
.20	-55.3	-430.	260.	-425.	258.	-1.85E+03	1.57E+03
.40	20.2	-793.	607.	-779.	603.	-2.00E+03	1.46E+03
.80	321.	-1.56E+03	1.49E+03	-1.52E+03	1.47E+03	-2.30E+03	1.44E+03

Table K–94. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	-73.7	-364.	59.6	-260.	54.4	-3.73E+03	2.56E+03
.10	-9.45	-381.	197.	-210.	188.	-2.00E+03	1.98E+03
.20	116.	-415.	456.	-194.	443.	-1.55E+03	1.64E+03
.40	329.	-984.	1.11E+03	-64.9	996.	-986.	1.67E+03
.80	923.	-2.14E+03	2.96E+03	-159.	2.34E+03	-1.35E+03	1.77E+03

Table K–95. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	-365.	-1.02E+03	190.	-972.	159.	-3.03E+03	2.62E+03
.40	-379.	-1.85E+03	648.	-1.69E+03	579.	-3.27E+03	2.40E+03
.80	-570.	-4.22E+03	3.13E+03	-4.19E+03	2.45E+03	-4.53E+03	3.78E+03

Table K–96. Minimum and Maximum of Variables F_x^{ptot} and $(F_x^{\text{ptot}})^* = (F_x^{\text{ptot}} - \langle F_x^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	F_x^{ptot} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{ptot}})^*$ Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-13. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–97. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.02E+04	9.16E+04	8.02E+04	9.16E+04	-1.14E+05	1.14E+05
.10	8.59E+04	7.45E+04	9.73E+04	7.45E+04	9.73E+04	-1.14E+05	1.14E+05
.20	8.59E+04	6.31E+04	1.09E+05	6.30E+04	1.09E+05	-1.14E+05	1.14E+05
.40	8.59E+04	4.02E+04	1.32E+05	4.01E+04	1.32E+05	-1.14E+05	1.14E+05
.80	8.59E+04	-5.50E+03	1.77E+05	-5.64E+03	1.77E+05	-1.14E+05	1.14E+05

Table K–98. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.24E+05	1.23E+05
.10	8.58E+04	7.39E+04	9.75E+04	7.39E+04	9.75E+04	-1.19E+05	1.17E+05
.20	8.57E+04	6.40E+04	1.07E+05	6.40E+04	1.07E+05	-1.08E+05	1.07E+05
.40	8.57E+04	4.51E+04	1.27E+05	4.51E+04	1.27E+05	-1.02E+05	1.04E+05
.80	8.95E+04	1.73E+04	1.72E+05	1.71E+04	1.72E+05	-9.04E+04	1.03E+05

Table K–99. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.95E+04	9.11E+04	7.95E+04	9.11E+04	-1.16E+05	1.17E+05
.10	8.53E+04	7.38E+04	9.69E+04	7.38E+04	9.69E+04	-1.15E+05	1.16E+05
.20	8.55E+04	6.32E+04	1.08E+05	6.32E+04	1.08E+05	-1.12E+05	1.15E+05
.40	8.63E+04	4.39E+04	1.31E+05	4.40E+04	1.31E+05	-1.06E+05	1.12E+05
.80	8.96E+04	1.49E+04	1.74E+05	1.49E+04	1.74E+05	-9.33E+04	1.05E+05

Table K–100. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.96E+04	9.15E+04	7.96E+04	9.15E+04	-1.19E+05	1.19E+05
.10	8.56E+04	7.36E+04	9.75E+04	7.36E+04	9.75E+04	-1.19E+05	1.19E+05
.20	8.56E+04	6.17E+04	1.09E+05	6.17E+04	1.09E+05	-1.19E+05	1.19E+05
.40	8.56E+04	3.79E+04	1.33E+05	3.79E+04	1.33E+05	-1.19E+05	1.19E+05
.80	8.57E+04	-9.84E+03	1.81E+05	-9.80E+03	1.81E+05	-1.19E+05	1.19E+05

Table K–101. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.96E+04	9.14E+04	7.96E+04	9.14E+04	-1.18E+05	1.18E+05
.10	8.56E+04	7.39E+04	9.73E+04	7.39E+04	9.73E+04	-1.17E+05	1.18E+05
.20	8.57E+04	6.30E+04	1.09E+05	6.30E+04	1.09E+05	-1.14E+05	1.16E+05
.40	8.65E+04	4.34E+04	1.32E+05	4.34E+04	1.32E+05	-1.08E+05	1.13E+05
.80	8.98E+04	1.37E+04	1.75E+05	1.37E+04	1.75E+05	-9.52E+04	1.07E+05

Table K–102. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.96E+04	9.15E+04	7.96E+04	9.14E+04	-1.18E+05	1.19E+05
.10	8.56E+04	7.39E+04	9.74E+04	7.39E+04	9.73E+04	-1.17E+05	1.18E+05
.20	8.57E+04	6.29E+04	1.09E+05	6.29E+04	1.09E+05	-1.14E+05	1.17E+05
.40	8.64E+04	4.29E+04	1.32E+05	4.29E+04	1.32E+05	-1.09E+05	1.14E+05
.80	8.94E+04	1.08E+04	1.76E+05	1.08E+04	1.76E+05	-9.82E+04	1.08E+05

Table K–103. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–104. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.01E+04	9.17E+04	8.02E+04	9.16E+04	-1.14E+05	1.14E+05
.10	8.59E+04	7.45E+04	9.75E+04	7.46E+04	9.74E+04	-1.13E+05	1.15E+05
.20	8.61E+04	6.36E+04	1.09E+05	6.38E+04	1.09E+05	-1.11E+05	1.13E+05
.40	8.68E+04	4.38E+04	1.32E+05	4.42E+04	1.31E+05	-1.07E+05	1.11E+05
.80	8.98E+04	1.15E+04	1.75E+05	1.20E+04	1.75E+05	-9.72E+04	1.06E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-14. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-105. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.09E+04	9.08E+04	8.10E+04	9.08E+04	-9.85E+04	9.81E+04
.10	8.59E+04	7.60E+04	9.57E+04	7.61E+04	9.57E+04	-9.85E+04	9.81E+04
.20	8.59E+04	6.61E+04	1.06E+05	6.62E+04	1.06E+05	-9.85E+04	9.81E+04
.40	8.59E+04	4.62E+04	1.25E+05	4.65E+04	1.25E+05	-9.85E+04	9.81E+04
.80	8.60E+04	6.51E+03	1.65E+05	7.16E+03	1.64E+05	-9.85E+04	9.81E+04

Table K-106. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.05E+04	9.12E+04	8.05E+04	9.12E+04	-1.08E+05	1.07E+05
.10	8.58E+04	7.55E+04	9.59E+04	7.55E+04	9.59E+04	-1.03E+05	1.00E+05
.20	8.57E+04	6.71E+04	1.04E+05	6.72E+04	1.04E+05	-9.23E+04	9.09E+04
.40	8.57E+04	5.11E+04	1.21E+05	5.15E+04	1.21E+05	-8.55E+04	8.73E+04
.80	8.95E+04	2.80E+04	1.59E+05	2.91E+04	1.59E+05	-7.55E+04	8.63E+04

Table K–107. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.98E+04	9.08E+04	7.98E+04	9.07E+04	-1.09E+05	1.09E+05
.10	8.53E+04	7.45E+04	9.62E+04	7.46E+04	9.62E+04	-1.08E+05	1.09E+05
.20	8.55E+04	6.45E+04	1.07E+05	6.46E+04	1.07E+05	-1.05E+05	1.07E+05
.40	8.63E+04	4.64E+04	1.28E+05	4.66E+04	1.28E+05	-9.93E+04	1.04E+05
.80	8.96E+04	1.86E+04	1.68E+05	1.88E+04	1.68E+05	-8.85E+04	9.82E+04

Table K–108. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	8.06E+04	9.05E+04	8.06E+04	9.05E+04	-9.93E+04	9.92E+04
.10	8.56E+04	7.56E+04	9.55E+04	7.56E+04	9.55E+04	-9.93E+04	9.92E+04
.20	8.56E+04	6.57E+04	1.05E+05	6.57E+04	1.05E+05	-9.94E+04	9.91E+04
.40	8.57E+04	4.58E+04	1.25E+05	4.59E+04	1.25E+05	-9.96E+04	9.89E+04
.80	8.61E+04	6.05E+03	1.65E+05	6.16E+03	1.65E+05	-9.99E+04	9.86E+04

Table K-109. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	8.06E+04	9.05E+04	8.06E+04	9.05E+04	-9.83E+04	9.86E+04
.10	8.56E+04	7.59E+04	9.54E+04	7.59E+04	9.53E+04	-9.69E+04	9.78E+04
.20	8.58E+04	6.70E+04	1.05E+05	6.70E+04	1.05E+05	-9.38E+04	9.62E+04
.40	8.66E+04	5.13E+04	1.24E+05	5.13E+04	1.24E+05	-8.82E+04	9.29E+04
.80	9.01E+04	2.94E+04	1.59E+05	2.94E+04	1.59E+05	-7.59E+04	8.63E+04

Table K-110. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	8.06E+04	9.05E+04	8.06E+04	9.05E+04	-9.86E+04	9.89E+04
.10	8.55E+04	7.58E+04	9.54E+04	7.58E+04	9.54E+04	-9.77E+04	9.86E+04
.20	8.57E+04	6.66E+04	1.05E+05	6.66E+04	1.05E+05	-9.56E+04	9.77E+04
.40	8.63E+04	4.96E+04	1.25E+05	4.96E+04	1.25E+05	-9.17E+04	9.58E+04
.80	8.85E+04	1.99E+04	1.62E+05	2.00E+04	1.62E+05	-8.56E+04	9.21E+04

Table K–111. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–112. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.06E+04	9.12E+04	8.06E+04	9.11E+04	-1.05E+05	1.05E+05
.10	8.59E+04	7.54E+04	9.66E+04	7.55E+04	9.65E+04	-1.04E+05	1.06E+05
.20	8.60E+04	6.53E+04	1.07E+05	6.55E+04	1.07E+05	-1.03E+05	1.04E+05
.40	8.67E+04	4.68E+04	1.28E+05	4.72E+04	1.28E+05	-9.88E+04	1.03E+05
.80	8.92E+04	1.52E+04	1.69E+05	1.57E+04	1.68E+05	-9.19E+04	9.83E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-15. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-113. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.14E+04	9.00E+04	8.18E+04	8.99E+04	-8.10E+04	8.05E+04
.10	8.59E+04	7.70E+04	9.42E+04	7.78E+04	9.39E+04	-8.10E+04	8.05E+04
.20	8.59E+04	6.80E+04	1.02E+05	6.97E+04	1.02E+05	-8.10E+04	8.05E+04
.40	8.59E+04	5.02E+04	1.19E+05	5.35E+04	1.18E+05	-8.10E+04	8.05E+04
.80	8.58E+04	1.45E+04	1.52E+05	2.10E+04	1.50E+05	-8.10E+04	8.05E+04

Table K-114. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.14E+04	9.00E+04	8.18E+04	8.98E+04	-8.19E+04	7.92E+04
.10	8.58E+04	7.73E+04	9.38E+04	7.79E+04	9.35E+04	-7.87E+04	7.67E+04
.20	8.56E+04	6.97E+04	1.00E+05	7.13E+04	9.98E+04	-7.16E+04	7.06E+04
.40	8.57E+04	5.61E+04	1.12E+05	5.92E+04	1.12E+05	-6.62E+04	6.49E+04
.80	8.94E+04	3.08E+04	1.42E+05	3.82E+04	1.39E+05	-6.40E+04	6.20E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-115. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	8.13E+04	8.92E+04	8.14E+04	8.91E+04	-7.70E+04	7.71E+04
.10	8.53E+04	7.74E+04	9.32E+04	7.76E+04	9.30E+04	-7.67E+04	7.66E+04
.20	8.55E+04	6.98E+04	1.01E+05	7.03E+04	1.01E+05	-7.59E+04	7.55E+04
.40	8.63E+04	5.54E+04	1.17E+05	5.65E+04	1.16E+05	-7.45E+04	7.34E+04
.80	8.96E+04	2.83E+04	1.47E+05	3.11E+04	1.45E+05	-7.31E+04	6.91E+04

Table K-116. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	8.18E+04	8.93E+04	8.19E+04	8.93E+04	-7.38E+04	7.51E+04
.10	8.55E+04	7.81E+04	9.32E+04	7.82E+04	9.31E+04	-7.31E+04	7.58E+04
.20	8.53E+04	7.08E+04	1.01E+05	7.10E+04	1.01E+05	-7.18E+04	7.72E+04
.40	8.46E+04	5.67E+04	1.17E+05	5.70E+04	1.17E+05	-6.91E+04	7.99E+04
.80	8.18E+04	3.05E+04	1.51E+05	3.08E+04	1.50E+05	-6.37E+04	8.53E+04

Table K-117. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	8.17E+04	8.94E+04	8.17E+04	8.94E+04	-7.62E+04	7.77E+04
.10	8.55E+04	7.79E+04	9.34E+04	7.80E+04	9.33E+04	-7.50E+04	7.79E+04
.20	8.55E+04	7.08E+04	1.01E+05	7.10E+04	1.01E+05	-7.27E+04	7.82E+04
.40	8.55E+04	5.78E+04	1.18E+05	5.81E+04	1.17E+05	-6.87E+04	7.90E+04
.80	8.58E+04	3.33E+04	1.51E+05	3.42E+04	1.50E+05	-6.46E+04	8.05E+04

Table K-118. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	8.15E+04	8.94E+04	8.16E+04	8.93E+04	-7.77E+04	7.64E+04
.10	8.54E+04	7.69E+04	9.31E+04	7.73E+04	9.30E+04	-8.13E+04	7.62E+04
.20	8.51E+04	6.79E+04	1.00E+05	6.86E+04	1.00E+05	-8.23E+04	7.48E+04
.40	8.44E+04	4.96E+04	1.13E+05	5.06E+04	1.13E+05	-8.45E+04	7.13E+04
.80	8.33E+04	9.20E+03	1.49E+05	1.17E+04	1.41E+05	-8.96E+04	7.19E+04

Table K–119. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–120. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.58E+04	8.19E+04	8.97E+04	8.20E+04	8.96E+04	-7.75E+04	7.57E+04
.10	8.58E+04	7.80E+04	9.32E+04	7.80E+04	9.32E+04	-7.75E+04	7.39E+04
.20	8.55E+04	6.97E+04	1.00E+05	7.00E+04	9.98E+04	-7.78E+04	7.15E+04
.40	8.51E+04	5.26E+04	1.13E+05	5.31E+04	1.13E+05	-7.99E+04	6.85E+04
.80	8.49E+04	1.17E+04	1.53E+05	1.31E+04	1.44E+05	-8.97E+04	7.38E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-16. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-121. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.12E+04	9.06E+04	8.12E+04	9.06E+04	-9.45E+04	9.31E+04
.10	8.59E+04	7.65E+04	9.52E+04	7.65E+04	9.52E+04	-9.45E+04	9.31E+04
.20	8.59E+04	6.71E+04	1.05E+05	6.70E+04	1.05E+05	-9.45E+04	9.31E+04
.40	8.60E+04	4.82E+04	1.23E+05	4.82E+04	1.23E+05	-9.45E+04	9.31E+04
.80	8.60E+04	1.05E+04	1.61E+05	1.04E+04	1.60E+05	-9.45E+04	9.31E+04

Table K-122. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.07E+04	9.10E+04	8.07E+04	9.10E+04	-1.04E+05	1.02E+05
.10	8.58E+04	7.59E+04	9.54E+04	7.59E+04	9.54E+04	-9.95E+04	9.57E+04
.20	8.57E+04	6.80E+04	1.03E+05	6.80E+04	1.03E+05	-8.84E+04	8.61E+04
.40	8.58E+04	5.32E+04	1.19E+05	5.31E+04	1.19E+05	-8.16E+04	8.28E+04
.80	8.96E+04	3.29E+04	1.55E+05	3.32E+04	1.55E+05	-7.05E+04	8.22E+04

Table K–123. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.95E+04	9.11E+04	7.95E+04	9.11E+04	-1.16E+05	1.17E+05
.10	8.53E+04	7.38E+04	9.69E+04	7.38E+04	9.69E+04	-1.15E+05	1.16E+05
.20	8.55E+04	6.32E+04	1.08E+05	6.32E+04	1.08E+05	-1.12E+05	1.15E+05
.40	8.63E+04	4.39E+04	1.31E+05	4.40E+04	1.31E+05	-1.06E+05	1.12E+05
.80	8.96E+04	1.49E+04	1.74E+05	1.49E+04	1.74E+05	-9.33E+04	1.05E+05

Table K–124. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.59E+04	8.77E+04	7.59E+04	8.77E+04	-1.18E+05	1.18E+05
.10	8.18E+04	7.00E+04	9.37E+04	7.00E+04	9.37E+04	-1.18E+05	1.18E+05
.20	8.18E+04	5.82E+04	1.05E+05	5.82E+04	1.05E+05	-1.18E+05	1.18E+05
.40	8.19E+04	3.45E+04	1.29E+05	3.45E+04	1.29E+05	-1.18E+05	1.18E+05
.80	8.20E+04	-1.29E+04	1.77E+05	-1.28E+04	1.76E+05	-1.18E+05	1.18E+05

Table K-125. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.59E+04	8.77E+04	7.59E+04	8.77E+04	-1.17E+05	1.18E+05
.10	8.18E+04	7.02E+04	9.35E+04	7.02E+04	9.35E+04	-1.16E+05	1.17E+05
.20	8.20E+04	5.95E+04	1.05E+05	5.95E+04	1.05E+05	-1.13E+05	1.15E+05
.40	8.28E+04	4.00E+04	1.28E+05	4.00E+04	1.28E+05	-1.07E+05	1.12E+05
.80	8.61E+04	1.06E+04	1.71E+05	1.06E+04	1.71E+05	-9.43E+04	1.06E+05

Table K-126. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.17E+04	7.60E+04	8.71E+04	7.60E+04	8.71E+04	-1.13E+05	1.09E+05
.10	8.17E+04	7.02E+04	9.27E+04	7.02E+04	9.27E+04	-1.15E+05	1.10E+05
.20	8.17E+04	5.93E+04	1.04E+05	5.93E+04	1.04E+05	-1.12E+05	1.10E+05
.40	8.23E+04	4.00E+04	1.26E+05	4.00E+04	1.26E+05	-1.06E+05	1.09E+05
.80	8.52E+04	1.02E+04	1.68E+05	1.03E+04	1.68E+05	-9.37E+04	1.04E+05

Table K–127. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–128. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.00E+04	9.17E+04	8.01E+04	9.17E+04	-1.16E+05	1.16E+05
.10	8.59E+04	7.44E+04	9.77E+04	7.45E+04	9.75E+04	-1.14E+05	1.16E+05
.20	8.61E+04	6.34E+04	1.09E+05	6.36E+04	1.09E+05	-1.13E+05	1.14E+05
.40	8.67E+04	4.34E+04	1.32E+05	4.38E+04	1.32E+05	-1.07E+05	1.12E+05
.80	8.96E+04	1.09E+04	1.76E+05	1.14E+04	1.75E+05	-9.78E+04	1.07E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-17. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-129. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.05E+04	9.12E+04	8.06E+04	9.12E+04	-1.06E+05	1.06E+05
.10	8.59E+04	7.52E+04	9.65E+04	7.52E+04	9.65E+04	-1.06E+05	1.06E+05
.20	8.58E+04	6.45E+04	1.07E+05	6.45E+04	1.07E+05	-1.06E+05	1.06E+05
.40	8.57E+04	4.30E+04	1.28E+05	4.32E+04	1.28E+05	-1.06E+05	1.06E+05
.80	8.56E+04	95.6	1.71E+05	444.	1.70E+05	-1.06E+05	1.06E+05

Table K-130. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.01E+04	9.16E+04	8.01E+04	9.16E+04	-1.15E+05	1.14E+05
.10	8.58E+04	7.47E+04	9.66E+04	7.47E+04	9.66E+04	-1.11E+05	1.08E+05
.20	8.56E+04	6.55E+04	1.05E+05	6.56E+04	1.05E+05	-1.00E+05	9.89E+04
.40	8.56E+04	4.80E+04	1.24E+05	4.82E+04	1.24E+05	-9.35E+04	9.53E+04
.80	8.92E+04	2.17E+04	1.65E+05	2.20E+04	1.64E+05	-8.39E+04	9.41E+04

Table K–131. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.98E+04	9.08E+04	7.98E+04	9.07E+04	-1.09E+05	1.09E+05
.10	8.53E+04	7.45E+04	9.62E+04	7.46E+04	9.62E+04	-1.08E+05	1.09E+05
.20	8.55E+04	6.45E+04	1.07E+05	6.46E+04	1.07E+05	-1.05E+05	1.07E+05
.40	8.63E+04	4.64E+04	1.28E+05	4.66E+04	1.28E+05	-9.93E+04	1.04E+05
.80	8.96E+04	1.86E+04	1.68E+05	1.88E+04	1.68E+05	-8.85E+04	9.82E+04

Table K–132. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.66E+04	8.71E+04	7.66E+04	8.70E+04	-1.04E+05	1.04E+05
.10	8.18E+04	7.14E+04	9.23E+04	7.14E+04	9.23E+04	-1.04E+05	1.04E+05
.20	8.19E+04	6.09E+04	1.03E+05	6.10E+04	1.03E+05	-1.05E+05	1.04E+05
.40	8.19E+04	4.00E+04	1.24E+05	4.01E+04	1.24E+05	-1.05E+05	1.04E+05
.80	8.22E+04	-1.84E+03	1.65E+05	-1.73E+03	1.65E+05	-1.05E+05	1.04E+05

Table K-133. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.66E+04	8.70E+04	7.66E+04	8.70E+04	-1.04E+05	1.04E+05
.10	8.18E+04	7.16E+04	9.22E+04	7.16E+04	9.21E+04	-1.02E+05	1.03E+05
.20	8.20E+04	6.22E+04	1.02E+05	6.22E+04	1.02E+05	-9.91E+04	1.01E+05
.40	8.28E+04	4.53E+04	1.22E+05	4.54E+04	1.22E+05	-9.36E+04	9.83E+04
.80	8.62E+04	2.05E+04	1.60E+05	2.06E+04	1.60E+05	-8.21E+04	9.19E+04

Table K-134. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.17E+04	7.66E+04	8.66E+04	7.66E+04	8.66E+04	-1.02E+05	9.86E+04
.10	8.17E+04	7.12E+04	9.17E+04	7.13E+04	9.17E+04	-1.04E+05	1.00E+05
.20	8.16E+04	6.12E+04	1.02E+05	6.12E+04	1.02E+05	-1.02E+05	1.01E+05
.40	8.19E+04	4.25E+04	1.22E+05	4.27E+04	1.22E+05	-9.81E+04	9.97E+04
.80	8.36E+04	1.10E+04	1.60E+05	1.14E+04	1.60E+05	-9.03E+04	9.60E+04

Table K–135. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	7.92E+04	5.74E+04	1.02E+05	5.76E+04	1.02E+05	-1.08E+05	1.13E+05
.40	7.94E+04	3.80E+04	1.24E+05	3.82E+04	1.24E+05	-1.03E+05	1.10E+05
.80	8.17E+04	8.19E+03	1.66E+05	8.42E+03	1.65E+05	-9.16E+04	1.04E+05

Table K–136. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.05E+04	9.13E+04	8.05E+04	9.13E+04	-1.07E+05	1.07E+05
.10	8.59E+04	7.52E+04	9.68E+04	7.53E+04	9.67E+04	-1.06E+05	1.08E+05
.20	8.61E+04	6.49E+04	1.07E+05	6.51E+04	1.07E+05	-1.05E+05	1.06E+05
.40	8.65E+04	4.60E+04	1.29E+05	4.64E+04	1.28E+05	-1.00E+05	1.04E+05
.80	8.89E+04	1.40E+04	1.69E+05	1.45E+04	1.69E+05	-9.30E+04	9.99E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-18. Minimum and maximum of filtered $(F_z^{ptot} - \langle F_z^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-137. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.16E+04	8.98E+04	8.22E+04	8.97E+04	-7.48E+04	7.54E+04
.10	8.59E+04	7.74E+04	9.37E+04	7.84E+04	9.34E+04	-7.48E+04	7.54E+04
.20	8.59E+04	6.88E+04	1.01E+05	7.09E+04	1.01E+05	-7.48E+04	7.54E+04
.40	8.58E+04	5.18E+04	1.17E+05	5.59E+04	1.16E+05	-7.48E+04	7.54E+04
.80	8.57E+04	1.76E+04	1.48E+05	2.59E+04	1.46E+05	-7.48E+04	7.54E+04

Table K-138. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	8.18E+04	8.97E+04	8.21E+04	8.96E+04	-7.56E+04	7.39E+04
.10	8.58E+04	7.79E+04	9.32E+04	7.86E+04	9.29E+04	-7.23E+04	7.15E+04
.20	8.56E+04	7.05E+04	9.91E+04	7.25E+04	9.87E+04	-6.53E+04	6.56E+04
.40	8.56E+04	5.77E+04	1.10E+05	6.16E+04	1.10E+05	-6.01E+04	5.99E+04
.80	8.93E+04	3.39E+04	1.38E+05	4.25E+04	1.35E+05	-5.85E+04	5.69E+04

Table K-139. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	8.13E+04	8.92E+04	8.14E+04	8.91E+04	-7.70E+04	7.71E+04
.10	8.53E+04	7.74E+04	9.32E+04	7.76E+04	9.30E+04	-7.67E+04	7.66E+04
.20	8.55E+04	6.98E+04	1.01E+05	7.03E+04	1.01E+05	-7.59E+04	7.55E+04
.40	8.63E+04	5.54E+04	1.17E+05	5.65E+04	1.16E+05	-7.45E+04	7.34E+04
.80	8.96E+04	2.83E+04	1.47E+05	3.11E+04	1.45E+05	-7.31E+04	6.91E+04

Table K-140. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.81E+04	8.56E+04	7.81E+04	8.55E+04	-7.36E+04	7.46E+04
.10	8.18E+04	7.44E+04	8.94E+04	7.45E+04	8.93E+04	-7.30E+04	7.52E+04
.20	8.16E+04	6.71E+04	9.71E+04	6.73E+04	9.69E+04	-7.18E+04	7.64E+04
.40	8.10E+04	5.30E+04	1.13E+05	5.33E+04	1.13E+05	-6.95E+04	7.88E+04
.80	7.87E+04	2.65E+04	1.46E+05	2.67E+04	1.45E+05	-6.49E+04	8.35E+04

Table K-141. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.18E+04	7.79E+04	8.57E+04	7.80E+04	8.56E+04	-7.61E+04	7.73E+04
.10	8.18E+04	7.42E+04	8.96E+04	7.43E+04	8.95E+04	-7.52E+04	7.75E+04
.20	8.18E+04	6.70E+04	9.75E+04	6.71E+04	9.73E+04	-7.33E+04	7.77E+04
.40	8.20E+04	5.35E+04	1.14E+05	5.38E+04	1.13E+05	-7.03E+04	7.82E+04
.80	8.27E+04	2.77E+04	1.47E+05	2.87E+04	1.46E+05	-6.76E+04	7.92E+04

Table K-142. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.17E+04	7.84E+04	8.57E+04	7.85E+04	8.57E+04	-6.36E+04	8.04E+04
.10	8.15E+04	7.39E+04	8.93E+04	7.42E+04	8.92E+04	-7.25E+04	7.72E+04
.20	8.10E+04	6.48E+04	9.62E+04	6.55E+04	9.60E+04	-7.73E+04	7.51E+04
.40	8.00E+04	4.72E+04	1.09E+05	4.82E+04	1.09E+05	-7.95E+04	7.18E+04
.80	7.90E+04	1.05E+04	1.47E+05	1.32E+04	1.39E+05	-8.22E+04	7.50E+04

Table K–143. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	8.09E+04	6.43E+04	9.61E+04	6.56E+04	9.58E+04	-7.62E+04	7.44E+04
.40	8.08E+04	4.49E+04	1.14E+05	4.75E+04	1.11E+05	-8.34E+04	7.64E+04
.80	8.29E+04	1.23E+04	1.57E+05	1.44E+04	1.44E+05	-8.57E+04	7.57E+04

Table K–144. Minimum and Maximum of Variables F_z^{ptot} and $(F_z^{\text{ptot}})^* = (F_z^{\text{ptot}} - \langle F_z^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{ptot}} \rangle$ Mean (kN)	Unfiltered F_z^{ptot}		Filtered F_z^{ptot}		Filtered $(F_z^{\text{ptot}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.58E+04	8.17E+04	8.99E+04	8.17E+04	8.99E+04	-8.20E+04	8.09E+04
.10	8.57E+04	7.75E+04	9.37E+04	7.76E+04	9.36E+04	-8.14E+04	7.90E+04
.20	8.56E+04	6.91E+04	1.01E+05	6.93E+04	1.01E+05	-8.14E+04	7.61E+04
.40	8.44E+04	5.06E+04	1.16E+05	5.10E+04	1.15E+05	-8.33E+04	7.72E+04
.80	8.34E+04	9.00E+03	1.60E+05	1.03E+04	1.47E+05	-9.13E+04	7.93E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K–19. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-145. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-0.790	-4.62E+04	4.62E+04	-4.63E+04	4.61E+04	-9.25E+05	9.22E+05
.10	-1.58	-9.24E+04	9.23E+04	-9.25E+04	9.22E+04	-9.25E+05	9.22E+05
.20	-3.16	-1.85E+05	1.85E+05	-1.85E+05	1.84E+05	-9.25E+05	9.22E+05
.40	-6.31	-3.69E+05	3.69E+05	-3.70E+05	3.69E+05	-9.25E+05	9.22E+05
.80	-12.6	-7.39E+05	7.39E+05	-7.40E+05	7.38E+05	-9.25E+05	9.22E+05

Table K-146. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.17E+04	5.35E+04	-4.18E+04	5.35E+04	-8.91E+05	1.01E+06
.10	8.68E+03	-7.30E+04	1.02E+05	-7.31E+04	1.02E+05	-8.18E+05	9.32E+05
.20	2.72E+04	-1.08E+05	2.10E+05	-1.08E+05	2.10E+05	-6.75E+05	9.14E+05
.40	7.68E+04	-1.60E+05	4.41E+05	-1.59E+05	4.41E+05	-5.89E+05	9.10E+05
.80	2.33E+05	-1.66E+05	9.05E+05	-1.64E+05	9.04E+05	-4.95E+05	8.39E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K–147. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.02E+04	5.06E+04	-4.01E+04	5.07E+04	-8.96E+05	9.20E+05
.10	6.79E+03	-7.75E+04	9.72E+04	-7.74E+04	9.73E+04	-8.42E+05	9.05E+05
.20	1.74E+04	-1.27E+05	1.90E+05	-1.27E+05	1.90E+05	-7.22E+05	8.66E+05
.40	5.80E+04	-1.70E+05	3.75E+05	-1.70E+05	3.76E+05	-5.70E+05	7.95E+05
.80	1.91E+05	-2.12E+05	7.44E+05	-2.11E+05	7.45E+05	-5.03E+05	6.92E+05

Table K–148. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.46	-4.90E+04	4.90E+04	-4.90E+04	4.90E+04	-9.80E+05	9.80E+05
.10	17.7	-9.80E+04	9.80E+04	-9.80E+04	9.80E+04	-9.80E+05	9.79E+05
.20	70.9	-1.96E+05	1.96E+05	-1.96E+05	1.96E+05	-9.80E+05	9.79E+05
.40	283.	-3.92E+05	3.92E+05	-3.92E+05	3.92E+05	-9.80E+05	9.79E+05
.80	1.13E+03	-7.84E+05	7.84E+05	-7.84E+05	7.84E+05	-9.81E+05	9.78E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-149. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-957.	-4.84E+04	4.73E+04	-4.83E+04	4.73E+04	-9.48E+05	9.65E+05
.10	948.	-8.81E+04	9.58E+04	-8.81E+04	9.58E+04	-8.90E+05	9.48E+05
.20	1.12E+04	-1.41E+05	1.92E+05	-1.41E+05	1.92E+05	-7.63E+05	9.05E+05
.40	5.13E+04	-1.76E+05	3.83E+05	-1.76E+05	3.83E+05	-5.68E+05	8.29E+05
.80	1.82E+05	-1.77E+05	7.56E+05	-1.77E+05	7.55E+05	-4.49E+05	7.16E+05

Table K-150. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-981.	-4.86E+04	4.74E+04	-4.86E+04	4.73E+04	-9.51E+05	9.67E+05
.10	783.	-8.95E+04	9.60E+04	-8.95E+04	9.59E+04	-9.03E+05	9.52E+05
.20	1.04E+04	-1.47E+05	1.93E+05	-1.47E+05	1.93E+05	-7.89E+05	9.12E+05
.40	4.84E+04	-1.97E+05	3.85E+05	-1.97E+05	3.85E+05	-6.13E+05	8.41E+05
.80	1.73E+05	-1.90E+05	7.61E+05	-1.83E+05	7.61E+05	-4.45E+05	7.35E+05

Table K–151. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–152. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-66.5	-4.38E+04	4.56E+04	-4.35E+04	4.51E+04	-8.68E+05	9.04E+05
.10	3.04E+03	-7.84E+04	9.20E+04	-7.77E+04	9.11E+04	-8.07E+05	8.81E+05
.20	1.17E+04	-1.39E+05	1.85E+05	-1.38E+05	1.83E+05	-7.50E+05	8.56E+05
.40	4.88E+04	-1.87E+05	3.74E+05	-1.86E+05	3.70E+05	-5.86E+05	8.03E+05
.80	1.74E+05	-1.91E+05	7.60E+05	-1.79E+05	7.55E+05	-4.40E+05	7.26E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-20. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-153. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-8.98	-3.64E+04	3.53E+04	-3.54E+04	3.52E+04	-7.07E+05	7.05E+05
.10	-18.0	-7.28E+04	7.07E+04	-7.07E+04	7.04E+04	-7.07E+05	7.05E+05
.20	-35.9	-1.46E+05	1.41E+05	-1.41E+05	1.41E+05	-7.07E+05	7.05E+05
.40	-71.8	-2.91E+05	2.83E+05	-2.83E+05	2.82E+05	-7.07E+05	7.05E+05
.80	-144.	-5.83E+05	5.66E+05	-5.66E+05	5.64E+05	-7.07E+05	7.05E+05

Table K-154. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.74E+03	-3.20E+04	4.15E+04	-3.12E+04	4.14E+04	-6.79E+05	7.73E+05
.10	8.66E+03	-5.40E+04	8.02E+04	-5.30E+04	8.00E+04	-6.17E+05	7.13E+05
.20	2.71E+04	-8.77E+04	1.64E+05	-8.70E+04	1.63E+05	-5.70E+05	6.80E+05
.40	7.68E+04	-1.40E+05	3.43E+05	-1.37E+05	3.41E+05	-5.33E+05	6.60E+05
.80	2.33E+05	-2.34E+05	7.05E+05	-2.30E+05	6.98E+05	-5.78E+05	5.82E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K–155. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-3.61E+04	4.64E+04	-3.59E+04	4.62E+04	-8.13E+05	8.30E+05
.10	6.78E+03	-7.03E+04	8.86E+04	-7.01E+04	8.83E+04	-7.69E+05	8.15E+05
.20	1.73E+04	-1.20E+05	1.73E+05	-1.19E+05	1.72E+05	-6.83E+05	7.76E+05
.40	5.79E+04	-1.87E+05	3.41E+05	-1.86E+05	3.40E+05	-6.09E+05	7.05E+05
.80	1.91E+05	-2.95E+05	6.76E+05	-2.90E+05	6.73E+05	-6.02E+05	6.03E+05

Table K–156. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	11.6	-4.12E+04	4.12E+04	-4.12E+04	4.12E+04	-8.24E+05	8.24E+05
.10	46.5	-8.25E+04	8.25E+04	-8.24E+04	8.24E+04	-8.24E+05	8.23E+05
.20	186.	-1.65E+05	1.65E+05	-1.65E+05	1.65E+05	-8.25E+05	8.23E+05
.40	745.	-3.30E+05	3.30E+05	-3.30E+05	3.29E+05	-8.26E+05	8.22E+05
.80	2.98E+03	-6.60E+05	6.60E+05	-6.59E+05	6.59E+05	-8.28E+05	8.20E+05

Table K-157. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-956.	-4.06E+04	3.96E+04	-4.06E+04	3.95E+04	-7.93E+05	8.10E+05
.10	942.	-7.27E+04	8.04E+04	-7.26E+04	8.03E+04	-7.36E+05	7.93E+05
.20	1.11E+04	-1.11E+05	1.61E+05	-1.11E+05	1.61E+05	-6.10E+05	7.50E+05
.40	5.09E+04	-1.32E+05	3.21E+05	-1.31E+05	3.21E+05	-4.56E+05	6.75E+05
.80	1.82E+05	-1.45E+05	6.32E+05	-1.44E+05	6.31E+05	-4.06E+05	5.62E+05

Table K-158. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.03E+03	-4.13E+04	3.97E+04	-4.13E+04	3.97E+04	-8.05E+05	8.14E+05
.10	411.	-7.70E+04	8.09E+04	-7.69E+04	8.08E+04	-7.73E+05	8.04E+05
.20	8.63E+03	-1.29E+05	1.63E+05	-1.29E+05	1.63E+05	-6.87E+05	7.72E+05
.40	4.13E+04	-1.84E+05	3.27E+05	-1.82E+05	3.27E+05	-5.57E+05	7.14E+05
.80	1.47E+05	-2.16E+05	6.48E+05	-1.97E+05	6.47E+05	-4.29E+05	6.26E+05

Table K–159. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–160. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-449.	-3.92E+04	3.98E+04	-3.89E+04	3.95E+04	-7.69E+05	7.98E+05
.10	2.24E+03	-6.95E+04	8.09E+04	-6.90E+04	8.00E+04	-7.12E+05	7.78E+05
.20	8.51E+03	-1.29E+05	1.62E+05	-1.27E+05	1.60E+05	-6.76E+05	7.59E+05
.40	4.03E+04	-1.78E+05	3.32E+05	-1.75E+05	3.28E+05	-5.37E+05	7.20E+05
.80	1.52E+05	-1.98E+05	6.84E+05	-1.67E+05	6.79E+05	-3.99E+05	6.59E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-21. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-161. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-419.	-3.56E+04	3.55E+04	-3.51E+04	3.43E+04	-6.94E+05	6.95E+05
.10	-838.	-7.12E+04	7.09E+04	-7.02E+04	6.87E+04	-6.94E+05	6.95E+05
.20	-1.68E+03	-1.42E+05	1.42E+05	-1.40E+05	1.37E+05	-6.94E+05	6.95E+05
.40	-3.35E+03	-2.85E+05	2.84E+05	-2.81E+05	2.75E+05	-6.94E+05	6.95E+05
.80	-6.71E+03	-5.70E+05	5.68E+05	-5.62E+05	5.49E+05	-6.94E+05	6.95E+05

Table K-162. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.33E+03	-3.09E+04	3.04E+04	-2.95E+04	2.98E+04	-6.37E+05	5.49E+05
.10	7.82E+03	-6.00E+04	6.34E+04	-5.89E+04	6.15E+04	-6.67E+05	5.37E+05
.20	2.54E+04	-1.19E+05	1.29E+05	-1.17E+05	1.22E+05	-7.12E+05	4.82E+05
.40	7.35E+04	-2.36E+05	2.63E+05	-2.30E+05	2.52E+05	-7.58E+05	4.45E+05
.80	2.25E+05	-4.71E+05	7.15E+05	-4.55E+05	6.76E+05	-8.49E+05	5.64E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-163. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-3.66E+04	4.50E+04	-3.69E+04	4.56E+04	-8.32E+05	8.18E+05
.10	6.78E+03	-7.75E+04	8.58E+04	-7.79E+04	8.70E+04	-8.47E+05	8.02E+05
.20	1.73E+04	-1.59E+05	1.67E+05	-1.59E+05	1.70E+05	-8.83E+05	7.62E+05
.40	5.78E+04	-3.22E+05	3.37E+05	-3.18E+05	3.36E+05	-9.39E+05	6.95E+05
.80	1.91E+05	-6.49E+05	8.73E+05	-6.21E+05	8.38E+05	-1.01E+06	8.10E+05

Table K-164. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	16.5	-2.37E+04	2.38E+04	-2.34E+04	2.39E+04	-4.69E+05	4.78E+05
.10	65.7	-4.74E+04	4.76E+04	-4.69E+04	4.80E+04	-4.69E+05	4.79E+05
.20	262.	-9.48E+04	9.58E+04	-9.37E+04	9.68E+04	-4.70E+05	4.82E+05
.40	1.05E+03	-1.91E+05	1.95E+05	-1.88E+05	1.96E+05	-4.74E+05	4.89E+05
.80	4.18E+03	-3.93E+05	4.08E+05	-3.88E+05	4.05E+05	-4.90E+05	5.01E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-165. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-949.	-2.68E+04	2.41E+04	-2.65E+04	2.44E+04	-5.11E+05	5.07E+05
.10	974.	-5.22E+04	4.98E+04	-5.17E+04	5.03E+04	-5.26E+05	4.93E+05
.20	1.12E+04	-1.03E+05	1.02E+05	-1.02E+05	1.03E+05	-5.67E+05	4.57E+05
.40	5.13E+04	-2.08E+05	2.75E+05	-2.05E+05	2.71E+05	-6.42E+05	5.49E+05
.80	1.83E+05	-4.35E+05	7.88E+05	-4.29E+05	7.77E+05	-7.65E+05	7.42E+05

Table K-166. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.27E+03	-2.71E+04	2.55E+04	-2.58E+04	2.57E+04	-4.90E+05	5.40E+05
.10	-1.92E+03	-5.09E+04	5.86E+04	-4.88E+04	5.65E+04	-4.69E+05	5.85E+05
.20	-870.	-9.86E+04	1.49E+05	-8.96E+04	1.38E+05	-4.44E+05	6.92E+05
.40	1.25E+04	-1.77E+05	4.82E+05	-1.46E+05	4.01E+05	-3.96E+05	9.71E+05
.80	6.72E+04	-2.46E+05	1.51E+06	-1.89E+05	1.20E+06	-3.20E+05	1.41E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K-167. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-168. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-2.43E+03	-4.08E+04	4.26E+04	-3.97E+04	3.98E+04	-7.45E+05	8.44E+05
.10	-2.35E+03	-7.95E+04	7.67E+04	-7.61E+04	7.35E+04	-7.38E+05	7.59E+05
.20	-9.81E+03	-1.59E+05	1.53E+05	-1.53E+05	1.47E+05	-7.16E+05	7.84E+05
.40	-4.69E+03	-2.96E+05	4.86E+05	-2.69E+05	3.24E+05	-6.60E+05	8.22E+05
.80	8.27E+04	-5.22E+05	1.64E+06	-3.70E+05	9.31E+05	-5.65E+05	1.06E+06

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-22. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-169. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-36.7	-3.24E+04	3.21E+04	-2.89E+04	2.86E+04	-5.78E+05	5.73E+05
.10	-73.3	-6.47E+04	6.42E+04	-5.78E+04	5.73E+04	-5.78E+05	5.73E+05
.20	-147.	-1.29E+05	1.28E+05	-1.16E+05	1.15E+05	-5.78E+05	5.73E+05
.40	-293.	-2.59E+05	2.57E+05	-2.31E+05	2.29E+05	-5.78E+05	5.73E+05
.80	-587.	-5.18E+05	5.14E+05	-4.63E+05	4.58E+05	-5.78E+05	5.73E+05

Table K-170. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.71E+03	-3.15E+04	3.75E+04	-2.88E+04	3.41E+04	-6.31E+05	6.27E+05
.10	8.60E+03	-5.49E+04	7.73E+04	-5.19E+04	7.03E+04	-6.05E+05	6.17E+05
.20	2.70E+04	-9.66E+04	1.49E+05	-9.51E+04	1.36E+05	-6.10E+05	5.43E+05
.40	7.65E+04	-1.84E+05	3.08E+05	-1.84E+05	2.80E+05	-6.50E+05	5.09E+05
.80	2.32E+05	-3.57E+05	6.43E+05	-3.54E+05	5.81E+05	-7.33E+05	4.36E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-171. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-2.63E+04	3.57E+04	-2.63E+04	3.56E+04	-6.19E+05	6.19E+05
.10	6.79E+03	-5.46E+04	6.72E+04	-5.45E+04	6.71E+04	-6.13E+05	6.03E+05
.20	1.74E+04	-1.05E+05	1.30E+05	-1.05E+05	1.30E+05	-6.13E+05	5.64E+05
.40	5.80E+04	-1.98E+05	2.56E+05	-1.97E+05	2.56E+05	-6.39E+05	4.94E+05
.80	1.91E+05	-3.76E+05	5.07E+05	-3.73E+05	5.06E+05	-7.06E+05	3.93E+05

Table K-172. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.07E+04	-5.77E+04	3.64E+04	-5.77E+04	3.64E+04	-9.41E+05	9.40E+05
.10	-1.06E+04	-1.05E+05	8.34E+04	-1.05E+05	8.34E+04	-9.41E+05	9.40E+05
.20	-1.05E+04	-1.99E+05	1.78E+05	-1.99E+05	1.77E+05	-9.41E+05	9.40E+05
.40	-9.83E+03	-3.87E+05	3.66E+05	-3.87E+05	3.66E+05	-9.42E+05	9.39E+05
.80	-7.29E+03	-7.63E+05	7.43E+05	-7.62E+05	7.42E+05	-9.44E+05	9.37E+05

Table K-173. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.16E+04	-5.72E+04	3.47E+04	-5.72E+04	3.47E+04	-9.11E+05	9.26E+05
.10	-9.70E+03	-9.59E+04	8.13E+04	-9.59E+04	8.12E+04	-8.62E+05	9.09E+05
.20	659.	-1.51E+05	1.74E+05	-1.51E+05	1.74E+05	-7.60E+05	8.66E+05
.40	4.11E+04	-2.21E+05	3.57E+05	-2.21E+05	3.57E+05	-6.55E+05	7.90E+05
.80	1.74E+05	-3.20E+05	7.16E+05	-3.19E+05	7.16E+05	-6.17E+05	6.77E+05

Table K-174. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.60E+04	-5.18E+04	1.87E+04	-5.06E+04	1.51E+04	-6.92E+05	6.22E+05
.10	-1.97E+04	-1.06E+05	5.11E+04	-1.05E+05	5.10E+04	-8.51E+05	7.07E+05
.20	-2.03E+04	-1.94E+05	1.33E+05	-1.89E+05	1.33E+05	-8.45E+05	7.67E+05
.40	5.06E+03	-2.92E+05	3.02E+05	-2.86E+05	3.01E+05	-7.28E+05	7.41E+05
.80	1.15E+05	-3.80E+05	6.24E+05	-3.66E+05	6.23E+05	-6.01E+05	6.35E+05

Table K-175. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-176. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-84.4	-4.02E+04	4.22E+04	-3.99E+04	4.17E+04	-7.96E+05	8.36E+05
.10	2.15E+03	-7.11E+04	8.39E+04	-7.04E+04	8.30E+04	-7.26E+05	8.09E+05
.20	1.23E+04	-1.26E+05	1.68E+05	-1.26E+05	1.66E+05	-6.89E+05	7.69E+05
.40	4.29E+04	-1.79E+05	3.39E+05	-1.76E+05	3.36E+05	-5.47E+05	7.32E+05
.80	1.58E+05	-2.58E+05	6.98E+05	-2.28E+05	6.92E+05	-4.82E+05	6.69E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K–23. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-177. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-88.2	-1.78E+04	1.75E+04	-1.77E+04	1.74E+04	-3.53E+05	3.50E+05
.10	-176.	-3.56E+04	3.50E+04	-3.55E+04	3.48E+04	-3.53E+05	3.50E+05
.20	-353.	-7.11E+04	7.00E+04	-7.10E+04	6.96E+04	-3.53E+05	3.50E+05
.40	-705.	-1.42E+05	1.40E+05	-1.42E+05	1.39E+05	-3.53E+05	3.50E+05
.80	-1.41E+03	-2.84E+05	2.80E+05	-2.84E+05	2.79E+05	-3.53E+05	3.50E+05

Table K-178. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.66E+03	-1.57E+04	2.27E+04	-1.56E+04	2.26E+04	-3.66E+05	3.98E+05
.10	8.50E+03	-2.72E+04	4.53E+04	-2.69E+04	4.47E+04	-3.54E+05	3.62E+05
.20	2.68E+04	-4.74E+04	8.94E+04	-4.68E+04	8.89E+04	-3.68E+05	3.11E+05
.40	7.62E+04	-8.58E+04	1.90E+05	-8.36E+04	1.88E+05	-4.00E+05	2.78E+05
.80	2.31E+05	-1.61E+05	4.99E+05	-1.56E+05	4.93E+05	-4.84E+05	3.27E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-179. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-1.33E+04	2.25E+04	-1.33E+04	2.25E+04	-3.59E+05	3.57E+05
.10	6.78E+03	-2.94E+04	4.09E+04	-2.92E+04	4.09E+04	-3.60E+05	3.42E+05
.20	1.73E+04	-5.87E+04	7.78E+04	-5.80E+04	7.78E+04	-3.76E+05	3.02E+05
.40	5.79E+04	-1.14E+05	1.51E+05	-1.11E+05	1.51E+05	-4.23E+05	2.33E+05
.80	1.91E+05	-2.21E+05	5.44E+05	-2.12E+05	5.41E+05	-5.04E+05	4.38E+05

Table K-180. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.06E+04	-3.87E+04	1.74E+04	-3.87E+04	1.74E+04	-5.61E+05	5.60E+05
.10	-1.05E+04	-6.68E+04	4.54E+04	-6.67E+04	4.55E+04	-5.62E+05	5.59E+05
.20	-9.79E+03	-1.23E+05	1.02E+05	-1.23E+05	1.02E+05	-5.64E+05	5.57E+05
.40	-7.13E+03	-2.35E+05	2.14E+05	-2.35E+05	2.14E+05	-5.69E+05	5.53E+05
.80	3.51E+03	-4.59E+05	4.39E+05	-4.59E+05	4.39E+05	-5.78E+05	5.44E+05

Table K-181. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$ Mean (kN-m)	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
		Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.16E+04	-3.81E+04	1.55E+04	-3.81E+04	1.55E+04	-5.29E+05	5.41E+05
.10	-9.56E+03	-5.87E+04	4.28E+04	-5.87E+04	4.28E+04	-4.91E+05	5.24E+05
.20	1.14E+03	-8.57E+04	9.70E+04	-8.55E+04	9.71E+04	-4.33E+05	4.80E+05
.40	4.30E+04	-1.22E+05	2.04E+05	-1.22E+05	2.04E+05	-4.12E+05	4.02E+05
.80	1.82E+05	-1.76E+05	4.09E+05	-1.74E+05	4.09E+05	-4.45E+05	2.84E+05

Table K-182. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$ Mean (kN-m)	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
		Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.59E+04	-4.67E+04	1.36E+04	-3.57E+04	2.76E+03	-3.95E+05	3.74E+05
.10	-2.05E+04	-6.16E+04	2.70E+04	-5.46E+04	1.38E+04	-3.41E+05	3.43E+05
.20	-2.51E+04	-1.12E+05	6.14E+04	-1.06E+05	5.02E+04	-4.05E+05	3.77E+05
.40	-1.34E+04	-1.70E+05	1.54E+05	-1.63E+05	1.54E+05	-3.74E+05	4.17E+05
.80	5.50E+04	-2.52E+05	3.93E+05	-2.27E+05	3.93E+05	-3.52E+05	4.22E+05

Table K–183. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	-6.63E+04	-1.33E+05	2.92E+04	-1.29E+05	2.82E+04	-3.11E+05	4.73E+05
.40	-4.92E+04	-1.54E+05	1.38E+05	-1.51E+05	1.32E+05	-2.54E+05	4.53E+05
.80	3.87E+04	-2.07E+05	4.09E+05	-1.84E+05	4.06E+05	-2.79E+05	4.59E+05

Table K–184. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-217.	-3.23E+04	3.35E+04	-3.21E+04	3.32E+04	-6.38E+05	6.69E+05
.10	1.16E+03	-5.60E+04	6.60E+04	-5.55E+04	6.53E+04	-5.67E+05	6.42E+05
.20	1.11E+04	-1.02E+05	1.32E+05	-1.03E+05	1.31E+05	-5.69E+05	5.99E+05
.40	3.35E+04	-1.49E+05	2.72E+05	-1.43E+05	2.69E+05	-4.40E+05	5.89E+05
.80	1.35E+05	-2.19E+05	5.81E+05	-1.71E+05	5.75E+05	-3.82E+05	5.51E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-24. Minimum and maximum of filtered $(M_y^{ptot} - \langle M_y^{ptot} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-185. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$ Mean (kN-m)	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
		Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-792.	-4.40E+04	3.59E+04	-3.60E+04	3.48E+04	-7.05E+05	7.12E+05
.10	-1.58E+03	-8.81E+04	7.18E+04	-7.21E+04	6.96E+04	-7.05E+05	7.12E+05
.20	-3.17E+03	-1.76E+05	1.44E+05	-1.44E+05	1.39E+05	-7.05E+05	7.12E+05
.40	-6.34E+03	-3.52E+05	2.87E+05	-2.88E+05	2.79E+05	-7.05E+05	7.12E+05
.80	-1.27E+04	-7.05E+05	5.75E+05	-5.77E+05	5.57E+05	-7.05E+05	7.12E+05

Table K-186. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$ Mean (kN-m)	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
		Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	1.96E+03	-3.93E+04	3.63E+04	-3.11E+04	3.49E+04	-6.60E+05	6.58E+05
.10	7.07E+03	-7.19E+04	7.46E+04	-5.73E+04	7.09E+04	-6.44E+05	6.38E+05
.20	2.39E+04	-1.31E+05	1.45E+05	-1.07E+05	1.40E+05	-6.56E+05	5.79E+05
.40	7.06E+04	-2.22E+05	2.98E+05	-2.02E+05	2.87E+05	-6.82E+05	5.40E+05
.80	2.19E+05	-4.32E+05	6.14E+05	-3.99E+05	5.88E+05	-7.72E+05	4.62E+05

Table K-187. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-2.67E+04	3.71E+04	-2.57E+04	3.59E+04	-6.08E+05	6.25E+05
.10	6.78E+03	-5.74E+04	7.70E+04	-5.56E+04	7.42E+04	-6.24E+05	6.74E+05
.20	1.73E+04	-1.19E+05	1.82E+05	-1.15E+05	1.75E+05	-6.63E+05	7.88E+05
.40	5.78E+04	-2.43E+05	4.65E+05	-2.36E+05	4.45E+05	-7.33E+05	9.69E+05
.80	1.91E+05	-4.93E+05	1.21E+06	-4.78E+05	1.16E+06	-8.36E+05	1.21E+06

Table K-188. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.08E+04	-2.85E+04	8.13E+03	-2.84E+04	7.90E+03	-3.52E+05	3.74E+05
.10	-1.11E+04	-4.55E+04	2.79E+04	-4.52E+04	2.74E+04	-3.41E+05	3.85E+05
.20	-1.23E+04	-7.66E+04	7.03E+04	-7.62E+04	6.90E+04	-3.19E+05	4.07E+05
.40	-1.73E+04	-1.31E+05	1.66E+05	-1.31E+05	1.63E+05	-2.83E+05	4.51E+05
.80	-3.73E+04	-2.80E+05	4.05E+05	-2.74E+05	3.95E+05	-2.96E+05	5.40E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-189. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.17E+04	-3.00E+04	7.54E+03	-2.98E+04	7.30E+03	-3.62E+05	3.81E+05
.10	-1.02E+04	-4.60E+04	2.81E+04	-4.54E+04	2.76E+04	-3.53E+05	3.77E+05
.20	-1.35E+03	-7.45E+04	7.22E+04	-7.29E+04	7.09E+04	-3.58E+05	3.61E+05
.40	3.30E+04	-1.29E+05	1.73E+05	-1.29E+05	1.69E+05	-4.06E+05	3.40E+05
.80	1.42E+05	-2.77E+05	4.60E+05	-2.71E+05	4.50E+05	-5.16E+05	3.85E+05

Table K-190. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.62E+04	-4.27E+04	9.37E+03	-3.79E+04	-1.78E+03	-4.34E+05	2.88E+05
.10	-2.24E+04	-5.57E+04	2.96E+04	-5.28E+04	1.80E+04	-3.04E+05	4.04E+05
.20	-3.21E+04	-1.40E+05	7.50E+04	-1.32E+05	5.44E+04	-4.98E+05	4.33E+05
.40	-2.96E+04	-2.68E+05	3.14E+05	-2.50E+05	2.26E+05	-5.50E+05	6.39E+05
.80	5.60E+04	-4.98E+05	1.28E+06	-3.76E+05	9.06E+05	-5.40E+05	1.06E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K–191. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	-3.83E+04	-1.13E+05	2.58E+04	-1.03E+05	1.66E+04	-3.23E+05	2.74E+05
.40	-46.3	-3.00E+05	4.05E+05	-2.37E+05	3.26E+05	-5.93E+05	8.16E+05
.80	1.08E+05	-9.46E+05	1.46E+06	-8.84E+05	9.91E+05	-1.24E+06	1.10E+06

Table K–192. Minimum and Maximum of Variables M_y^{ptot} and $(M_y^{\text{ptot}})^* = (M_y^{\text{ptot}} - \langle M_y^{\text{ptot}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{ptot}} \rangle$	Unfiltered M_y^{ptot}		Filtered M_y^{ptot}		Filtered $(M_y^{\text{ptot}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.68E+03	-3.11E+04	3.84E+04	-2.95E+04	3.42E+04	-5.57E+05	7.18E+05
.10	-5.55E+03	-6.33E+04	6.16E+04	-5.87E+04	5.38E+04	-5.32E+05	5.94E+05
.20	-143.	-1.23E+05	1.89E+05	-1.14E+05	1.83E+05	-5.69E+05	9.14E+05
.40	-2.14E+04	-2.35E+05	5.54E+05	-1.86E+05	3.47E+05	-4.13E+05	9.22E+05
.80	1.22E+05	-3.90E+05	1.37E+06	-2.22E+05	7.81E+05	-4.30E+05	8.24E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-25. Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–193. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–194. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.09	1.76	16.2	1.86	16.1	-105.	181.
.10	10.5	1.76	18.6	2.04	18.2	-84.4	77.3
.20	12.9	-1.64E+03	53.5	-212.	53.6	-1.13E+03	204.
.40	33.6	-62.3	128.	-26.5	128.	-150.	235.
.80	90.2	-80.4	984.	-84.3	367.	-218.	346.

Table K–195. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.37	-8.29	-10.6	11.0
.10	-8.87	-9.37	-8.28	-9.36	-8.29	-4.95	5.75
.20	-9.37	-12.0	-7.55	-11.9	-7.55	-12.9	9.07
.40	-8.36	-12.0	-6.62	-11.7	-6.63	-8.26	4.33
.80	-7.06	-12.0	-2.14	-10.7	-2.15	-4.58	6.14

Table K–196. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–197. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.2	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.1	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.6	57.3
.40	-39.1	-62.0	-16.5	-62.0	-16.5	-57.1	56.5
.80	-41.1	-84.9	-3.53	-84.9	-3.53	-54.8	46.9

Table K–198. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.2	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.1	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.6	57.3
.40	-39.1	-62.0	-16.5	-62.0	-16.5	-57.1	56.5
.80	-41.1	-84.9	-3.53	-84.9	-3.53	-54.8	46.9

Table K–199. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–200. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-26. Minimum and maximum of filtered $(F_x^{hst} - \langle F_x^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–201. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–202. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.10	1.77	16.2	2.00	16.1	-102.	180.
.10	10.5	1.76	18.6	2.32	17.8	-81.5	72.8
.20	21.7	1.76	53.5	2.56	53.3	-95.8	158.
.40	33.8	-60.6	128.	-26.2	126.	-150.	232.
.80	88.5	-78.5	368.	-69.3	366.	-197.	347.

Table K–203. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.28	-9.37	-8.29	-10.5	11.0
.10	-8.87	-9.37	-8.28	-9.35	-8.30	-4.76	5.68
.20	-9.38	-12.0	-7.55	-11.9	-7.56	-12.7	9.10
.40	-8.34	-12.0	-6.63	-11.0	-6.64	-6.61	4.26
.80	-7.06	-12.0	-2.14	-9.84	-2.17	-3.47	6.11

Table K–204. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–205. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.1	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.0	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-61.9	-16.5	-57.1	56.5
.80	-41.0	-84.9	-3.53	-84.8	-3.54	-54.8	46.9

Table K–206. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.1	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.0	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-61.9	-16.5	-57.1	56.5
.80	-41.0	-84.9	-3.53	-84.8	-3.54	-54.8	46.9

Table K–207. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–208. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-27. Minimum and maximum of filtered $(F_x^{hst} - \langle F_x^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–209. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–210. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.10	1.77	16.1	2.51	15.7	-91.9	173.
.10	10.5	1.78	18.3	3.07	16.5	-73.9	60.7
.20	21.7	2.20	53.5	4.72	54.2	-84.9	162.
.40	34.1	-26.8	128.	-27.4	124.	-154.	224.
.80	107.	-78.3	984.	-69.0	351.	-220.	305.

Table K–211. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.36	-8.29	-10.4	11.0
.10	-8.87	-9.37	-8.29	-9.21	-8.41	-3.43	4.57
.20	-9.37	-12.0	-7.55	-11.9	-7.60	-12.8	8.89
.40	-8.34	-11.8	-6.63	-9.59	-6.76	-3.12	3.95
.80	-7.06	-11.4	-2.14	-9.74	-2.55	-3.35	5.64

Table K–212. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–213. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-55.6	57.7
.10	-39.0	-44.6	-33.3	-44.6	-33.4	-55.5	56.6
.20	-39.0	-50.3	-27.5	-50.1	-27.6	-55.9	56.6
.40	-39.1	-62.0	-16.5	-61.7	-16.7	-56.5	56.0
.80	-41.1	-84.9	-3.53	-84.4	-3.67	-54.2	46.7

Table K–214. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-55.6	57.7
.10	-39.0	-44.6	-33.3	-44.6	-33.4	-55.5	56.6
.20	-39.0	-50.3	-27.5	-50.1	-27.6	-55.9	56.6
.40	-39.1	-62.0	-16.5	-61.7	-16.7	-56.5	56.0
.80	-41.1	-84.9	-3.53	-84.4	-3.67	-54.2	46.7

Table K–215. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–216. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-28. Minimum and maximum of filtered $(F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–217. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–218. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.10	1.76	16.2	1.86	16.1	-105.	181.
.10	10.5	1.76	18.6	2.04	18.2	-84.4	77.3
.20	12.9	-1.64E+03	53.5	-212.	53.6	-1.13E+03	204.
.40	33.6	-62.3	128.	-26.5	128.	-150.	235.
.80	90.2	-80.4	984.	-84.3	367.	-218.	346.

Table K–219. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.37	-8.29	-10.6	11.0
.10	-8.87	-9.37	-8.28	-9.36	-8.29	-4.95	5.75
.20	-9.37	-12.0	-7.55	-11.9	-7.55	-12.9	9.07
.40	-8.36	-12.0	-6.62	-11.7	-6.63	-8.26	4.33
.80	-7.06	-12.0	-2.14	-10.7	-2.15	-4.58	6.14

Table K–220. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–221. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.2	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.1	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-62.0	-16.5	-57.1	56.5
.80	-41.1	-84.9	-3.53	-84.9	-3.53	-54.8	46.9

Table K–222. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.2	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.1	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-62.0	-16.5	-57.1	56.5
.80	-41.1	-84.9	-3.53	-84.9	-3.53	-54.8	46.9

Table K-223. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-224. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-29. Minimum and maximum of filtered $(F_x^{hst} - \langle F_x^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-225. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-226. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.10	1.77	16.2	2.00	16.1	-102.	180.
.10	10.5	1.76	18.6	2.32	17.8	-81.5	72.8
.20	21.7	1.76	53.5	2.56	53.3	-95.8	158.
.40	33.8	-60.6	128.	-26.2	126.	-150.	232.
.80	88.5	-78.5	368.	-69.3	366.	-197.	347.

Table K–227. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.28	-9.37	-8.29	-10.5	11.0
.10	-8.87	-9.37	-8.28	-9.35	-8.30	-4.76	5.68
.20	-9.38	-12.0	-7.55	-11.9	-7.56	-12.7	9.10
.40	-8.34	-12.0	-6.63	-11.0	-6.64	-6.61	4.26
.80	-7.06	-12.0	-2.14	-9.84	-2.17	-3.47	6.11

Table K–228. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–229. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.1	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.0	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-61.9	-16.5	-57.1	56.5
.80	-41.0	-84.9	-3.53	-84.8	-3.54	-54.8	46.9

Table K–230. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-56.1	58.3
.10	-39.0	-44.6	-33.3	-44.6	-33.3	-56.0	57.2
.20	-39.0	-50.3	-27.5	-50.3	-27.5	-56.5	57.3
.40	-39.1	-62.0	-16.5	-61.9	-16.5	-57.1	56.5
.80	-41.0	-84.9	-3.53	-84.8	-3.54	-54.8	46.9

Table K–231. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–232. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-30. Minimum and maximum of filtered $(F_x^{hst} - \langle F_x^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-233. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-234. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	7.10	1.77	16.1	2.51	15.7	-91.9	173.
.10	10.5	1.78	18.3	3.07	16.5	-73.9	60.7
.20	21.7	2.20	53.5	4.72	54.2	-84.9	162.
.40	34.1	-26.8	128.	-27.4	124.	-154.	224.
.80	107.	-78.3	984.	-69.0	351.	-220.	305.

Table K-235. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.84	-9.37	-8.29	-9.36	-8.29	-10.4	11.0
.10	-8.87	-9.37	-8.29	-9.21	-8.41	-3.43	4.57
.20	-9.37	-12.0	-7.55	-11.9	-7.60	-12.8	8.89
.40	-8.34	-11.8	-6.63	-9.59	-6.76	-3.12	3.95
.80	-7.06	-11.4	-2.14	-9.74	-2.55	-3.35	5.64

Table K-236. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-237. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-55.6	57.7
.10	-39.0	-44.6	-33.3	-44.6	-33.4	-55.5	56.6
.20	-39.0	-50.3	-27.5	-50.1	-27.6	-55.9	56.6
.40	-39.1	-62.0	-16.5	-61.7	-16.7	-56.5	56.0
.80	-41.1	-84.9	-3.53	-84.4	-3.67	-54.2	46.7

Table K-238. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-39.1	-41.9	-36.2	-41.9	-36.2	-55.6	57.7
.10	-39.0	-44.6	-33.3	-44.6	-33.4	-55.5	56.6
.20	-39.0	-50.3	-27.5	-50.1	-27.6	-55.9	56.6
.40	-39.1	-62.0	-16.5	-61.7	-16.7	-56.5	56.0
.80	-41.1	-84.9	-3.53	-84.4	-3.67	-54.2	46.7

Table K-239. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-240. Minimum and Maximum of Variables F_x^{hst} and $(F_x^{\text{hst}})^* = (F_x^{\text{hst}} - \langle F_x^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{hst}} \rangle$	Unfiltered F_x^{hst}		Filtered F_x^{hst}		Filtered $(F_x^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-31. Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–241. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.96E+04	9.22E+04	-1.27E+05	1.26E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.32E+04	9.86E+04	-1.27E+05	1.26E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.06E+04	1.11E+05	-1.27E+05	1.26E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.52E+04	1.36E+05	-1.27E+05	1.26E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.54E+04	1.87E+05	-1.27E+05	1.26E+05

Table K–242. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.91E+04	9.27E+04	-1.36E+05	1.36E+05
.10	8.58E+04	7.26E+04	9.88E+04	7.27E+04	9.87E+04	-1.32E+05	1.29E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.20E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.02E+04	1.32E+05	-1.14E+05	1.16E+05
.80	8.95E+04	7.38E+03	1.82E+05	7.37E+03	1.82E+05	-1.03E+05	1.16E+05

Table K-243. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.90E+04	9.16E+04	-1.25E+05	1.26E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.29E+04	9.78E+04	-1.24E+05	1.25E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.14E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.04E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	7.92E+03	1.81E+05	7.97E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-244. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.92E+04	9.19E+04	-1.26E+05	1.26E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.29E+04	9.82E+04	-1.26E+05	1.26E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.03E+04	1.11E+05	-1.26E+05	1.26E+05
.40	8.56E+04	3.50E+04	1.36E+05	3.51E+04	1.36E+05	-1.26E+05	1.26E+05
.80	8.56E+04	-1.55E+04	1.87E+05	-1.54E+04	1.87E+05	-1.26E+05	1.26E+05

Table K-245. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.26E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.35E+05	-1.15E+05	1.20E+05
.80	8.97E+04	8.02E+03	1.81E+05	8.04E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-246. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.26E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.35E+05	-1.15E+05	1.20E+05
.80	8.97E+04	8.02E+03	1.81E+05	8.04E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-247. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-248. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.22E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-32. Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-249. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.96E+04	9.22E+04	-1.27E+05	1.26E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.32E+04	9.85E+04	-1.27E+05	1.26E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.05E+04	1.11E+05	-1.27E+05	1.26E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.51E+04	1.36E+05	-1.27E+05	1.26E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.57E+04	1.87E+05	-1.27E+05	1.26E+05

Table K-250. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.91E+04	9.27E+04	-1.36E+05	1.35E+05
.10	8.58E+04	7.26E+04	9.88E+04	7.26E+04	9.87E+04	-1.32E+05	1.29E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.15E+04	1.10E+05	-1.21E+05	1.19E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.01E+04	1.32E+05	-1.14E+05	1.16E+05
.80	8.95E+04	7.38E+03	1.82E+05	7.20E+03	1.82E+05	-1.03E+05	1.15E+05

Table K-251. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.90E+04	9.15E+04	-1.25E+05	1.25E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.30E+04	9.78E+04	-1.23E+05	1.25E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.14E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.05E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	7.92E+03	1.81E+05	8.09E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-252. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.93E+04	9.19E+04	-1.26E+05	1.26E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.29E+04	9.82E+04	-1.26E+05	1.26E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.03E+04	1.11E+05	-1.26E+05	1.26E+05
.40	8.56E+04	3.50E+04	1.36E+05	3.51E+04	1.36E+05	-1.26E+05	1.26E+05
.80	8.56E+04	-1.55E+04	1.87E+05	-1.53E+04	1.86E+05	-1.26E+05	1.26E+05

Table K-253. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	8.02E+03	1.81E+05	8.08E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-254. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	8.02E+03	1.81E+05	8.08E+03	1.81E+05	-1.02E+05	1.14E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-255. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-256. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.23E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-33. Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-257. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.97E+04	9.20E+04	-1.24E+05	1.23E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.35E+04	9.82E+04	-1.24E+05	1.23E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.12E+04	1.10E+05	-1.24E+05	1.23E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.65E+04	1.35E+05	-1.24E+05	1.23E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.29E+04	1.84E+05	-1.24E+05	1.23E+05

Table K-258. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.93E+04	9.25E+04	-1.32E+05	1.32E+05
.10	8.58E+04	7.26E+04	9.87E+04	7.30E+04	9.84E+04	-1.28E+05	1.26E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.22E+04	1.09E+05	-1.17E+05	1.17E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.14E+04	1.31E+05	-1.11E+05	1.13E+05
.80	8.95E+04	7.38E+03	1.82E+05	9.04E+03	1.79E+05	-1.01E+05	1.12E+05

Table K-259. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.92E+04	9.14E+04	-1.21E+05	1.22E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.33E+04	9.74E+04	-1.20E+05	1.21E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.21E+04	1.09E+05	-1.17E+05	1.20E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.16E+04	1.33E+05	-1.12E+05	1.17E+05
.80	8.96E+04	7.92E+03	1.81E+05	9.50E+03	1.78E+05	-1.00E+05	1.11E+05

Table K-260. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.31E+04	9.80E+04	-1.25E+05	1.25E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.06E+04	1.11E+05	-1.25E+05	1.25E+05
.40	8.56E+04	3.51E+04	1.36E+05	3.56E+04	1.36E+05	-1.25E+05	1.25E+05
.80	8.56E+04	-1.54E+04	1.87E+05	-1.43E+04	1.85E+05	-1.25E+05	1.25E+05

Table K-261. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.17E+04	-1.24E+05	1.24E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.33E+04	9.79E+04	-1.22E+05	1.23E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.19E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.10E+04	1.34E+05	-1.14E+05	1.19E+05
.80	8.96E+04	8.04E+03	1.81E+05	8.60E+03	1.80E+05	-1.01E+05	1.13E+05

Table K-262. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.17E+04	-1.24E+05	1.24E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.33E+04	9.79E+04	-1.22E+05	1.23E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.19E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.10E+04	1.34E+05	-1.14E+05	1.19E+05
.80	8.96E+04	8.04E+03	1.81E+05	8.60E+03	1.80E+05	-1.01E+05	1.13E+05

Table K-263. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-264. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.23E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-34. Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-265. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.96E+04	9.22E+04	-1.27E+05	1.26E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.32E+04	9.86E+04	-1.27E+05	1.26E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.06E+04	1.11E+05	-1.27E+05	1.26E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.52E+04	1.36E+05	-1.27E+05	1.26E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.54E+04	1.87E+05	-1.27E+05	1.26E+05

Table K-266. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.91E+04	9.27E+04	-1.36E+05	1.36E+05
.10	8.58E+04	7.26E+04	9.88E+04	7.27E+04	9.87E+04	-1.32E+05	1.29E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.20E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.02E+04	1.32E+05	-1.14E+05	1.16E+05
.80	8.95E+04	7.38E+03	1.82E+05	7.37E+03	1.82E+05	-1.03E+05	1.16E+05

Table K-267. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.90E+04	9.16E+04	-1.25E+05	1.26E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.29E+04	9.78E+04	-1.24E+05	1.25E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.14E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.04E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	7.92E+03	1.81E+05	7.97E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-268. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.92E+04	9.19E+04	-1.26E+05	1.26E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.29E+04	9.82E+04	-1.26E+05	1.26E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.03E+04	1.11E+05	-1.26E+05	1.26E+05
.40	8.56E+04	3.50E+04	1.36E+05	3.51E+04	1.36E+05	-1.26E+05	1.26E+05
.80	8.56E+04	-1.55E+04	1.87E+05	-1.54E+04	1.87E+05	-1.26E+05	1.26E+05

Table K-269. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.26E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.35E+05	-1.15E+05	1.20E+05
.80	8.97E+04	8.02E+03	1.81E+05	8.04E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-270. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.26E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.21E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.35E+05	-1.15E+05	1.20E+05
.80	8.97E+04	8.02E+03	1.81E+05	8.04E+03	1.81E+05	-1.02E+05	1.14E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-271. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-272. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.22E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-35. Minimum and maximum of filtered $(F_z^{hst} - \langle F_z^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-273. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.96E+04	9.22E+04	-1.27E+05	1.26E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.32E+04	9.85E+04	-1.27E+05	1.26E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.05E+04	1.11E+05	-1.27E+05	1.26E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.51E+04	1.36E+05	-1.27E+05	1.26E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.57E+04	1.87E+05	-1.27E+05	1.26E+05

Table K-274. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.91E+04	9.27E+04	-1.36E+05	1.35E+05
.10	8.58E+04	7.26E+04	9.88E+04	7.26E+04	9.87E+04	-1.32E+05	1.29E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.15E+04	1.10E+05	-1.21E+05	1.19E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.01E+04	1.32E+05	-1.14E+05	1.16E+05
.80	8.95E+04	7.38E+03	1.82E+05	7.20E+03	1.82E+05	-1.03E+05	1.15E+05

Table K-275. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.90E+04	9.15E+04	-1.25E+05	1.25E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.30E+04	9.78E+04	-1.23E+05	1.25E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.14E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.05E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	7.92E+03	1.81E+05	8.09E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-276. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.93E+04	9.19E+04	-1.26E+05	1.26E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.29E+04	9.82E+04	-1.26E+05	1.26E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.03E+04	1.11E+05	-1.26E+05	1.26E+05
.40	8.56E+04	3.50E+04	1.36E+05	3.51E+04	1.36E+05	-1.26E+05	1.26E+05
.80	8.56E+04	-1.55E+04	1.87E+05	-1.53E+04	1.86E+05	-1.26E+05	1.26E+05

Table K-277. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	8.02E+03	1.81E+05	8.08E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-278. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.32E+04	9.80E+04	-1.24E+05	1.25E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.16E+04	1.10E+05	-1.20E+05	1.23E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.06E+04	1.34E+05	-1.15E+05	1.20E+05
.80	8.96E+04	8.02E+03	1.81E+05	8.08E+03	1.81E+05	-1.02E+05	1.14E+05

Table K-279. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-280. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.23E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-36. Minimum and maximum of filtered $(F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–281. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.96E+04	9.22E+04	7.97E+04	9.20E+04	-1.24E+05	1.23E+05
.10	8.59E+04	7.32E+04	9.86E+04	7.35E+04	9.82E+04	-1.24E+05	1.23E+05
.20	8.59E+04	6.06E+04	1.11E+05	6.12E+04	1.10E+05	-1.24E+05	1.23E+05
.40	8.59E+04	3.53E+04	1.37E+05	3.65E+04	1.35E+05	-1.24E+05	1.23E+05
.80	8.59E+04	-1.54E+04	1.87E+05	-1.29E+04	1.84E+05	-1.24E+05	1.23E+05

Table K–282. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.91E+04	9.27E+04	7.93E+04	9.25E+04	-1.32E+05	1.32E+05
.10	8.58E+04	7.26E+04	9.87E+04	7.30E+04	9.84E+04	-1.28E+05	1.26E+05
.20	8.57E+04	6.15E+04	1.10E+05	6.22E+04	1.09E+05	-1.17E+05	1.17E+05
.40	8.57E+04	4.02E+04	1.32E+05	4.14E+04	1.31E+05	-1.11E+05	1.13E+05
.80	8.95E+04	7.38E+03	1.82E+05	9.04E+03	1.79E+05	-1.01E+05	1.12E+05

Table K–283. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.53E+04	7.90E+04	9.16E+04	7.92E+04	9.14E+04	-1.21E+05	1.22E+05
.10	8.53E+04	7.29E+04	9.78E+04	7.33E+04	9.74E+04	-1.20E+05	1.21E+05
.20	8.55E+04	6.14E+04	1.10E+05	6.21E+04	1.09E+05	-1.17E+05	1.20E+05
.40	8.63E+04	4.03E+04	1.34E+05	4.16E+04	1.33E+05	-1.12E+05	1.17E+05
.80	8.96E+04	7.92E+03	1.81E+05	9.50E+03	1.78E+05	-1.00E+05	1.11E+05

Table K–284. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.56E+04	7.92E+04	9.19E+04	7.93E+04	9.18E+04	-1.25E+05	1.25E+05
.10	8.56E+04	7.29E+04	9.82E+04	7.31E+04	9.80E+04	-1.25E+05	1.25E+05
.20	8.56E+04	6.03E+04	1.11E+05	6.06E+04	1.11E+05	-1.25E+05	1.25E+05
.40	8.56E+04	3.51E+04	1.36E+05	3.56E+04	1.36E+05	-1.25E+05	1.25E+05
.80	8.56E+04	-1.54E+04	1.87E+05	-1.43E+04	1.85E+05	-1.25E+05	1.25E+05

Table K–285. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.17E+04	-1.24E+05	1.24E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.33E+04	9.79E+04	-1.22E+05	1.23E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.19E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.10E+04	1.34E+05	-1.14E+05	1.19E+05
.80	8.96E+04	8.04E+03	1.81E+05	8.60E+03	1.80E+05	-1.01E+05	1.13E+05

Table K–286. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$ Mean (kN)	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.55E+04	7.93E+04	9.18E+04	7.93E+04	9.17E+04	-1.24E+05	1.24E+05
.10	8.56E+04	7.32E+04	9.80E+04	7.33E+04	9.79E+04	-1.22E+05	1.23E+05
.20	8.57E+04	6.16E+04	1.10E+05	6.19E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.65E+04	4.06E+04	1.35E+05	4.10E+04	1.34E+05	-1.14E+05	1.19E+05
.80	8.96E+04	8.04E+03	1.81E+05	8.60E+03	1.80E+05	-1.01E+05	1.13E+05

Table K-287. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-288. Minimum and Maximum of Variables F_z^{hst} and $(F_z^{\text{hst}})^* = (F_z^{\text{hst}} - \langle F_z^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{hst}} \rangle$	Unfiltered F_z^{hst}		Filtered F_z^{hst}		Filtered $(F_z^{\text{hst}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	8.59E+04	7.97E+04	9.21E+04	7.97E+04	9.21E+04	-1.23E+05	1.23E+05
.10	8.60E+04	7.36E+04	9.84E+04	7.38E+04	9.83E+04	-1.22E+05	1.23E+05
.20	8.61E+04	6.20E+04	1.11E+05	6.23E+04	1.10E+05	-1.19E+05	1.22E+05
.40	8.69E+04	4.10E+04	1.35E+05	4.14E+04	1.35E+05	-1.14E+05	1.19E+05
.80	9.03E+04	8.24E+03	1.82E+05	8.63E+03	1.81E+05	-1.02E+05	1.13E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-37. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-289. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	3.50E-02	-5.22E+04	5.22E+04	-5.22E+04	5.22E+04	-1.04E+06	1.04E+06
.10	7.23E-02	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.146	-2.09E+05	2.09E+05	-2.09E+05	2.09E+05	-1.04E+06	1.04E+06
.40	0.302	-4.18E+05	4.18E+05	-4.18E+05	4.17E+05	-1.04E+06	1.04E+06
.80	0.575	-8.36E+05	8.36E+05	-8.36E+05	8.35E+05	-1.04E+06	1.04E+06

Table K-290. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.96E+04	-4.78E+04	5.95E+04	-1.01E+06	1.14E+06
.10	8.68E+03	-8.51E+04	1.14E+05	-8.51E+04	1.14E+05	-9.37E+05	1.05E+06
.20	2.72E+04	-1.32E+05	2.35E+05	-1.32E+05	2.34E+05	-7.94E+05	1.04E+06
.40	7.68E+04	-2.04E+05	4.90E+05	-2.05E+05	4.89E+05	-7.04E+05	1.03E+06
.80	2.33E+05	-2.34E+05	1.00E+06	-2.08E+05	1.00E+06	-5.51E+05	9.60E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K–291. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.55E+04	5.60E+04	-1.00E+06	1.03E+06
.10	6.79E+03	-8.81E+04	1.08E+05	-8.80E+04	1.08E+05	-9.48E+05	1.01E+06
.20	1.74E+04	-1.48E+05	2.12E+05	-1.47E+05	2.12E+05	-8.24E+05	9.71E+05
.40	5.80E+04	-1.94E+05	4.19E+05	-1.94E+05	4.18E+05	-6.30E+05	9.00E+05
.80	1.91E+05	-1.94E+05	8.30E+05	-1.93E+05	8.29E+05	-4.81E+05	7.97E+05

Table K–292. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	3.33E-02	-5.22E+04	5.22E+04	-5.22E+04	5.22E+04	-1.04E+06	1.04E+06
.10	5.86E-02	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.152	-2.09E+05	2.09E+05	-2.09E+05	2.09E+05	-1.04E+06	1.04E+06
.40	0.230	-4.18E+05	4.18E+05	-4.17E+05	4.17E+05	-1.04E+06	1.04E+06
.80	0.525	-8.35E+05	8.35E+05	-8.35E+05	8.35E+05	-1.04E+06	1.04E+06

Table K-293. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-962.	-5.15E+04	5.05E+04	-5.15E+04	5.05E+04	-1.01E+06	1.03E+06
.10	931.	-9.45E+04	1.02E+05	-9.45E+04	1.02E+05	-9.54E+05	1.01E+06
.20	1.11E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.26E+05	9.69E+05
.40	5.10E+04	-2.01E+05	4.09E+05	-2.01E+05	4.09E+05	-6.30E+05	8.94E+05
.80	1.81E+05	-2.01E+05	8.07E+05	-2.02E+05	8.06E+05	-4.79E+05	7.81E+05

Table K-294. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-962.	-5.15E+04	5.05E+04	-5.15E+04	5.05E+04	-1.01E+06	1.03E+06
.10	931.	-9.45E+04	1.02E+05	-9.45E+04	1.02E+05	-9.54E+05	1.01E+06
.20	1.11E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.26E+05	9.69E+05
.40	5.10E+04	-2.01E+05	4.09E+05	-2.01E+05	4.09E+05	-6.30E+05	8.94E+05
.80	1.81E+05	-2.01E+05	8.07E+05	-2.02E+05	8.06E+05	-4.79E+05	7.81E+05

Table K-295. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-296. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	158.	-4.88E+04	5.14E+04	-4.85E+04	5.09E+04	-9.73E+05	1.01E+06
.10	3.57E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.25E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-38. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–297. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-2.41E-03	-5.22E+04	5.22E+04	-5.24E+04	5.20E+04	-1.05E+06	1.04E+06
.10	4.44E-04	-1.04E+05	1.04E+05	-1.05E+05	1.04E+05	-1.05E+06	1.04E+06
.20	2.14E-06	-2.09E+05	2.09E+05	-2.09E+05	2.08E+05	-1.05E+06	1.04E+06
.40	-1.24E-02	-4.18E+05	4.18E+05	-4.19E+05	4.16E+05	-1.05E+06	1.04E+06
.80	8.56E-03	-8.36E+05	8.36E+05	-8.38E+05	8.33E+05	-1.05E+06	1.04E+06

Table K–298. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.96E+04	-4.78E+04	5.93E+04	-1.01E+06	1.13E+06
.10	8.68E+03	-8.51E+04	1.14E+05	-8.52E+04	1.14E+05	-9.39E+05	1.05E+06
.20	2.71E+04	-1.32E+05	2.35E+05	-1.32E+05	2.34E+05	-7.95E+05	1.03E+06
.40	7.69E+04	-2.04E+05	4.90E+05	-2.05E+05	4.88E+05	-7.05E+05	1.03E+06
.80	2.33E+05	-2.10E+05	1.00E+06	-2.07E+05	9.98E+05	-5.49E+05	9.57E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K–299. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.54E+04	5.58E+04	-1.00E+06	1.02E+06
.10	6.78E+03	-8.81E+04	1.08E+05	-8.78E+04	1.08E+05	-9.46E+05	1.01E+06
.20	1.73E+04	-1.47E+05	2.12E+05	-1.47E+05	2.11E+05	-8.22E+05	9.68E+05
.40	5.79E+04	-1.94E+05	4.19E+05	-1.94E+05	4.17E+05	-6.29E+05	8.98E+05
.80	1.91E+05	-1.94E+05	8.30E+05	-1.92E+05	8.27E+05	-4.78E+05	7.95E+05

Table K–300. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	7.03E-02	-5.22E+04	5.22E+04	-5.21E+04	5.21E+04	-1.04E+06	1.04E+06
.10	0.136	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.255	-2.09E+05	2.09E+05	-2.08E+05	2.08E+05	-1.04E+06	1.04E+06
.40	0.596	-4.18E+05	4.18E+05	-4.17E+05	4.17E+05	-1.04E+06	1.04E+06
.80	1.15	-8.35E+05	8.35E+05	-8.34E+05	8.34E+05	-1.04E+06	1.04E+06

Table K-301. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-968.	-5.15E+04	5.05E+04	-5.15E+04	5.04E+04	-1.01E+06	1.03E+06
.10	896.	-9.45E+04	1.02E+05	-9.44E+04	1.02E+05	-9.53E+05	1.01E+06
.20	1.09E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.25E+05	9.69E+05
.40	5.01E+04	-2.01E+05	4.09E+05	-2.01E+05	4.08E+05	-6.28E+05	8.95E+05
.80	1.79E+05	-2.01E+05	8.07E+05	-2.00E+05	8.06E+05	-4.74E+05	7.84E+05

Table K-302. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-968.	-5.15E+04	5.05E+04	-5.15E+04	5.04E+04	-1.01E+06	1.03E+06
.10	896.	-9.45E+04	1.02E+05	-9.44E+04	1.02E+05	-9.53E+05	1.01E+06
.20	1.09E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.25E+05	9.69E+05
.40	5.01E+04	-2.01E+05	4.09E+05	-2.01E+05	4.08E+05	-6.28E+05	8.95E+05
.80	1.79E+05	-2.01E+05	8.07E+05	-2.00E+05	8.06E+05	-4.74E+05	7.84E+05

Table K-303. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-304. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	145.	-4.88E+04	5.14E+04	-4.85E+04	5.08E+04	-9.72E+05	1.01E+06
.10	3.55E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.24E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-39. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K–305. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	5.85E-02	-5.22E+04	5.22E+04	-5.10E+04	5.06E+04	-1.02E+06	1.01E+06
.10	0.109	-1.04E+05	1.04E+05	-1.02E+05	1.01E+05	-1.02E+06	1.01E+06
.20	0.218	-2.09E+05	2.09E+05	-2.04E+05	2.02E+05	-1.02E+06	1.01E+06
.40	0.446	-4.18E+05	4.17E+05	-4.08E+05	4.05E+05	-1.02E+06	1.01E+06
.80	0.905	-8.36E+05	8.35E+05	-8.15E+05	8.09E+05	-1.02E+06	1.01E+06

Table K–306. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.95E+04	-4.65E+04	5.77E+04	-9.85E+05	1.10E+06
.10	8.66E+03	-8.51E+04	1.14E+05	-8.28E+04	1.11E+05	-9.14E+05	1.03E+06
.20	2.71E+04	-1.32E+05	2.34E+05	-1.29E+05	2.28E+05	-7.82E+05	1.00E+06
.40	7.69E+04	-2.04E+05	4.90E+05	-2.03E+05	4.70E+05	-7.01E+05	9.83E+05
.80	2.31E+05	-2.34E+05	1.00E+06	-1.94E+05	9.50E+05	-5.31E+05	8.98E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-307. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.41E+04	5.44E+04	-9.75E+05	9.94E+05
.10	6.78E+03	-8.81E+04	1.08E+05	-8.57E+04	1.05E+05	-9.25E+05	9.79E+05
.20	1.73E+04	-1.48E+05	2.11E+05	-1.44E+05	2.05E+05	-8.09E+05	9.39E+05
.40	5.78E+04	-1.94E+05	4.18E+05	-1.93E+05	4.05E+05	-6.27E+05	8.69E+05
.80	1.91E+05	-1.94E+05	8.29E+05	-1.75E+05	8.03E+05	-4.57E+05	7.66E+05

Table K-308. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	0.113	-5.22E+04	5.22E+04	-5.16E+04	5.16E+04	-1.03E+06	1.03E+06
.10	0.220	-1.04E+05	1.04E+05	-1.03E+05	1.03E+05	-1.03E+06	1.03E+06
.20	0.437	-2.09E+05	2.09E+05	-2.06E+05	2.06E+05	-1.03E+06	1.03E+06
.40	0.902	-4.17E+05	4.17E+05	-4.13E+05	4.13E+05	-1.03E+06	1.03E+06
.80	1.86	-8.35E+05	8.35E+05	-8.25E+05	8.26E+05	-1.03E+06	1.03E+06

Table K-309. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-966.	-5.15E+04	5.05E+04	-5.10E+04	4.99E+04	-1.00E+06	1.02E+06
.10	909.	-9.45E+04	1.02E+05	-9.36E+04	1.01E+05	-9.45E+05	1.00E+06
.20	1.10E+04	-1.54E+05	2.05E+05	-1.53E+05	2.03E+05	-8.20E+05	9.59E+05
.40	5.03E+04	-2.01E+05	4.09E+05	-2.01E+05	4.04E+05	-6.28E+05	8.84E+05
.80	1.79E+05	-2.01E+05	8.06E+05	-1.95E+05	7.98E+05	-4.67E+05	7.73E+05

Table K-310. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-966.	-5.15E+04	5.05E+04	-5.10E+04	4.99E+04	-1.00E+06	1.02E+06
.10	909.	-9.45E+04	1.02E+05	-9.36E+04	1.01E+05	-9.45E+05	1.00E+06
.20	1.10E+04	-1.54E+05	2.05E+05	-1.53E+05	2.03E+05	-8.20E+05	9.59E+05
.40	5.03E+04	-2.01E+05	4.09E+05	-2.01E+05	4.04E+05	-6.28E+05	8.84E+05
.80	1.79E+05	-2.01E+05	8.06E+05	-1.95E+05	7.98E+05	-4.67E+05	7.73E+05

Table K-311. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-312. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	145.	-4.88E+04	5.14E+04	-4.85E+04	5.08E+04	-9.72E+05	1.01E+06
.10	3.55E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.24E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-40. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–313. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	3.50E-02	-5.22E+04	5.22E+04	-5.22E+04	5.22E+04	-1.04E+06	1.04E+06
.10	7.23E-02	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.146	-2.09E+05	2.09E+05	-2.09E+05	2.09E+05	-1.04E+06	1.04E+06
.40	0.302	-4.18E+05	4.18E+05	-4.18E+05	4.17E+05	-1.04E+06	1.04E+06
.80	0.575	-8.36E+05	8.36E+05	-8.36E+05	8.35E+05	-1.04E+06	1.04E+06

Table K–314. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.96E+04	-4.77E+04	5.95E+04	-1.01E+06	1.14E+06
.10	8.68E+03	-8.51E+04	1.14E+05	-8.51E+04	1.14E+05	-9.37E+05	1.05E+06
.20	2.72E+04	-1.32E+05	2.35E+05	-1.32E+05	2.34E+05	-7.94E+05	1.04E+06
.40	7.68E+04	-2.04E+05	4.90E+05	-2.05E+05	4.89E+05	-7.04E+05	1.03E+06
.80	2.33E+05	-2.34E+05	1.00E+06	-2.08E+05	1.00E+06	-5.51E+05	9.60E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K–315. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.55E+04	5.60E+04	-1.00E+06	1.03E+06
.10	6.79E+03	-8.81E+04	1.08E+05	-8.80E+04	1.08E+05	-9.48E+05	1.01E+06
.20	1.74E+04	-1.48E+05	2.12E+05	-1.47E+05	2.12E+05	-8.24E+05	9.71E+05
.40	5.80E+04	-1.94E+05	4.19E+05	-1.94E+05	4.18E+05	-6.30E+05	9.00E+05
.80	1.91E+05	-1.94E+05	8.30E+05	-1.93E+05	8.29E+05	-4.81E+05	7.97E+05

Table K–316. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	3.33E-02	-5.22E+04	5.22E+04	-5.22E+04	5.22E+04	-1.04E+06	1.04E+06
.10	5.86E-02	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.152	-2.09E+05	2.09E+05	-2.09E+05	2.09E+05	-1.04E+06	1.04E+06
.40	0.230	-4.18E+05	4.18E+05	-4.17E+05	4.17E+05	-1.04E+06	1.04E+06
.80	0.525	-8.35E+05	8.35E+05	-8.35E+05	8.35E+05	-1.04E+06	1.04E+06

Table K–317. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-963.	-5.15E+04	5.05E+04	-5.15E+04	5.05E+04	-1.01E+06	1.03E+06
.10	929.	-9.45E+04	1.02E+05	-9.45E+04	1.02E+05	-9.54E+05	1.01E+06
.20	1.11E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.26E+05	9.69E+05
.40	5.10E+04	-2.01E+05	4.09E+05	-2.01E+05	4.09E+05	-6.30E+05	8.94E+05
.80	1.81E+05	-2.01E+05	8.07E+05	-2.02E+05	8.06E+05	-4.79E+05	7.81E+05

Table K–318. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-963.	-5.15E+04	5.05E+04	-5.15E+04	5.05E+04	-1.01E+06	1.03E+06
.10	929.	-9.45E+04	1.02E+05	-9.45E+04	1.02E+05	-9.54E+05	1.01E+06
.20	1.11E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.26E+05	9.69E+05
.40	5.10E+04	-2.01E+05	4.09E+05	-2.01E+05	4.09E+05	-6.30E+05	8.94E+05
.80	1.81E+05	-2.01E+05	8.07E+05	-2.02E+05	8.06E+05	-4.79E+05	7.81E+05

Table K-319. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-320. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	158.	-4.88E+04	5.14E+04	-4.85E+04	5.09E+04	-9.73E+05	1.01E+06
.10	3.57E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.25E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-41. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–321. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-2.41E-03	-5.22E+04	5.22E+04	-5.24E+04	5.20E+04	-1.05E+06	1.04E+06
.10	4.44E-04	-1.04E+05	1.04E+05	-1.05E+05	1.04E+05	-1.05E+06	1.04E+06
.20	2.14E-06	-2.09E+05	2.09E+05	-2.09E+05	2.08E+05	-1.05E+06	1.04E+06
.40	-1.24E-02	-4.18E+05	4.18E+05	-4.19E+05	4.16E+05	-1.05E+06	1.04E+06
.80	8.56E-03	-8.36E+05	8.36E+05	-8.38E+05	8.33E+05	-1.05E+06	1.04E+06

Table K–322. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.96E+04	-4.78E+04	5.93E+04	-1.01E+06	1.13E+06
.10	8.68E+03	-8.51E+04	1.14E+05	-8.52E+04	1.14E+05	-9.39E+05	1.05E+06
.20	2.71E+04	-1.32E+05	2.35E+05	-1.32E+05	2.34E+05	-7.95E+05	1.03E+06
.40	7.69E+04	-2.04E+05	4.90E+05	-2.05E+05	4.88E+05	-7.05E+05	1.03E+06
.80	2.33E+05	-2.10E+05	1.00E+06	-2.07E+05	9.98E+05	-5.49E+05	9.57E+05

Table K-323. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.54E+04	5.58E+04	-1.00E+06	1.02E+06
.10	6.78E+03	-8.81E+04	1.08E+05	-8.78E+04	1.08E+05	-9.46E+05	1.01E+06
.20	1.73E+04	-1.47E+05	2.12E+05	-1.47E+05	2.11E+05	-8.22E+05	9.68E+05
.40	5.79E+04	-1.94E+05	4.19E+05	-1.94E+05	4.17E+05	-6.29E+05	8.98E+05
.80	1.91E+05	-1.94E+05	8.30E+05	-1.92E+05	8.27E+05	-4.78E+05	7.95E+05

Table K-324. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	7.03E-02	-5.22E+04	5.22E+04	-5.21E+04	5.21E+04	-1.04E+06	1.04E+06
.10	0.136	-1.04E+05	1.04E+05	-1.04E+05	1.04E+05	-1.04E+06	1.04E+06
.20	0.255	-2.09E+05	2.09E+05	-2.08E+05	2.08E+05	-1.04E+06	1.04E+06
.40	0.596	-4.18E+05	4.18E+05	-4.17E+05	4.17E+05	-1.04E+06	1.04E+06
.80	1.15	-8.35E+05	8.35E+05	-8.34E+05	8.34E+05	-1.04E+06	1.04E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K–325. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-968.	-5.15E+04	5.05E+04	-5.15E+04	5.04E+04	-1.01E+06	1.03E+06
.10	896.	-9.45E+04	1.02E+05	-9.44E+04	1.02E+05	-9.53E+05	1.01E+06
.20	1.09E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.25E+05	9.69E+05
.40	5.01E+04	-2.01E+05	4.09E+05	-2.01E+05	4.08E+05	-6.28E+05	8.95E+05
.80	1.79E+05	-2.01E+05	8.07E+05	-2.00E+05	8.06E+05	-4.74E+05	7.84E+05

Table K–326. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-968.	-5.15E+04	5.05E+04	-5.15E+04	5.04E+04	-1.01E+06	1.03E+06
.10	896.	-9.45E+04	1.02E+05	-9.44E+04	1.02E+05	-9.53E+05	1.01E+06
.20	1.09E+04	-1.54E+05	2.05E+05	-1.54E+05	2.05E+05	-8.25E+05	9.69E+05
.40	5.01E+04	-2.01E+05	4.09E+05	-2.01E+05	4.08E+05	-6.28E+05	8.95E+05
.80	1.79E+05	-2.01E+05	8.07E+05	-2.00E+05	8.06E+05	-4.74E+05	7.84E+05

Table K-327. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-328. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	145.	-4.88E+04	5.14E+04	-4.85E+04	5.08E+04	-9.72E+05	1.01E+06
.10	3.55E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.24E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-42. Minimum and maximum of filtered $(M_y^{hst} - \langle M_y^{hst} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K–329. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	5.85E-02	-5.22E+04	5.22E+04	-5.10E+04	5.06E+04	-1.02E+06	1.01E+06
.10	0.109	-1.04E+05	1.04E+05	-1.02E+05	1.01E+05	-1.02E+06	1.01E+06
.20	0.218	-2.09E+05	2.09E+05	-2.04E+05	2.02E+05	-1.02E+06	1.01E+06
.40	0.446	-4.18E+05	4.17E+05	-4.08E+05	4.05E+05	-1.02E+06	1.01E+06
.80	0.905	-8.36E+05	8.35E+05	-8.15E+05	8.09E+05	-1.02E+06	1.01E+06

Table K–330. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	2.75E+03	-4.78E+04	5.95E+04	-4.65E+04	5.77E+04	-9.85E+05	1.10E+06
.10	8.66E+03	-8.51E+04	1.14E+05	-8.28E+04	1.11E+05	-9.14E+05	1.03E+06
.20	2.71E+04	-1.32E+05	2.34E+05	-1.29E+05	2.28E+05	-7.82E+05	1.00E+06
.40	7.69E+04	-2.04E+05	4.90E+05	-2.03E+05	4.70E+05	-7.01E+05	9.83E+05
.80	2.31E+05	-2.34E+05	1.00E+06	-1.94E+05	9.50E+05	-5.31E+05	8.98E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-331. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.69E+03	-4.55E+04	5.60E+04	-4.41E+04	5.44E+04	-9.75E+05	9.94E+05
.10	6.78E+03	-8.81E+04	1.08E+05	-8.57E+04	1.05E+05	-9.25E+05	9.79E+05
.20	1.73E+04	-1.48E+05	2.11E+05	-1.44E+05	2.05E+05	-8.09E+05	9.39E+05
.40	5.78E+04	-1.94E+05	4.18E+05	-1.93E+05	4.05E+05	-6.27E+05	8.69E+05
.80	1.91E+05	-1.94E+05	8.29E+05	-1.75E+05	8.03E+05	-4.57E+05	7.66E+05

Table K-332. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	0.113	-5.22E+04	5.22E+04	-5.16E+04	5.16E+04	-1.03E+06	1.03E+06
.10	0.220	-1.04E+05	1.04E+05	-1.03E+05	1.03E+05	-1.03E+06	1.03E+06
.20	0.437	-2.09E+05	2.09E+05	-2.06E+05	2.06E+05	-1.03E+06	1.03E+06
.40	0.902	-4.17E+05	4.17E+05	-4.13E+05	4.13E+05	-1.03E+06	1.03E+06
.80	1.86	-8.35E+05	8.35E+05	-8.25E+05	8.26E+05	-1.03E+06	1.03E+06

Table K-333. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-966.	-5.15E+04	5.05E+04	-5.10E+04	4.99E+04	-1.00E+06	1.02E+06
.10	909.	-9.45E+04	1.02E+05	-9.36E+04	1.01E+05	-9.45E+05	1.00E+06
.20	1.10E+04	-1.54E+05	2.05E+05	-1.53E+05	2.03E+05	-8.20E+05	9.59E+05
.40	5.03E+04	-2.01E+05	4.09E+05	-2.01E+05	4.04E+05	-6.28E+05	8.84E+05
.80	1.79E+05	-2.01E+05	8.06E+05	-1.95E+05	7.98E+05	-4.67E+05	7.73E+05

Table K-334. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-966.	-5.15E+04	5.05E+04	-5.10E+04	4.99E+04	-1.00E+06	1.02E+06
.10	909.	-9.45E+04	1.02E+05	-9.36E+04	1.01E+05	-9.45E+05	1.00E+06
.20	1.10E+04	-1.54E+05	2.05E+05	-1.53E+05	2.03E+05	-8.20E+05	9.59E+05
.40	5.03E+04	-2.01E+05	4.09E+05	-2.01E+05	4.04E+05	-6.28E+05	8.84E+05
.80	1.79E+05	-2.01E+05	8.06E+05	-1.95E+05	7.98E+05	-4.67E+05	7.73E+05

Table K-335. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-336. Minimum and Maximum of Variables M_y^{hst} and $(M_y^{\text{hst}})^* = (M_y^{\text{hst}} - \langle M_y^{\text{hst}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{hst}} \rangle$	Unfiltered M_y^{hst}		Filtered M_y^{hst}		Filtered $(M_y^{\text{hst}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	145.	-4.88E+04	5.14E+04	-4.85E+04	5.08E+04	-9.72E+05	1.01E+06
.10	3.55E+03	-8.79E+04	1.03E+05	-8.71E+04	1.02E+05	-9.07E+05	9.89E+05
.20	1.40E+04	-1.51E+05	2.07E+05	-1.51E+05	2.05E+05	-8.24E+05	9.56E+05
.40	5.55E+04	-1.99E+05	4.16E+05	-1.98E+05	4.12E+05	-6.35E+05	8.92E+05
.80	1.92E+05	-1.99E+05	8.40E+05	-1.95E+05	8.33E+05	-4.84E+05	8.01E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-43. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-337. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.04E-03	-5.43	5.45	-5.42	5.43	-108.	109.
.10	-2.07E-03	-10.9	10.9	-10.8	10.9	-108.	109.
.20	-4.14E-03	-21.7	21.8	-21.7	21.7	-108.	109.
.40	-8.28E-03	-43.5	43.6	-43.4	43.4	-108.	109.
.80	-1.66E-02	-86.9	87.3	-86.7	86.8	-108.	109.

Table K-338. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.04E-03	-5.43	5.45	-5.42	5.43	-108.	109.
.10	-2.07E-03	-10.9	10.9	-10.8	10.9	-108.	109.
.20	-4.14E-03	-21.7	21.8	-21.7	21.7	-108.	109.
.40	-8.28E-03	-43.5	43.6	-43.4	43.4	-108.	109.
.80	-1.66E-02	-86.9	87.3	-86.7	86.8	-108.	109.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-339. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-340. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	4.87E-02	-3.66	3.66	-3.66	3.66	-74.2	72.3
.10	0.195	-7.33	7.33	-7.33	7.33	-75.2	71.3
.20	0.779	-14.7	14.7	-14.6	14.7	-77.1	69.4
.40	3.12	-29.3	29.3	-29.3	29.3	-81.0	65.5
.80	12.5	-58.6	58.8	-58.6	58.8	-88.8	57.9

Table K-341. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	4.87E-02	-3.66	3.66	-3.66	3.66	-74.2	72.3
.10	0.195	-7.33	7.33	-7.33	7.33	-75.2	71.3
.20	0.779	-14.7	14.7	-14.6	14.7	-77.1	69.4
.40	3.12	-29.3	29.3	-29.3	29.3	-81.0	65.5
.80	12.5	-58.6	58.8	-58.6	58.8	-88.8	57.9

Table K-342. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.124	-3.54	3.72	-3.54	3.72	-73.3	71.9
.10	0.442	-6.73	6.79	-6.72	6.78	-71.7	63.4
.20	1.54	-12.2	15.7	-12.2	12.9	-68.5	56.5
.40	5.53	-23.0	38.3	-20.8	32.1	-65.8	66.4
.80	17.7	-69.0	131.	-46.2	115.	-79.9	121.

Table K-343. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-344. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-44. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-345. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.68E-02	-33.6	33.6	-33.5	33.4	-669.	671.
.10	-0.174	-67.3	67.1	-67.1	66.9	-669.	671.
.20	-0.347	-135.	134.	-134.	134.	-669.	671.
.40	-0.695	-269.	269.	-268.	268.	-669.	671.
.80	-1.39	-538.	537.	-537.	535.	-669.	671.

Table K-346. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-8.68E-02	-33.6	33.6	-33.5	33.4	-669.	671.
.10	-0.174	-67.3	67.1	-67.1	66.9	-669.	671.
.20	-0.347	-135.	134.	-134.	134.	-669.	671.
.40	-0.695	-269.	269.	-268.	268.	-669.	671.
.80	-1.39	-538.	537.	-537.	535.	-669.	671.

Table K-347. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-348. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.148	-10.9	10.9	-10.9	10.9	-220.	214.
.10	0.592	-21.8	21.7	-21.7	21.7	-223.	211.
.20	2.37	-43.5	43.5	-43.4	43.4	-229.	205.
.40	9.47	-87.0	87.0	-86.8	86.9	-241.	194.
.80	37.9	-174.	175.	-174.	175.	-264.	171.

Table K-349. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.148	-10.9	10.9	-10.9	10.9	-220.	214.
.10	0.592	-21.8	21.7	-21.7	21.7	-223.	211.
.20	2.37	-43.5	43.5	-43.4	43.4	-229.	205.
.40	9.47	-87.0	87.0	-86.8	86.9	-241.	194.
.80	37.9	-174.	174.	-174.	174.	-264.	171.

Table K-350. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.520	-10.1	11.4	-10.1	11.4	-213.	217.
.10	1.85	-18.6	21.5	-18.6	21.5	-204.	197.
.20	6.62	-30.9	45.8	-30.8	39.4	-187.	164.
.40	23.9	-62.4	106.	-40.3	88.0	-160.	160.
.80	75.5	-170.	435.	-32.5	341.	-135.	332.

Table K–351. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–352. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-45. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-353. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered $(F_x^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-1.14	-111.	107.	-107.	104.	-2.13E+03	2.10E+03
.10	-2.28	-222.	215.	-215.	208.	-2.13E+03	2.10E+03
.20	-4.56	-443.	429.	-430.	416.	-2.13E+03	2.10E+03
.40	-9.13	-886.	859.	-859.	832.	-2.13E+03	2.10E+03
.80	-18.3	-1.77E+03	1.72E+03	-1.72E+03	1.66E+03	-2.13E+03	2.10E+03

Table K-354. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered $(F_x^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-1.14	-111.	107.	-107.	104.	-2.13E+03	2.10E+03
.10	-2.28	-222.	215.	-215.	208.	-2.13E+03	2.10E+03
.20	-4.56	-443.	429.	-430.	416.	-2.13E+03	2.10E+03
.40	-9.13	-886.	859.	-859.	832.	-2.13E+03	2.10E+03
.80	-18.3	-1.77E+03	1.72E+03	-1.72E+03	1.66E+03	-2.13E+03	2.10E+03

Table K-355. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-356. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	2.00	-124.	124.	-122.	123.	-2.48E+03	2.42E+03
.10	8.00	-247.	250.	-244.	247.	-2.52E+03	2.39E+03
.20	32.0	-491.	503.	-484.	499.	-2.58E+03	2.33E+03
.40	128.	-974.	1.03E+03	-959.	1.02E+03	-2.72E+03	2.23E+03
.80	512.	-1.92E+03	2.23E+03	-1.88E+03	2.21E+03	-2.99E+03	2.13E+03

Table K-357. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{rad}})^*$ Max. (kN)
.05	2.00	-124.	124.	-122.	123.	-2.48E+03	2.42E+03
.10	8.00	-246.	250.	-243.	247.	-2.51E+03	2.39E+03
.20	32.0	-491.	503.	-484.	498.	-2.58E+03	2.33E+03
.40	128.	-972.	1.03E+03	-956.	1.02E+03	-2.71E+03	2.23E+03
.80	512.	-1.91E+03	2.21E+03	-1.87E+03	2.20E+03	-2.98E+03	2.10E+03

Table K-358. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{rad}})^*$ Max. (kN)
.05	0.295	-126.	119.	-125.	118.	-2.50E+03	2.35E+03
.10	-4.94	-255.	217.	-252.	214.	-2.47E+03	2.19E+03
.20	-20.0	-519.	384.	-511.	341.	-2.46E+03	1.81E+03
.40	-39.6	-1.08E+03	1.04E+03	-1.06E+03	746.	-2.54E+03	1.96E+03
.80	-23.7	-2.36E+03	3.05E+03	-2.30E+03	2.35E+03	-2.84E+03	2.97E+03

Table K–359. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–360. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-46. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-361. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-0.208	-76.4	78.6	-76.4	78.5	-1.52E+03	1.57E+03
.10	-0.416	-153.	157.	-153.	157.	-1.52E+03	1.57E+03
.20	-0.833	-306.	314.	-305.	314.	-1.52E+03	1.57E+03
.40	-1.67	-611.	629.	-611.	628.	-1.52E+03	1.57E+03
.80	-3.33	-1.22E+03	1.26E+03	-1.22E+03	1.26E+03	-1.52E+03	1.57E+03

Table K-362. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-0.208	-76.4	78.6	-76.4	78.5	-1.52E+03	1.57E+03
.10	-0.416	-153.	157.	-153.	157.	-1.52E+03	1.57E+03
.20	-0.833	-306.	314.	-305.	314.	-1.52E+03	1.57E+03
.40	-1.67	-611.	629.	-611.	628.	-1.52E+03	1.57E+03
.80	-3.33	-1.22E+03	1.26E+03	-1.22E+03	1.26E+03	-1.52E+03	1.57E+03

TASK 1/HEAVE MOTION/MODEL 5613

Table K-363. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-364. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.5	-70.1	-12.7	-70.1	-12.8	-572.	574.
.10	-41.2	-98.4	16.3	-98.4	16.3	-572.	575.
.20	-40.3	-154.	75.2	-154.	75.1	-570.	577.
.40	-36.4	-263.	196.	-263.	196.	-567.	581.
.80	-21.0	-470.	450.	-470.	450.	-561.	589.

Table K-365. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.5	-70.2	-12.8	-70.2	-12.8	-573.	574.
.10	-41.3	-98.5	16.2	-98.5	16.2	-572.	575.
.20	-40.3	-154.	75.1	-154.	75.1	-570.	577.
.40	-36.5	-263.	196.	-263.	196.	-567.	581.
.80	-21.1	-470.	450.	-470.	450.	-561.	589.

Table K-366. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-30.4	-267.	172.	-206.	171.	-3.52E+03	4.03E+03
.10	31.5	-324.	377.	-282.	377.	-3.14E+03	3.45E+03
.20	173.	-426.	801.	-364.	800.	-2.68E+03	3.14E+03
.40	401.	-740.	1.60E+03	-469.	1.58E+03	-2.17E+03	2.94E+03
.80	804.	-1.67E+03	3.36E+03	-772.	2.98E+03	-1.97E+03	2.72E+03

Table K-367. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-368. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-47. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-369. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered $(F_x^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	4.80E-02	-68.9	70.4	-68.6	70.5	-1.37E+03	1.41E+03
.10	9.60E-02	-138.	141.	-137.	141.	-1.37E+03	1.41E+03
.20	0.192	-275.	282.	-274.	282.	-1.37E+03	1.41E+03
.40	0.384	-551.	563.	-548.	564.	-1.37E+03	1.41E+03
.80	0.768	-1.10E+03	1.13E+03	-1.10E+03	1.13E+03	-1.37E+03	1.41E+03

Table K-370. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered $(F_x^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	4.80E-02	-68.9	70.4	-68.6	70.5	-1.37E+03	1.41E+03
.10	9.60E-02	-138.	141.	-137.	141.	-1.37E+03	1.41E+03
.20	0.192	-275.	282.	-274.	282.	-1.37E+03	1.41E+03
.40	0.384	-551.	563.	-548.	564.	-1.37E+03	1.41E+03
.80	0.768	-1.10E+03	1.13E+03	-1.10E+03	1.13E+03	-1.37E+03	1.41E+03

Table K-371. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-372. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.2	-97.6	14.8	-97.5	14.7	-1.13E+03	1.12E+03
.10	-40.3	-153.	71.4	-153.	71.2	-1.13E+03	1.12E+03
.20	-36.6	-264.	186.	-264.	185.	-1.14E+03	1.11E+03
.40	-21.9	-483.	418.	-482.	418.	-1.15E+03	1.10E+03
.80	36.9	-912.	905.	-911.	904.	-1.18E+03	1.08E+03

Table K-373. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-41.3	-97.7	14.9	-97.7	14.8	-1.13E+03	1.12E+03
.10	-40.3	-154.	71.6	-153.	71.5	-1.13E+03	1.12E+03
.20	-36.7	-265.	186.	-264.	186.	-1.14E+03	1.11E+03
.40	-22.0	-484.	419.	-483.	419.	-1.15E+03	1.10E+03
.80	36.9	-914.	908.	-913.	907.	-1.19E+03	1.09E+03

Table K-374. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-33.6	-283.	132.	-243.	131.	-4.18E+03	3.30E+03
.10	27.5	-364.	297.	-295.	296.	-3.22E+03	2.69E+03
.20	159.	-453.	630.	-332.	624.	-2.45E+03	2.33E+03
.40	342.	-1.03E+03	1.21E+03	-439.	1.20E+03	-1.95E+03	2.14E+03
.80	587.	-2.53E+03	2.68E+03	-589.	2.24E+03	-1.47E+03	2.07E+03

Table K-375. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-376. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-48. Minimum and maximum of filtered $(F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-377. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.92	-66.8	67.9	-64.8	60.3	-1.26E+03	1.25E+03
.10	-3.83	-134.	136.	-130.	121.	-1.26E+03	1.25E+03
.20	-7.67	-267.	272.	-259.	241.	-1.26E+03	1.25E+03
.40	-15.3	-534.	543.	-518.	483.	-1.26E+03	1.25E+03
.80	-30.7	-1.07E+03	1.09E+03	-1.04E+03	966.	-1.26E+03	1.25E+03

Table K-378. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.92	-66.8	67.9	-64.8	60.3	-1.26E+03	1.25E+03
.10	-3.83	-134.	136.	-130.	121.	-1.26E+03	1.25E+03
.20	-7.67	-267.	272.	-259.	241.	-1.26E+03	1.25E+03
.40	-15.3	-534.	543.	-518.	483.	-1.26E+03	1.25E+03
.80	-30.7	-1.07E+03	1.09E+03	-1.04E+03	966.	-1.26E+03	1.25E+03

TASK 1/HEAVE MOTION/MODEL 5613

Table K-379. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-380. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-40.0	-124.	40.0	-123.	39.2	-1.65E+03	1.58E+03
.10	-35.2	-206.	121.	-204.	120.	-1.69E+03	1.55E+03
.20	-16.3	-374.	282.	-369.	280.	-1.76E+03	1.48E+03
.40	59.3	-717.	612.	-704.	608.	-1.91E+03	1.37E+03
.80	362.	-1.44E+03	1.46E+03	-1.40E+03	1.45E+03	-2.21E+03	1.36E+03

Table K-381. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{rad}})^*$ Max. (kN)
.05	-39.9	-125.	41.4	-124.	40.6	-1.68E+03	1.61E+03
.10	-35.2	-209.	124.	-207.	122.	-1.72E+03	1.58E+03
.20	-16.3	-380.	288.	-375.	286.	-1.79E+03	1.51E+03
.40	59.3	-731.	625.	-718.	621.	-1.94E+03	1.40E+03
.80	362.	-1.47E+03	1.50E+03	-1.44E+03	1.48E+03	-2.25E+03	1.40E+03

Table K-382. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	F_x^{rad} Max. (kN)	Filtered Min. (kN)	$(F_x^{\text{rad}})^*$ Max. (kN)
.05	-34.7	-324.	102.	-220.	96.2	-3.71E+03	2.62E+03
.10	29.6	-341.	241.	-170.	232.	-2.00E+03	2.03E+03
.20	154.	-374.	505.	-154.	492.	-1.54E+03	1.69E+03
.40	368.	-930.	1.16E+03	-46.9	1.05E+03	-1.04E+03	1.71E+03
.80	964.	-2.06E+03	3.04E+03	-156.	2.40E+03	-1.40E+03	1.80E+03

Table K–383. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–384. Minimum and Maximum of Variables F_x^{rad} and $(F_x^{\text{rad}})^* = (F_x^{\text{rad}} - \langle F_x^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_x^{\text{rad}} \rangle$	Unfiltered F_x^{rad}		Filtered F_x^{rad}		Filtered $(F_x^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-49. Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-385. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-1.79E-02	-626.	626.	-625.	625.	-1.25E+04	1.25E+04
.10	-3.58E-02	-1.25E+03	1.25E+03	-1.25E+03	1.25E+03	-1.25E+04	1.25E+04
.20	-7.15E-02	-2.50E+03	2.50E+03	-2.50E+03	2.50E+03	-1.25E+04	1.25E+04
.40	-0.143	-5.00E+03	5.01E+03	-5.00E+03	5.00E+03	-1.25E+04	1.25E+04
.80	-0.286	-1.00E+04	1.00E+04	-9.99E+03	1.00E+04	-1.25E+04	1.25E+04

Table K-386. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-1.79E-02	-626.	626.	-625.	625.	-1.25E+04	1.25E+04
.10	-3.58E-02	-1.25E+03	1.25E+03	-1.25E+03	1.25E+03	-1.25E+04	1.25E+04
.20	-7.15E-02	-2.50E+03	2.50E+03	-2.50E+03	2.50E+03	-1.25E+04	1.25E+04
.40	-0.143	-5.00E+03	5.01E+03	-5.00E+03	5.00E+03	-1.25E+04	1.25E+04
.80	-0.286	-1.00E+04	1.00E+04	-9.99E+03	1.00E+04	-1.25E+04	1.25E+04

Table K-387. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	4.88E-06	-597.	597.	-596.	596.	-1.19E+04	1.19E+04
.10	-1.86E-05	-1.19E+03	1.19E+03	-1.19E+03	1.19E+03	-1.19E+04	1.19E+04
.20	-7.87E-05	-2.39E+03	2.39E+03	-2.38E+03	2.38E+03	-1.19E+04	1.19E+04
.40	-1.81E-04	-4.77E+03	4.77E+03	-4.77E+03	4.77E+03	-1.19E+04	1.19E+04
.80	-2.31E-04	-9.55E+03	9.55E+03	-9.54E+03	9.54E+03	-1.19E+04	1.19E+04

Table K-388. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	0.463	-353.	353.	-353.	353.	-7.08E+03	7.06E+03
.10	1.85	-707.	707.	-707.	707.	-7.08E+03	7.05E+03
.20	7.41	-1.41E+03	1.41E+03	-1.41E+03	1.41E+03	-7.10E+03	7.03E+03
.40	29.6	-2.83E+03	2.83E+03	-2.83E+03	2.83E+03	-7.14E+03	6.99E+03
.80	119.	-5.66E+03	5.65E+03	-5.65E+03	5.65E+03	-7.22E+03	6.92E+03

Table K–389. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	0.463	-353.	353.	-353.	353.	-7.08E+03	7.06E+03
.10	1.85	-707.	707.	-707.	707.	-7.08E+03	7.05E+03
.20	7.41	-1.41E+03	1.41E+03	-1.41E+03	1.41E+03	-7.10E+03	7.03E+03
.40	29.6	-2.83E+03	2.83E+03	-2.83E+03	2.83E+03	-7.14E+03	6.99E+03
.80	119.	-5.66E+03	5.65E+03	-5.65E+03	5.65E+03	-7.22E+03	6.92E+03

Table K–390. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-0.314	-349.	348.	-349.	348.	-6.97E+03	6.96E+03
.10	-2.56	-689.	676.	-689.	676.	-6.87E+03	6.78E+03
.20	-13.1	-1.35E+03	1.28E+03	-1.35E+03	1.28E+03	-6.70E+03	6.47E+03
.40	-57.4	-2.64E+03	2.36E+03	-2.64E+03	2.35E+03	-6.45E+03	6.02E+03
.80	-326.	-5.36E+03	4.07E+03	-5.36E+03	4.02E+03	-6.29E+03	5.44E+03

TASK 1/HEAVE MOTION/MODEL 5613

Table K–391. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–392. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.55	-551.	544.	-545.	539.	-1.09E+04	1.08E+04
.10	-4.85	-1.09E+03	1.07E+03	-1.07E+03	1.06E+03	-1.07E+04	1.07E+04
.20	-30.9	-2.13E+03	2.05E+03	-2.11E+03	2.02E+03	-1.04E+04	1.02E+04
.40	-112.	-4.07E+03	3.80E+03	-4.04E+03	3.73E+03	-9.83E+03	9.60E+03
.80	-508.	-7.55E+03	7.34E+03	-7.50E+03	6.80E+03	-8.74E+03	9.14E+03

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-50. Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-393. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	3.02	-1.62E+03	1.63E+03	-1.61E+03	1.63E+03	-3.23E+04	3.24E+04
.10	6.05	-3.23E+03	3.26E+03	-3.22E+03	3.25E+03	-3.23E+04	3.24E+04
.20	12.1	-6.47E+03	6.52E+03	-6.44E+03	6.50E+03	-3.23E+04	3.24E+04
.40	24.2	-1.29E+04	1.30E+04	-1.29E+04	1.30E+04	-3.23E+04	3.24E+04
.80	48.4	-2.59E+04	2.61E+04	-2.58E+04	2.60E+04	-3.23E+04	3.24E+04

Table K-394. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	3.02	-1.62E+03	1.63E+03	-1.61E+03	1.63E+03	-3.23E+04	3.24E+04
.10	6.05	-3.23E+03	3.26E+03	-3.22E+03	3.25E+03	-3.23E+04	3.24E+04
.20	12.1	-6.47E+03	6.52E+03	-6.44E+03	6.50E+03	-3.23E+04	3.24E+04
.40	24.2	-1.29E+04	1.30E+04	-1.29E+04	1.30E+04	-3.23E+04	3.24E+04
.80	48.4	-2.59E+04	2.61E+04	-2.58E+04	2.60E+04	-3.23E+04	3.24E+04

Table K–395. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-1.37E-04	-1.40E+03	1.40E+03	-1.40E+03	1.39E+03	-2.79E+04	2.79E+04
.10	-2.54E-04	-2.80E+03	2.80E+03	-2.79E+03	2.79E+03	-2.79E+04	2.79E+04
.20	-5.84E-04	-5.59E+03	5.59E+03	-5.59E+03	5.57E+03	-2.79E+04	2.79E+04
.40	-1.28E-03	-1.12E+04	1.12E+04	-1.12E+04	1.11E+04	-2.79E+04	2.79E+04
.80	-1.30E-03	-2.24E+04	2.24E+04	-2.23E+04	2.23E+04	-2.79E+04	2.79E+04

Table K–396. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	2.03	-1.37E+03	1.37E+03	-1.37E+03	1.37E+03	-2.74E+04	2.73E+04
.10	8.11	-2.74E+03	2.74E+03	-2.73E+03	2.73E+03	-2.74E+04	2.72E+04
.20	32.4	-5.47E+03	5.47E+03	-5.47E+03	5.47E+03	-2.75E+04	2.72E+04
.40	130.	-1.10E+04	1.09E+04	-1.09E+04	1.09E+04	-2.77E+04	2.70E+04
.80	519.	-2.19E+04	2.19E+04	-2.19E+04	2.18E+04	-2.80E+04	2.67E+04

Table K-397. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	2.03	-1.37E+03	1.37E+03	-1.37E+03	1.37E+03	-2.74E+04	2.73E+04
.10	8.11	-2.74E+03	2.74E+03	-2.73E+03	2.73E+03	-2.74E+04	2.72E+04
.20	32.4	-5.47E+03	5.47E+03	-5.47E+03	5.46E+03	-2.75E+04	2.72E+04
.40	130.	-1.10E+04	1.09E+04	-1.09E+04	1.09E+04	-2.77E+04	2.70E+04
.80	519.	-2.19E+04	2.19E+04	-2.19E+04	2.18E+04	-2.80E+04	2.66E+04

Table K-398. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.02E-02	-1.35E+03	1.35E+03	-1.35E+03	1.35E+03	-2.70E+04	2.70E+04
.10	-5.36	-2.67E+03	2.63E+03	-2.66E+03	2.63E+03	-2.66E+04	2.64E+04
.20	-31.8	-5.20E+03	5.02E+03	-5.19E+03	5.01E+03	-2.58E+04	2.52E+04
.40	-158.	-9.95E+03	9.18E+03	-9.94E+03	9.12E+03	-2.44E+04	2.32E+04
.80	-1.11E+03	-1.85E+04	1.30E+04	-1.85E+04	1.27E+04	-2.17E+04	1.72E+04

Table K-399. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-400. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-9.84	-1.32E+03	1.29E+03	-1.31E+03	1.27E+03	-2.59E+04	2.57E+04
.10	-21.9	-2.60E+03	2.55E+03	-2.58E+03	2.52E+03	-2.56E+04	2.54E+04
.20	-88.5	-5.15E+03	4.94E+03	-5.09E+03	4.87E+03	-2.50E+04	2.48E+04
.40	-263.	-9.93E+03	9.26E+03	-9.83E+03	9.12E+03	-2.39E+04	2.35E+04
.80	-1.04E+03	-1.87E+04	1.90E+04	-1.84E+04	1.75E+04	-2.18E+04	2.32E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-51. Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000 \text{ rad/s}$, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154 \text{ m}$.

Table K-401. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-5.85	-4.20E+03	4.18E+03	-4.07E+03	4.06E+03	-8.13E+04	8.12E+04
.10	-11.7	-8.40E+03	8.37E+03	-8.15E+03	8.11E+03	-8.13E+04	8.12E+04
.20	-23.4	-1.68E+04	1.67E+04	-1.63E+04	1.62E+04	-8.13E+04	8.12E+04
.40	-46.8	-3.36E+04	3.35E+04	-3.26E+04	3.25E+04	-8.13E+04	8.12E+04
.80	-93.6	-6.72E+04	6.69E+04	-6.52E+04	6.49E+04	-8.13E+04	8.12E+04

Table K-402. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-5.85	-4.20E+03	4.18E+03	-4.07E+03	4.06E+03	-8.13E+04	8.12E+04
.10	-11.7	-8.40E+03	8.37E+03	-8.15E+03	8.11E+03	-8.13E+04	8.12E+04
.20	-23.4	-1.68E+04	1.67E+04	-1.63E+04	1.62E+04	-8.13E+04	8.12E+04
.40	-46.8	-3.36E+04	3.35E+04	-3.26E+04	3.25E+04	-8.13E+04	8.12E+04
.80	-93.6	-6.72E+04	6.69E+04	-6.52E+04	6.49E+04	-8.13E+04	8.12E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K–403. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-3.40E-05	-4.66E+03	4.66E+03	-4.52E+03	4.53E+03	-9.04E+04	9.06E+04
.10	1.02E-04	-9.33E+03	9.33E+03	-9.04E+03	9.06E+03	-9.04E+04	9.06E+04
.20	-3.03E-04	-1.87E+04	1.87E+04	-1.81E+04	1.81E+04	-9.04E+04	9.06E+04
.40	-1.08E-03	-3.73E+04	3.73E+04	-3.62E+04	3.62E+04	-9.04E+04	9.06E+04
.80	-1.25E-03	-7.46E+04	7.46E+04	-7.23E+04	7.25E+04	-9.04E+04	9.06E+04

Table K–404. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-14.8	-4.52E+03	4.43E+03	-4.47E+03	4.38E+03	-8.91E+04	8.78E+04
.10	-59.3	-9.13E+03	8.76E+03	-9.03E+03	8.66E+03	-8.97E+04	8.72E+04
.20	-237.	-1.86E+04	1.71E+04	-1.84E+04	1.70E+04	-9.09E+04	8.60E+04
.40	-949.	-3.88E+04	3.28E+04	-3.84E+04	3.25E+04	-9.35E+04	8.36E+04
.80	-3.80E+03	-8.39E+04	6.00E+04	-8.27E+04	5.95E+04	-9.87E+04	7.91E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-405. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-14.8	-4.52E+03	4.42E+03	-4.47E+03	4.37E+03	-8.91E+04	8.77E+04
.10	-59.3	-9.15E+03	8.73E+03	-9.04E+03	8.64E+03	-8.98E+04	8.70E+04
.20	-237.	-1.87E+04	1.71E+04	-1.85E+04	1.69E+04	-9.12E+04	8.56E+04
.40	-949.	-3.91E+04	3.25E+04	-3.86E+04	3.22E+04	-9.41E+04	8.29E+04
.80	-3.80E+03	-8.49E+04	5.89E+04	-8.37E+04	5.85E+04	-9.99E+04	7.79E+04

Table K-406. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-21.6	-4.42E+03	4.40E+03	-4.37E+03	4.34E+03	-8.71E+04	8.72E+04
.10	-168.	-8.75E+03	8.45E+03	-8.66E+03	8.30E+03	-8.49E+04	8.47E+04
.20	-659.	-1.72E+04	1.68E+04	-1.70E+04	1.61E+04	-8.19E+04	8.40E+04
.40	-2.11E+03	-3.42E+04	3.46E+04	-3.38E+04	3.21E+04	-7.92E+04	8.54E+04
.80	-6.28E+03	-7.08E+04	7.13E+04	-6.98E+04	6.43E+04	-7.94E+04	8.82E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-407. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-408. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-64.2	-4.73E+03	4.66E+03	-4.68E+03	4.61E+03	-9.24E+04	9.34E+04
.10	-164.	-9.30E+03	9.34E+03	-9.21E+03	9.22E+03	-9.05E+04	9.39E+04
.20	-607.	-1.84E+04	1.88E+04	-1.82E+04	1.84E+04	-8.82E+04	9.53E+04
.40	-1.84E+03	-3.63E+04	3.65E+04	-3.58E+04	3.60E+04	-8.50E+04	9.47E+04
.80	-5.41E+03	-7.55E+04	9.65E+04	-7.48E+04	8.34E+04	-8.67E+04	1.11E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-52. Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-409. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	6.06	-1.69E+03	1.74E+03	-1.69E+03	1.74E+03	-3.39E+04	3.46E+04
.10	12.1	-3.38E+03	3.48E+03	-3.38E+03	3.47E+03	-3.39E+04	3.46E+04
.20	24.2	-6.77E+03	6.95E+03	-6.76E+03	6.94E+03	-3.39E+04	3.46E+04
.40	48.5	-1.35E+04	1.39E+04	-1.35E+04	1.39E+04	-3.39E+04	3.46E+04
.80	97.0	-2.71E+04	2.78E+04	-2.70E+04	2.78E+04	-3.39E+04	3.46E+04

Table K-410. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	6.06	-1.69E+03	1.74E+03	-1.69E+03	1.74E+03	-3.39E+04	3.46E+04
.10	12.1	-3.38E+03	3.48E+03	-3.38E+03	3.47E+03	-3.39E+04	3.46E+04
.20	24.2	-6.77E+03	6.95E+03	-6.76E+03	6.94E+03	-3.39E+04	3.46E+04
.40	48.5	-1.35E+04	1.39E+04	-1.35E+04	1.39E+04	-3.39E+04	3.46E+04
.80	97.0	-2.71E+04	2.78E+04	-2.70E+04	2.78E+04	-3.39E+04	3.46E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-411. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-1.43E-05	-597.	597.	-596.	596.	-1.19E+04	1.19E+04
.10	-1.86E-05	-1.19E+03	1.19E+03	-1.19E+03	1.19E+03	-1.19E+04	1.19E+04
.20	-7.87E-05	-2.39E+03	2.39E+03	-2.38E+03	2.38E+03	-1.19E+04	1.19E+04
.40	-1.81E-04	-4.77E+03	4.77E+03	-4.77E+03	4.77E+03	-1.19E+04	1.19E+04
.80	-2.31E-04	-9.55E+03	9.55E+03	-9.54E+03	9.54E+03	-1.19E+04	1.19E+04

Table K-412. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-3.73E+03	-4.15E+03	-3.31E+03	-4.15E+03	-3.32E+03	-8.35E+03	8.33E+03
.10	-3.73E+03	-4.57E+03	-2.90E+03	-4.57E+03	-2.90E+03	-8.36E+03	8.32E+03
.20	-3.72E+03	-5.40E+03	-2.06E+03	-5.40E+03	-2.06E+03	-8.38E+03	8.30E+03
.40	-3.70E+03	-7.07E+03	-394.	-7.07E+03	-395.	-8.42E+03	8.26E+03
.80	-3.60E+03	-1.04E+04	2.95E+03	-1.04E+04	2.94E+03	-8.51E+03	8.18E+03

Table K–413. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.73E+03	-4.15E+03	-3.32E+03	-4.15E+03	-3.32E+03	-8.35E+03	8.33E+03
.10	-3.73E+03	-4.57E+03	-2.90E+03	-4.57E+03	-2.90E+03	-8.36E+03	8.32E+03
.20	-3.72E+03	-5.40E+03	-2.06E+03	-5.40E+03	-2.06E+03	-8.38E+03	8.30E+03
.40	-3.70E+03	-7.07E+03	-394.	-7.07E+03	-396.	-8.42E+03	8.26E+03
.80	-3.60E+03	-1.04E+04	2.94E+03	-1.04E+04	2.94E+03	-8.51E+03	8.18E+03

Table K–414. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.83E+03	-4.71E+03	-2.96E+03	-4.71E+03	-2.97E+03	-1.76E+04	1.72E+04
.10	-3.89E+03	-5.40E+03	-2.25E+03	-5.39E+03	-2.31E+03	-1.51E+04	1.58E+04
.20	-4.02E+03	-6.73E+03	-987.	-6.73E+03	-1.03E+03	-1.35E+04	1.50E+04
.40	-4.19E+03	-8.94E+03	1.08E+03	-8.93E+03	1.02E+03	-1.19E+04	1.30E+04
.80	-4.50E+03	-1.34E+04	4.15E+03	-1.28E+04	4.03E+03	-1.04E+04	1.07E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K–415. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–416. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.19	-576.	569.	-570.	563.	-1.13E+04	1.13E+04
.10	-19.8	-1.15E+03	1.12E+03	-1.14E+03	1.11E+03	-1.12E+04	1.13E+04
.20	-18.4	-2.28E+03	2.33E+03	-2.25E+03	2.30E+03	-1.11E+04	1.16E+04
.40	-198.	-4.43E+03	3.93E+03	-4.38E+03	3.85E+03	-1.04E+04	1.01E+04
.80	-712.	-8.35E+03	7.55E+03	-8.30E+03	6.98E+03	-9.48E+03	9.62E+03

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-53. Minimum and maximum of filtered $(F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-417. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-19.6	-1.48E+03	1.43E+03	-1.47E+03	1.43E+03	-2.90E+04	2.89E+04
.10	-39.2	-2.95E+03	2.87E+03	-2.93E+03	2.86E+03	-2.90E+04	2.89E+04
.20	-78.4	-5.90E+03	5.73E+03	-5.87E+03	5.71E+03	-2.90E+04	2.89E+04
.40	-157.	-1.18E+04	1.15E+04	-1.17E+04	1.14E+04	-2.90E+04	2.89E+04
.80	-314.	-2.36E+04	2.29E+04	-2.35E+04	2.28E+04	-2.90E+04	2.89E+04

Table K-418. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-19.6	-1.48E+03	1.43E+03	-1.47E+03	1.43E+03	-2.90E+04	2.89E+04
.10	-39.2	-2.95E+03	2.87E+03	-2.93E+03	2.86E+03	-2.90E+04	2.89E+04
.20	-78.4	-5.90E+03	5.73E+03	-5.87E+03	5.71E+03	-2.90E+04	2.89E+04
.40	-157.	-1.18E+04	1.15E+04	-1.17E+04	1.14E+04	-2.90E+04	2.89E+04
.80	-314.	-2.36E+04	2.29E+04	-2.35E+04	2.28E+04	-2.90E+04	2.89E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K–419. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-1.37E-04	-1.40E+03	1.40E+03	-1.40E+03	1.39E+03	-2.79E+04	2.79E+04
.10	-2.54E-04	-2.80E+03	2.80E+03	-2.79E+03	2.79E+03	-2.79E+04	2.79E+04
.20	-5.84E-04	-5.59E+03	5.59E+03	-5.59E+03	5.57E+03	-2.79E+04	2.79E+04
.40	-1.28E-03	-1.12E+04	1.12E+04	-1.12E+04	1.11E+04	-2.79E+04	2.79E+04
.80	-1.30E-03	-2.24E+04	2.24E+04	-2.23E+04	2.23E+04	-2.79E+04	2.79E+04

Table K–420. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-3.73E+03	-5.07E+03	-2.39E+03	-5.07E+03	-2.39E+03	-2.68E+04	2.67E+04
.10	-3.73E+03	-6.41E+03	-1.05E+03	-6.41E+03	-1.06E+03	-2.68E+04	2.67E+04
.20	-3.71E+03	-9.10E+03	1.62E+03	-9.09E+03	1.62E+03	-2.69E+04	2.66E+04
.40	-3.64E+03	-1.45E+04	6.97E+03	-1.45E+04	6.95E+03	-2.71E+04	2.65E+04
.80	-3.35E+03	-2.53E+04	1.76E+04	-2.53E+04	1.76E+04	-2.74E+04	2.62E+04

Table K-421. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.73E+03	-5.07E+03	-2.39E+03	-5.07E+03	-2.39E+03	-2.68E+04	2.67E+04
.10	-3.73E+03	-6.42E+03	-1.05E+03	-6.41E+03	-1.06E+03	-2.69E+04	2.67E+04
.20	-3.71E+03	-9.11E+03	1.62E+03	-9.10E+03	1.62E+03	-2.70E+04	2.66E+04
.40	-3.64E+03	-1.45E+04	6.97E+03	-1.45E+04	6.95E+03	-2.71E+04	2.65E+04
.80	-3.36E+03	-2.53E+04	1.76E+04	-2.53E+04	1.76E+04	-2.74E+04	2.62E+04

Table K-422. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to $L = 154$ m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-3.82E+03	-5.51E+03	-2.04E+03	-5.50E+03	-2.11E+03	-3.36E+04	3.43E+04
.10	-3.90E+03	-7.10E+03	-633.	-7.08E+03	-755.	-3.18E+04	3.15E+04
.20	-4.10E+03	-9.94E+03	1.92E+03	-9.93E+03	1.83E+03	-2.92E+04	2.97E+04
.40	-4.56E+03	-1.52E+04	6.55E+03	-1.51E+04	6.47E+03	-2.63E+04	2.76E+04
.80	-5.98E+03	-2.46E+04	1.57E+04	-2.39E+04	1.52E+04	-2.24E+04	2.65E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K–423. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K–424. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-10.7	-1.35E+03	1.32E+03	-1.34E+03	1.30E+03	-2.66E+04	2.62E+04
.10	-45.7	-2.70E+03	2.60E+03	-2.68E+03	2.57E+03	-2.63E+04	2.62E+04
.20	-52.8	-5.38E+03	5.45E+03	-5.29E+03	5.36E+03	-2.62E+04	2.71E+04
.40	-404.	-1.05E+04	9.53E+03	-1.03E+04	9.15E+03	-2.48E+04	2.39E+04
.80	-1.40E+03	-1.98E+04	1.90E+04	-1.96E+04	1.75E+04	-2.27E+04	2.37E+04

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-54. Minimum and maximum of filtered $(F_z^{rad} - \langle F_z^{rad} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-425. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-9.93	-4.34E+03	4.31E+03	-4.21E+03	4.17E+03	-8.39E+04	8.36E+04
.10	-19.9	-8.68E+03	8.61E+03	-8.41E+03	8.34E+03	-8.39E+04	8.36E+04
.20	-39.7	-1.74E+04	1.72E+04	-1.68E+04	1.67E+04	-8.39E+04	8.36E+04
.40	-79.4	-3.47E+04	3.44E+04	-3.37E+04	3.33E+04	-8.39E+04	8.36E+04
.80	-159.	-6.95E+04	6.89E+04	-6.73E+04	6.67E+04	-8.39E+04	8.36E+04

Table K-426. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
		Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-9.93	-4.34E+03	4.31E+03	-4.21E+03	4.17E+03	-8.39E+04	8.36E+04
.10	-19.9	-8.68E+03	8.61E+03	-8.41E+03	8.34E+03	-8.39E+04	8.36E+04
.20	-39.7	-1.74E+04	1.72E+04	-1.68E+04	1.67E+04	-8.39E+04	8.36E+04
.40	-79.4	-3.47E+04	3.44E+04	-3.37E+04	3.33E+04	-8.39E+04	8.36E+04
.80	-159.	-6.95E+04	6.89E+04	-6.73E+04	6.67E+04	-8.39E+04	8.36E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K–427. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-3.40E-05	-4.66E+03	4.66E+03	-4.52E+03	4.53E+03	-9.04E+04	9.06E+04
.10	1.02E-04	-9.33E+03	9.33E+03	-9.04E+03	9.06E+03	-9.04E+04	9.06E+04
.20	-3.03E-04	-1.87E+04	1.87E+04	-1.81E+04	1.81E+04	-9.04E+04	9.06E+04
.40	-1.08E-03	-3.73E+04	3.73E+04	-3.62E+04	3.62E+04	-9.04E+04	9.06E+04
.80	-1.25E-03	-7.46E+04	7.46E+04	-7.23E+04	7.25E+04	-9.04E+04	9.06E+04

Table K–428. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered $(F_z^{\text{rad}})^*$ Min. (kN)	Max. (kN)
.05	-3.74E+03	-8.58E+03	1.03E+03	-8.52E+03	981.	-9.56E+04	9.45E+04
.10	-3.78E+03	-1.35E+04	5.72E+03	-1.34E+04	5.61E+03	-9.62E+04	9.39E+04
.20	-3.93E+03	-2.36E+04	1.48E+04	-2.34E+04	1.46E+04	-9.73E+04	9.28E+04
.40	-4.52E+03	-4.49E+04	3.21E+04	-4.44E+04	3.17E+04	-9.96E+04	9.07E+04
.80	-6.88E+03	-9.15E+04	6.28E+04	-9.03E+04	6.23E+04	-1.04E+05	8.65E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-429. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-3.74E+03	-8.59E+03	1.03E+03	-8.54E+03	982.	-9.58E+04	9.45E+04
.10	-3.78E+03	-1.35E+04	5.71E+03	-1.34E+04	5.61E+03	-9.65E+04	9.39E+04
.20	-3.93E+03	-2.37E+04	1.48E+04	-2.35E+04	1.46E+04	-9.77E+04	9.26E+04
.40	-4.52E+03	-4.52E+04	3.19E+04	-4.46E+04	3.15E+04	-1.00E+05	9.01E+04
.80	-6.88E+03	-9.25E+04	6.19E+04	-9.13E+04	6.14E+04	-1.06E+05	8.54E+04

Table K-430. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$ Mean (kN)	Unfiltered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	F_z^{rad} Max. (kN)	Filtered Min. (kN)	$(F_z^{\text{rad}})^*$ Max. (kN)
.05	-3.86E+03	-9.06E+03	547.	-8.98E+03	437.	-1.02E+05	8.60E+04
.10	-4.06E+03	-1.37E+04	4.68E+03	-1.36E+04	4.55E+03	-9.52E+04	8.60E+04
.20	-4.72E+03	-2.28E+04	1.31E+04	-2.26E+04	1.24E+04	-8.95E+04	8.58E+04
.40	-6.51E+03	-4.10E+04	3.07E+04	-4.06E+04	2.77E+04	-8.52E+04	8.55E+04
.80	-1.06E+04	-8.01E+04	6.90E+04	-7.91E+04	6.16E+04	-8.55E+04	9.04E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-431. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-432. Minimum and Maximum of Variables F_z^{rad} and $(F_z^{\text{rad}})^* = (F_z^{\text{rad}} - \langle F_z^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle F_z^{\text{rad}} \rangle$	Unfiltered F_z^{rad}		Filtered F_z^{rad}		Filtered $(F_z^{\text{rad}})^*$	
	Mean (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)	Min. (kN)	Max. (kN)
.05	-62.6	-4.79E+03	4.69E+03	-4.75E+03	4.64E+03	-9.37E+04	9.41E+04
.10	-244.	-9.50E+03	9.35E+03	-9.42E+03	9.23E+03	-9.17E+04	9.47E+04
.20	-530.	-1.87E+04	2.00E+04	-1.86E+04	1.96E+04	-9.04E+04	1.00E+05
.40	-2.58E+03	-3.69E+04	3.89E+04	-3.65E+04	3.39E+04	-8.48E+04	9.11E+04
.80	-6.90E+03	-7.67E+04	9.13E+04	-7.58E+04	7.84E+04	-8.61E+04	1.07E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-55. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-433. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-0.826	-6.13E+03	6.14E+03	-6.12E+03	6.13E+03	-1.22E+05	1.23E+05
.10	-1.65	-1.23E+04	1.23E+04	-1.22E+04	1.23E+04	-1.22E+05	1.23E+05
.20	-3.30	-2.45E+04	2.46E+04	-2.45E+04	2.45E+04	-1.22E+05	1.23E+05
.40	-6.60	-4.91E+04	4.91E+04	-4.90E+04	4.90E+04	-1.22E+05	1.23E+05
.80	-13.2	-9.82E+04	9.82E+04	-9.80E+04	9.81E+04	-1.22E+05	1.23E+05

Table K-434. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-0.826	-6.13E+03	6.14E+03	-6.12E+03	6.13E+03	-1.22E+05	1.23E+05
.10	-1.65	-1.23E+04	1.23E+04	-1.22E+04	1.23E+04	-1.22E+05	1.23E+05
.20	-3.30	-2.45E+04	2.46E+04	-2.45E+04	2.45E+04	-1.22E+05	1.23E+05
.40	-6.60	-4.91E+04	4.91E+04	-4.90E+04	4.90E+04	-1.22E+05	1.23E+05
.80	-13.2	-9.82E+04	9.82E+04	-9.80E+04	9.81E+04	-1.22E+05	1.23E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-435. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-7.39E-04	-7.03E+03	7.03E+03	-7.02E+03	7.02E+03	-1.40E+05	1.40E+05
.10	-2.21E-03	-1.41E+04	1.41E+04	-1.40E+04	1.40E+04	-1.40E+05	1.40E+05
.20	-3.90E-03	-2.81E+04	2.81E+04	-2.81E+04	2.81E+04	-1.40E+05	1.40E+05
.40	-8.37E-03	-5.62E+04	5.62E+04	-5.61E+04	5.61E+04	-1.40E+05	1.40E+05
.80	-2.12E-02	-1.12E+05	1.12E+05	-1.12E+05	1.12E+05	-1.40E+05	1.40E+05

Table K-436. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.42	-3.21E+03	3.21E+03	-3.21E+03	3.20E+03	-6.42E+04	6.40E+04
.10	17.7	-6.41E+03	6.41E+03	-6.41E+03	6.41E+03	-6.43E+04	6.39E+04
.20	70.7	-1.28E+04	1.28E+04	-1.28E+04	1.28E+04	-6.45E+04	6.37E+04
.40	283.	-2.57E+04	2.56E+04	-2.57E+04	2.56E+04	-6.48E+04	6.34E+04
.80	1.13E+03	-5.14E+04	5.12E+04	-5.13E+04	5.12E+04	-6.56E+04	6.26E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-437. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	4.42	-3.21E+03	3.21E+03	-3.21E+03	3.20E+03	-6.42E+04	6.40E+04
.10	17.7	-6.41E+03	6.41E+03	-6.41E+03	6.41E+03	-6.43E+04	6.39E+04
.20	70.7	-1.28E+04	1.28E+04	-1.28E+04	1.28E+04	-6.45E+04	6.37E+04
.40	283.	-2.57E+04	2.56E+04	-2.57E+04	2.56E+04	-6.48E+04	6.34E+04
.80	1.13E+03	-5.14E+04	5.12E+04	-5.13E+04	5.12E+04	-6.56E+04	6.26E+04

Table K-438. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-19.8	-3.17E+03	2.99E+03	-3.17E+03	2.99E+03	-6.29E+04	6.01E+04
.10	-147.	-6.25E+03	4.99E+03	-6.25E+03	4.99E+03	-6.11E+04	5.14E+04
.20	-709.	-1.22E+04	9.57E+03	-1.22E+04	8.36E+03	-5.76E+04	4.54E+04
.40	-2.60E+03	-2.37E+04	2.31E+04	-2.37E+04	2.09E+04	-5.27E+04	5.87E+04
.80	-8.23E+03	-4.57E+04	8.01E+04	-4.57E+04	7.09E+04	-4.68E+04	9.89E+04

TASK 1/HEAVE MOTION/MODEL 5613

Table K-439. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-440. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-225.	-7.23E+03	6.30E+03	-7.16E+03	6.24E+03	-1.39E+05	1.29E+05
.10	-522.	-1.42E+04	1.23E+04	-1.40E+04	1.22E+04	-1.35E+05	1.27E+05
.20	-2.27E+03	-2.81E+04	2.26E+04	-2.77E+04	2.17E+04	-1.27E+05	1.20E+05
.40	-6.64E+03	-5.33E+04	4.62E+04	-5.26E+04	3.33E+04	-1.15E+05	1.00E+05
.80	-1.86E+04	-9.79E+04	1.01E+05	-9.64E+04	6.63E+04	-9.72E+04	1.06E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-56. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K–441. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-8.98	-2.22E+04	2.24E+04	-2.22E+04	2.23E+04	-4.43E+05	4.46E+05
.10	-18.0	-4.44E+04	4.48E+04	-4.43E+04	4.46E+04	-4.43E+05	4.46E+05
.20	-35.9	-8.89E+04	8.95E+04	-8.86E+04	8.92E+04	-4.43E+05	4.46E+05
.40	-71.8	-1.78E+05	1.79E+05	-1.77E+05	1.78E+05	-4.43E+05	4.46E+05
.80	-144.	-3.56E+05	3.58E+05	-3.54E+05	3.57E+05	-4.43E+05	4.46E+05

Table K–442. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-8.98	-2.22E+04	2.24E+04	-2.22E+04	2.23E+04	-4.43E+05	4.46E+05
.10	-18.0	-4.44E+04	4.48E+04	-4.43E+04	4.46E+04	-4.43E+05	4.46E+05
.20	-35.9	-8.89E+04	8.95E+04	-8.86E+04	8.92E+04	-4.43E+05	4.46E+05
.40	-71.8	-1.78E+05	1.79E+05	-1.77E+05	1.78E+05	-4.43E+05	4.46E+05
.80	-144.	-3.56E+05	3.58E+05	-3.54E+05	3.57E+05	-4.43E+05	4.46E+05

Table K-443. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-8.92E-04	-1.67E+04	1.67E+04	-1.67E+04	1.67E+04	-3.35E+05	3.33E+05
.10	-3.54E-03	-3.35E+04	3.35E+04	-3.35E+04	3.33E+04	-3.35E+05	3.33E+05
.20	-5.22E-03	-6.69E+04	6.69E+04	-6.69E+04	6.67E+04	-3.35E+05	3.33E+05
.40	-1.02E-02	-1.34E+05	1.34E+05	-1.34E+05	1.33E+05	-3.35E+05	3.33E+05
.80	-1.82E-02	-2.68E+05	2.68E+05	-2.68E+05	2.67E+05	-3.35E+05	3.33E+05

Table K-444. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	11.6	-1.12E+04	1.12E+04	-1.11E+04	1.11E+04	-2.23E+05	2.23E+05
.10	46.4	-2.23E+04	2.23E+04	-2.23E+04	2.23E+04	-2.23E+05	2.22E+05
.20	186.	-4.47E+04	4.46E+04	-4.46E+04	4.45E+04	-2.24E+05	2.22E+05
.40	745.	-8.94E+04	8.91E+04	-8.93E+04	8.90E+04	-2.25E+05	2.21E+05
.80	2.98E+03	-1.79E+05	1.78E+05	-1.79E+05	1.78E+05	-2.27E+05	2.18E+05

Table K-445. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	11.6	-1.12E+04	1.12E+04	-1.11E+04	1.11E+04	-2.23E+05	2.23E+05
.10	46.4	-2.23E+04	2.23E+04	-2.23E+04	2.23E+04	-2.23E+05	2.22E+05
.20	186.	-4.47E+04	4.46E+04	-4.46E+04	4.45E+04	-2.24E+05	2.22E+05
.40	745.	-8.95E+04	8.90E+04	-8.93E+04	8.89E+04	-2.25E+05	2.20E+05
.80	2.98E+03	-1.79E+05	1.78E+05	-1.79E+05	1.77E+05	-2.28E+05	2.18E+05

Table K-446. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-60.5	-1.10E+04	1.05E+04	-1.10E+04	1.05E+04	-2.19E+05	2.11E+05
.10	-484.	-2.17E+04	1.81E+04	-2.17E+04	1.79E+04	-2.12E+05	1.84E+05
.20	-2.30E+03	-4.26E+04	3.02E+04	-4.26E+04	2.83E+04	-2.01E+05	1.53E+05
.40	-8.80E+03	-8.28E+04	7.37E+04	-8.27E+04	6.62E+04	-1.85E+05	1.87E+05
.80	-3.18E+04	-1.61E+05	2.63E+05	-1.61E+05	2.10E+05	-1.61E+05	3.02E+05

Table K-447. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-448. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-594.	-1.69E+04	1.46E+04	-1.68E+04	1.44E+04	-3.24E+05	3.00E+05
.10	-1.31E+03	-3.32E+04	2.89E+04	-3.29E+04	2.84E+04	-3.16E+05	2.97E+05
.20	-5.48E+03	-6.65E+04	5.48E+04	-6.54E+04	5.22E+04	-2.99E+05	2.89E+05
.40	-1.51E+04	-1.27E+05	1.09E+05	-1.25E+05	8.02E+04	-2.75E+05	2.38E+05
.80	-4.03E+04	-2.37E+05	2.51E+05	-2.33E+05	1.67E+05	-2.40E+05	2.59E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-57. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.0$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K-449. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-419.	-5.58E+04	5.47E+04	-5.41E+04	5.31E+04	-1.07E+06	1.07E+06
.10	-838.	-1.12E+05	1.09E+05	-1.08E+05	1.06E+05	-1.07E+06	1.07E+06
.20	-1.68E+03	-2.23E+05	2.19E+05	-2.16E+05	2.12E+05	-1.07E+06	1.07E+06
.40	-3.35E+03	-4.46E+05	4.38E+05	-4.33E+05	4.24E+05	-1.07E+06	1.07E+06
.80	-6.71E+03	-8.93E+05	8.76E+05	-8.65E+05	8.49E+05	-1.07E+06	1.07E+06

Table K-450. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-419.	-5.58E+04	5.47E+04	-5.41E+04	5.31E+04	-1.07E+06	1.07E+06
.10	-838.	-1.12E+05	1.09E+05	-1.08E+05	1.06E+05	-1.07E+06	1.07E+06
.20	-1.68E+03	-2.23E+05	2.19E+05	-2.16E+05	2.12E+05	-1.07E+06	1.07E+06
.40	-3.35E+03	-4.46E+05	4.38E+05	-4.33E+05	4.24E+05	-1.07E+06	1.07E+06
.80	-6.71E+03	-8.93E+05	8.76E+05	-8.65E+05	8.49E+05	-1.07E+06	1.07E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K-451. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-3.39E-03	-6.44E+04	6.44E+04	-6.24E+04	6.26E+04	-1.25E+06	1.25E+06
.10	-7.79E-03	-1.29E+05	1.29E+05	-1.25E+05	1.25E+05	-1.25E+06	1.25E+06
.20	-2.72E-02	-2.58E+05	2.58E+05	-2.50E+05	2.50E+05	-1.25E+06	1.25E+06
.40	-4.37E-02	-5.15E+05	5.15E+05	-4.99E+05	5.01E+05	-1.25E+06	1.25E+06
.80	-5.29E-02	-1.03E+06	1.03E+06	-9.99E+05	1.00E+06	-1.25E+06	1.25E+06

Table K-452. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	16.4	-6.16E+04	6.12E+04	-6.09E+04	6.05E+04	-1.22E+06	1.21E+06
.10	65.4	-1.24E+05	1.22E+05	-1.22E+05	1.21E+05	-1.22E+06	1.21E+06
.20	261.	-2.49E+05	2.42E+05	-2.46E+05	2.39E+05	-1.23E+06	1.20E+06
.40	1.05E+03	-5.06E+05	4.77E+05	-5.00E+05	4.72E+05	-1.25E+06	1.18E+06
.80	4.18E+03	-1.04E+06	9.24E+05	-1.03E+06	9.16E+05	-1.29E+06	1.14E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K-453. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	16.4	-6.16E+04	6.11E+04	-6.09E+04	6.04E+04	-1.22E+06	1.21E+06
.10	65.4	-1.24E+05	1.22E+05	-1.22E+05	1.20E+05	-1.22E+06	1.20E+06
.20	262.	-2.50E+05	2.41E+05	-2.47E+05	2.38E+05	-1.24E+06	1.19E+06
.40	1.05E+03	-5.09E+05	4.73E+05	-5.02E+05	4.69E+05	-1.26E+06	1.17E+06
.80	4.18E+03	-1.05E+06	9.13E+05	-1.04E+06	9.05E+05	-1.31E+06	1.13E+06

Table K-454. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-305.	-6.07E+04	5.85E+04	-6.01E+04	5.76E+04	-1.20E+06	1.16E+06
.10	-2.83E+03	-1.20E+05	1.05E+05	-1.19E+05	1.04E+05	-1.16E+06	1.07E+06
.20	-1.18E+04	-2.35E+05	2.16E+05	-2.32E+05	1.97E+05	-1.10E+06	1.04E+06
.40	-3.78E+04	-4.57E+05	5.84E+05	-4.52E+05	4.43E+05	-1.04E+06	1.20E+06
.80	-1.12E+05	-9.11E+05	1.57E+06	-8.98E+05	1.25E+06	-9.83E+05	1.70E+06

Table K-455. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-456. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.0$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-2.58E+03	-6.38E+04	5.62E+04	-6.33E+04	5.55E+04	-1.21E+06	1.16E+06
.10	-5.89E+03	-1.23E+05	1.15E+05	-1.22E+05	1.12E+05	-1.16E+06	1.18E+06
.20	-2.38E+04	-2.49E+05	2.43E+05	-2.46E+05	2.27E+05	-1.11E+06	1.25E+06
.40	-6.02E+04	-4.71E+05	5.65E+05	-4.62E+05	3.69E+05	-1.00E+06	1.07E+06
.80	-1.09E+05	-9.50E+05	1.83E+06	-9.26E+05	1.10E+06	-1.02E+06	1.51E+06

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-58. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.2079$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

Table K–457. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-36.7	-3.82E+04	3.91E+04	-3.81E+04	3.89E+04	-7.62E+05	7.79E+05
.10	-73.4	-7.64E+04	7.82E+04	-7.63E+04	7.79E+04	-7.62E+05	7.79E+05
.20	-147.	-1.53E+05	1.56E+05	-1.53E+05	1.56E+05	-7.62E+05	7.79E+05
.40	-294.	-3.06E+05	3.13E+05	-3.05E+05	3.11E+05	-7.62E+05	7.79E+05
.80	-587.	-6.11E+05	6.25E+05	-6.10E+05	6.23E+05	-7.62E+05	7.79E+05

Table K–458. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-36.7	-3.82E+04	3.91E+04	-3.81E+04	3.89E+04	-7.62E+05	7.79E+05
.10	-73.4	-7.64E+04	7.82E+04	-7.63E+04	7.79E+04	-7.62E+05	7.79E+05
.20	-147.	-1.53E+05	1.56E+05	-1.53E+05	1.56E+05	-7.62E+05	7.79E+05
.40	-294.	-3.06E+05	3.13E+05	-3.05E+05	3.11E+05	-7.62E+05	7.79E+05
.80	-587.	-6.11E+05	6.25E+05	-6.10E+05	6.23E+05	-7.62E+05	7.79E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-459. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	1.39E-03	-3.62E+04	3.62E+04	-3.61E+04	3.61E+04	-7.23E+05	7.23E+05
.10	5.51E-04	-7.24E+04	7.24E+04	-7.23E+04	7.23E+04	-7.23E+05	7.23E+05
.20	4.71E-03	-1.45E+05	1.45E+05	-1.45E+05	1.45E+05	-7.23E+05	7.23E+05
.40	5.79E-03	-2.90E+05	2.90E+05	-2.89E+05	2.89E+05	-7.23E+05	7.23E+05
.80	7.94E-03	-5.79E+05	5.79E+05	-5.78E+05	5.78E+05	-7.23E+05	7.23E+05

Table K-460. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.07E+04	-2.36E+04	2.32E+03	-2.36E+04	2.31E+03	-2.59E+05	2.60E+05
.10	-1.06E+04	-3.66E+04	1.54E+04	-3.65E+04	1.53E+04	-2.59E+05	2.60E+05
.20	-1.05E+04	-6.23E+04	4.15E+04	-6.23E+04	4.15E+04	-2.59E+05	2.60E+05
.40	-9.83E+03	-1.13E+05	9.43E+04	-1.13E+05	9.42E+04	-2.59E+05	2.60E+05
.80	-7.29E+03	-2.14E+05	2.02E+05	-2.14E+05	2.01E+05	-2.58E+05	2.61E+05

Table K-461. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.07E+04	-2.36E+04	2.31E+03	-2.36E+04	2.30E+03	-2.59E+05	2.60E+05
.10	-1.06E+04	-3.66E+04	1.53E+04	-3.66E+04	1.53E+04	-2.59E+05	2.60E+05
.20	-1.05E+04	-6.23E+04	4.15E+04	-6.23E+04	4.15E+04	-2.59E+05	2.60E+05
.40	-9.84E+03	-1.13E+05	9.43E+04	-1.13E+05	9.42E+04	-2.59E+05	2.60E+05
.80	-7.30E+03	-2.14E+05	2.02E+05	-2.14E+05	2.01E+05	-2.58E+05	2.61E+05

Table K-462. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.50E+04	-4.85E+04	2.59E+04	-4.84E+04	2.08E+04	-6.67E+05	7.16E+05
.10	-2.06E+04	-7.16E+04	4.48E+04	-7.15E+04	3.94E+04	-5.09E+05	6.00E+05
.20	-3.14E+04	-1.16E+05	8.61E+04	-1.16E+05	6.84E+04	-4.21E+05	4.99E+05
.40	-4.59E+04	-1.96E+05	1.56E+05	-1.93E+05	1.33E+05	-3.67E+05	4.48E+05
.80	-6.60E+04	-3.38E+05	2.94E+05	-3.36E+05	2.74E+05	-3.38E+05	4.25E+05

Table K-463. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-464. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.2079$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-242.	-1.02E+04	9.20E+03	-1.01E+04	9.13E+03	-1.97E+05	1.87E+05
.10	-1.42E+03	-2.15E+04	1.84E+04	-2.13E+04	1.82E+04	-1.99E+05	1.96E+05
.20	-1.75E+03	-4.39E+04	4.49E+04	-4.35E+04	4.28E+04	-2.09E+05	2.23E+05
.40	-1.25E+04	-8.64E+04	8.64E+04	-8.56E+04	6.97E+04	-1.83E+05	2.06E+05
.80	-3.45E+04	-1.58E+05	1.82E+05	-1.57E+05	1.53E+05	-1.53E+05	2.34E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-59. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 0.3831$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-465. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-88.2	-3.95E+04	3.90E+04	-3.93E+04	3.84E+04	-7.85E+05	7.71E+05
.10	-176.	-7.90E+04	7.80E+04	-7.87E+04	7.69E+04	-7.85E+05	7.71E+05
.20	-353.	-1.58E+05	1.56E+05	-1.57E+05	1.54E+05	-7.85E+05	7.71E+05
.40	-705.	-3.16E+05	3.12E+05	-3.15E+05	3.08E+05	-7.85E+05	7.71E+05
.80	-1.41E+03	-6.32E+05	6.24E+05	-6.29E+05	6.15E+05	-7.85E+05	7.71E+05

Table K-466. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-88.2	-3.95E+04	3.90E+04	-3.93E+04	3.84E+04	-7.85E+05	7.71E+05
.10	-176.	-7.90E+04	7.80E+04	-7.87E+04	7.69E+04	-7.85E+05	7.71E+05
.20	-353.	-1.58E+05	1.56E+05	-1.57E+05	1.54E+05	-7.85E+05	7.71E+05
.40	-705.	-3.16E+05	3.12E+05	-3.15E+05	3.08E+05	-7.85E+05	7.71E+05
.80	-1.41E+03	-6.32E+05	6.24E+05	-6.29E+05	6.15E+05	-7.85E+05	7.71E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-467. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-3.21E-03	-4.14E+04	4.14E+04	-4.12E+04	4.12E+04	-8.24E+05	8.24E+05
.10	-6.49E-03	-8.27E+04	8.27E+04	-8.24E+04	8.24E+04	-8.24E+05	8.24E+05
.20	-1.28E-02	-1.65E+05	1.65E+05	-1.65E+05	1.65E+05	-8.24E+05	8.24E+05
.40	-1.77E-02	-3.31E+05	3.31E+05	-3.30E+05	3.30E+05	-8.24E+05	8.24E+05
.80	-4.74E-02	-6.62E+05	6.62E+05	-6.60E+05	6.60E+05	-8.24E+05	8.24E+05

Table K-468. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.06E+04	-3.81E+04	1.68E+04	-3.81E+04	1.67E+04	-5.49E+05	5.47E+05
.10	-1.05E+04	-6.55E+04	4.42E+04	-6.54E+04	4.41E+04	-5.50E+05	5.46E+05
.20	-9.79E+03	-1.20E+05	9.92E+04	-1.20E+05	9.91E+04	-5.51E+05	5.44E+05
.40	-7.13E+03	-2.29E+05	2.09E+05	-2.29E+05	2.09E+05	-5.55E+05	5.41E+05
.80	3.51E+03	-4.47E+05	4.32E+05	-4.47E+05	4.31E+05	-5.63E+05	5.34E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-469. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.06E+04	-3.82E+04	1.68E+04	-3.81E+04	1.68E+04	-5.50E+05	5.48E+05
.10	-1.05E+04	-6.56E+04	4.43E+04	-6.55E+04	4.43E+04	-5.51E+05	5.47E+05
.20	-9.79E+03	-1.20E+05	9.95E+04	-1.20E+05	9.93E+04	-5.53E+05	5.46E+05
.40	-7.13E+03	-2.30E+05	2.10E+05	-2.30E+05	2.10E+05	-5.56E+05	5.42E+05
.80	3.51E+03	-4.48E+05	4.33E+05	-4.47E+05	4.32E+05	-5.64E+05	5.36E+05

Table K-470. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.50E+04	-7.00E+04	3.70E+04	-6.97E+04	3.33E+04	-1.10E+06	9.65E+05
.10	-2.14E+04	-1.07E+05	6.36E+04	-1.07E+05	5.60E+04	-8.54E+05	7.74E+05
.20	-3.60E+04	-1.76E+05	1.13E+05	-1.76E+05	9.67E+04	-6.98E+05	6.64E+05
.40	-6.35E+04	-3.00E+05	1.76E+05	-2.98E+05	1.33E+05	-5.86E+05	4.90E+05
.80	-1.24E+05	-5.04E+05	2.29E+05	-4.99E+05	1.84E+05	-4.69E+05	3.85E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-471. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-472. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 0.3831$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-362.	-1.92E+04	1.72E+04	-1.90E+04	1.70E+04	-3.73E+05	3.48E+05
.10	-2.39E+03	-4.04E+04	3.28E+04	-4.00E+04	3.25E+04	-3.76E+05	3.49E+05
.20	-2.91E+03	-8.02E+04	6.84E+04	-7.95E+04	6.61E+04	-3.83E+05	3.45E+05
.40	-2.20E+04	-1.55E+05	1.03E+05	-1.53E+05	8.86E+04	-3.28E+05	2.77E+05
.80	-5.73E+04	-2.84E+05	2.31E+05	-2.81E+05	1.90E+05	-2.80E+05	3.10E+05

TASK 1/HEAVE MOTION/MODEL 5613




Figure K-60. Minimum and maximum of filtered $(M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ vs. (z_a/T) for $\omega = 1.1000$ rad/s, $F_n = 0.3$ in the case of task 1, forced heave motion, and Model 5613 scaled to $L = 154$ m.

TASK 1/HEAVE MOTION/MODEL 5613

Table K-473. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-792.	-4.05E+04	3.94E+04	-3.93E+04	3.81E+04	-7.71E+05	7.78E+05
.10	-1.58E+03	-8.10E+04	7.87E+04	-7.87E+04	7.63E+04	-7.71E+05	7.78E+05
.20	-3.17E+03	-1.62E+05	1.57E+05	-1.57E+05	1.53E+05	-7.71E+05	7.78E+05
.40	-6.34E+03	-3.24E+05	3.15E+05	-3.15E+05	3.05E+05	-7.71E+05	7.78E+05
.80	-1.27E+04	-6.48E+05	6.30E+05	-6.29E+05	6.10E+05	-7.71E+05	7.78E+05

Table K-474. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (AEGIR-2, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

AEGIR-2							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-792.	-4.05E+04	3.94E+04	-3.93E+04	3.81E+04	-7.71E+05	7.78E+05
.10	-1.58E+03	-8.10E+04	7.87E+04	-7.87E+04	7.63E+04	-7.71E+05	7.78E+05
.20	-3.17E+03	-1.62E+05	1.57E+05	-1.57E+05	1.53E+05	-7.71E+05	7.78E+05
.40	-6.34E+03	-3.24E+05	3.15E+05	-3.15E+05	3.05E+05	-7.71E+05	7.78E+05
.80	-1.27E+04	-6.48E+05	6.30E+05	-6.29E+05	6.10E+05	-7.71E+05	7.78E+05

TASK 1/HEAVE MOTION/MODEL 5613

Table K-475. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (FREDYN, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

FREDYN							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-3.41E-03	-8.24E+04	8.24E+04	-7.99E+04	7.97E+04	-1.60E+06	1.59E+06
.10	-6.87E-03	-1.65E+05	1.65E+05	-1.60E+05	1.59E+05	-1.60E+06	1.59E+06
.20	-1.75E-03	-3.30E+05	3.29E+05	-3.20E+05	3.19E+05	-1.60E+06	1.59E+06
.40	-2.71E-02	-6.59E+05	6.59E+05	-6.39E+05	6.38E+05	-1.60E+06	1.59E+06
.80	1.77E-02	-1.32E+06	1.32E+06	-1.28E+06	1.28E+06	-1.60E+06	1.59E+06

Table K-476. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-1, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-1							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.08E+04	-5.33E+04	3.08E+04	-5.28E+04	3.04E+04	-8.41E+05	8.23E+05
.10	-1.11E+04	-9.71E+04	7.12E+04	-9.60E+04	7.04E+04	-8.50E+05	8.15E+05
.20	-1.23E+04	-1.88E+05	1.49E+05	-1.86E+05	1.47E+05	-8.68E+05	7.99E+05
.40	-1.73E+04	-3.85E+05	2.94E+05	-3.80E+05	2.91E+05	-9.07E+05	7.71E+05
.80	-3.73E+04	-8.42E+05	5.67E+05	-8.29E+05	5.60E+05	-9.90E+05	7.47E+05

Table K-477. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-3, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-3							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.08E+04	-5.39E+04	3.13E+04	-5.34E+04	3.09E+04	-8.52E+05	8.33E+05
.10	-1.11E+04	-9.83E+04	7.21E+04	-9.73E+04	7.13E+04	-8.62E+05	8.24E+05
.20	-1.23E+04	-1.91E+05	1.50E+05	-1.89E+05	1.49E+05	-8.83E+05	8.06E+05
.40	-1.73E+04	-3.93E+05	2.96E+05	-3.88E+05	2.93E+05	-9.26E+05	7.77E+05
.80	-3.73E+04	-8.64E+05	5.74E+05	-8.50E+05	5.67E+05	-1.02E+06	7.55E+05

Table K-478. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (LAMP-4, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

LAMP-4							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.52E+04	-7.95E+04	4.47E+04	-7.81E+04	4.19E+04	-1.26E+06	1.14E+06
.10	-2.33E+04	-1.31E+05	7.12E+04	-1.29E+05	5.45E+04	-1.06E+06	7.79E+05
.20	-4.31E+04	-2.40E+05	1.31E+05	-2.35E+05	1.07E+05	-9.59E+05	7.52E+05
.40	-7.99E+04	-4.31E+05	4.16E+05	-4.22E+05	2.61E+05	-8.55E+05	8.53E+05
.80	-1.23E+05	-8.27E+05	1.33E+06	-8.12E+05	9.63E+05	-8.61E+05	1.36E+06

TASK 1/HEAVE MOTION/MODEL 5613

Table K-479. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NFA, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NFA							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	—	—	—	—	—	—	—
.10	—	—	—	—	—	—	—
.20	—	—	—	—	—	—	—
.40	—	—	—	—	—	—	—
.80	—	—	—	—	—	—	—

Table K-480. Minimum and Maximum of Variables M_y^{rad} and $(M_y^{\text{rad}})^* = (M_y^{\text{rad}} - \langle M_y^{\text{rad}} \rangle) / (z_a/T)$ for the case (NSHIPMO, Task 1, Forced Heave Motion, Model 5613 Scaled to L = 154 m, $\omega = 1.1000$ rad/s, $F_n = 0.3$)

NSHIPMO							
(z_a/T)	$\langle M_y^{\text{rad}} \rangle$	Unfiltered M_y^{rad}		Filtered M_y^{rad}		Filtered $(M_y^{\text{rad}})^*$	
	Mean (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)	Min. (kN-m)	Max. (kN-m)
.05	-1.82E+03	-6.15E+04	5.21E+04	-6.08E+04	5.17E+04	-1.18E+06	1.07E+06
.10	-9.10E+03	-1.26E+05	9.92E+04	-1.24E+05	9.74E+04	-1.15E+06	1.06E+06
.20	-1.41E+04	-2.48E+05	2.79E+05	-2.46E+05	2.62E+05	-1.16E+06	1.38E+06
.40	-7.69E+04	-4.65E+05	6.33E+05	-4.55E+05	3.50E+05	-9.46E+05	1.07E+06
.80	-7.02E+04	-8.57E+05	1.49E+06	-8.52E+05	8.49E+05	-9.77E+05	1.15E+06